technology for propulsion at 75 per cent main engine power.

Mechanical recovered waste energy directly coupled to shafts need not be measured, since the effect of the technology is directly reflected in the Vref.

In case of a ship equipped dual-fuel engine or a number of engines, the CFME and SFC ME should be the power weighted average of all the main engines.

.5 PAEeff (i) is the auxiliary power reducti on due to innovative electrical energy efficient technology measured at PME(i).

.6 PAE is the required auxiliary engine power to supply normal

---CHUNK---

SOURCE: MEPC.212(63).pdf
average of all the main engines.

.5 PAEeff (i) is the auxiliary power reducti on due to innovative electrical energy efficient technology measured at PME(i).

.6 PAE is the required auxiliary engine power to supply normal
maximum sea load including necessary power for propulsion machinery/systems and accommodation, e.g. main engine pumps, navigational systems and equipment and living on board, but excluding the power not for propulsion machinery/systems, e.g. thrusters, cargo pumps, cargo gear, ballast pumps, maintaining cargo, e.g. reefers and cargo hold fans, in the condition where the ship engaged in voyage at the speed (Vref) under the condition as mentioned in paragraph 2.2.

.1 For ships with a main engine power of 10,000 kW or above, PAE is defined as:

250)75 . 0(025 . 0 1
) (
1
) 10000(

nPTI
i
i PTInME
i
MEiKWMCRMEAE
P
MCRP

.2 For ships with a main engine power below 10,000 kW, PAE is defined as:

)75 . 0(05 . 0 1
) (
1
) 10000(
nPTI
i
i PTInME
i
MEiKWMCRMEAE
P
MCRP

RESOLUTION MEPC.212(63)
Adopted on 2 March 2012

---CHUNK---

SOURCE: MEPC.212(63).pdf
MCRP

.2 For ships with a main engine power below 10,000 kW, PAE is defined as:

)75 . 0(05 . 0 1
) (
1
) 10000(
nPTI
i
i PTInME
i
MEiKWMCRMEAE
P
MCRP

RESOLUTION MEPC.212(63)
Adopted on 2 March 2012
2012 GUIDELINES ON THE METHOD OF CALCULATION OF THE
ATTAINED ENERGY EFFICIENCY DESIGN INDEX (EEDI) FOR NEW SHIPSMEPC 63/23
Annex 8, page 8

.3 For ship where the P AE value calculated by paragraph 2.5.6.1 or 2.5.6.2 is significantly different from the total power used at normal seagoing, e.g. in cases of passenger ships (see NOTE under the formula of EEDI), the PAE value should be estimated by the consumed electric power (excluding propulsion) in conditions when the ship is engaged in a voyage at reference speed (Vref) as given in the electric power table 1, divided by the average efficiency of the generator(s) weighted by power (see appendix 2).

.6 Vref, Capacity and P should be consistent with each other.

.7 SFC is the certified specific fuel consumption, measured in g/kWh, of the engines. The subscripts ME(i) and AE(i) refer to the main and auxiliary engine(s),

---CHUNK---

SOURCE: MEPC.212(63).pdf
(see appendix 2).

.6 Vref, Capacity and P should be consistent with each other.

.7 SFC is the certified specific fuel consumption, measured in g/kWh, of the engines. The subscripts ME(i) and AE(i) refer to the main and auxiliary engine(s), respectively. For engines certified to the E2 or E3 test cycles of the NO x Technical Code 2008, the engine Specific Fuel Consumption (SFCME(i)) is that recorded in the test report included in a NO x technical file for the engine(s) at 75 per cent of MCR power of its torque rating. For engines certified to the D2 or C1 test cycles of the NO x Technical Code 2008, the engine Specific Fuel Consumption (SFCAE(i)) is that recorded on the test report included in a NO x technical file at the engine(s) 50 per cent of MCR power or torque rating.

The SFC should be corrected to the value corresponding to the ISO standard reference conditions using the standard lower calorific value of the fuel oil (42,700kJ/kg), referring to ISO 15550:2002 and ISO 3046-1:2002.

For ships where the PAE value calculated by paragraphs 2.5.6.1 and 2.5.6.2