is significantly different from the total power used at normal seagoing,

---CHUNK---

SOURCE: MEPC.212(63).pdf
fuel oil (42,700kJ/kg), referring to ISO 15550:2002 and ISO 3046-1:2002.

For ships where the PAE value calculated by paragraphs 2.5.6.1 and 2.5.6.2 is significantly different from the total power used at normal seagoing, e.g. conventional passenger ships, the Specific Fuel Consumption (SFCAE) of the auxiliary generators is that recorded in the test report included in a NOx technical file for the engine(s) at 75 per cent of MCR power of its torque rating.

SFCAE is the power-weighted average among SFC AE(i) of the respective engines i.

For those engines which do not have a test report included in a NO x technical file because its power is below 130 kW, the SFC specified by the manufacturer and endorsed by a competent authority should be used.

At the design stage, in case of unavailability of test report in the NO x file, the SFC specified by the manufacturer and endorsed by a competent authority should be used.

For LNG driven engines of which SFC is measured in kJ/kWh should be corrected to the SFC value of g/kWh using the standard lower calorific value of the LNG (48,000 kJ/kg), referring to the 2006 IPCC Guidelines.

---CHUNK---

SOURCE: MEPC.212(63).pdf
authority should be used.

For LNG driven engines of which SFC is measured in kJ/kWh should be corrected to the SFC value of g/kWh using the standard lower calorific value of the LNG (48,000 kJ/kg), referring to the 2006 IPCC Guidelines.

1 The electric power table should be examined and valida ted by the verifier. W here ambient conditions affect any electrical load in the power table the contractual ambient conditions leading to the maximum design electrical load of the installed system for the ship in general should apply.

.8 fj is a correction factor to account for ship specific design elements:

.1 The power correction factor, fj, for ice-classed ships should be taken as the greater value of fj0 and f j,min as tabulated in Table 1

but not greater than fj,max = 1.0.

For further information on approximate correspondence between
ice classes, see HELCOM Recommendation 25/72.

---CHUNK---

SOURCE: MEPC.212(63).pdf
taken as the greater value of fj0 and f j,min as tabulated in Table 1
but not greater than fj,max = 1.0.

For further information on approximate correspondence between
ice classes, see HELCOM Recommendation 25/72.

Table 1: Correction factor for power f j for ice-classed ships
Ship type fj0
fj,min depending on the ice class
IA Super IA IB IC
Tanker

nME
i
i ME
PP
P
L
1
) (
920 . 1
308 . 0
30 . 0
15 . 0PPL
21 . 0
27 . 0PPL 13 . 045 . 0PPL 06 . 070 . 0PPL
Bulk carrier

nME
i
i ME
PP
P
L
1
) (
754 . 1
639 . 0 09 . 0
47 . 0PPL
07 . 0
58 . 0PPL
04 . 0
73 . 0PPL
02 . 0

87 . 0PPL
General
cargo ship

nME
i
i ME
PP
P
L
1
) (
483 . 2
0227 . 0 16 . 0
31 . 0PPL
12 . 0
43 . 0PPL 09 . 056 . 0PPL 07 . 067 . 0PPL

.2 The factor fj, for shuttle tankers with propulsion redundancy should be fj = 0.77. This correction factors applies to shuttle tankers with propulsion redundancy between 80,000 and 160,000 deadweight. The Shuttle Tankers with Propulsion Redundancy are tankers used for loading of crude oil from offshore installations equipped with dual-engine and twin-propellers need to meet the

---CHUNK---

SOURCE: MEPC.212(63).pdf
propulsion redundancy between 80,000 and 160,000 deadweight. The Shuttle Tankers with Propulsion Redundancy are tankers used for loading of crude oil from offshore installations equipped with dual-engine and twin-propellers need to meet the
requirements for dynamic positioning and redundancy propulsion class notation.

.3 For other ship types, fj should be taken as 1.0.

.9 fw is a non-dimensional coefficient indicating the decrease of speed in representative sea conditions of wave height, wave frequency and wind speed (e.g. Beaufort Scale 6), and is determined as follows:

.1 for attained EEDI calculated under regulations 20 and 21 of MARPOL Annex VI, fw is 1.00;

.2 when fw is calculated according to the subparagraph .2.1 or .2.2 below, the value for attained EEDI calculated by the formula in paragraph 2 using the obtained fw should be referred to as "attained EEDIweather";

.1 fw can be determined by conducting the ship specific simulation on its performance at representative sea conditions. The simulation methodology should be based on the Guidelines developed by the Organization and the

---CHUNK---

SOURCE: MEPC.212(63).pdf
simulation on its performance at representative sea conditions. The simulation methodology should be based on the Guidelines developed by the Organization and the

2 HELCOM Recommendation 25/7 may be found at http://www.helcom.fi.

method and outcome for an individual ship should be verified by the Administration or an organization recognized by the Administration; and

.2 in cases where a simulation is not conducted, fw should be taken from the "Standard fw " table/curve. A "Standard fw "