I:\MEPC\63\23.doc
Other measures

5.36 Development of computer software for the calculation of fuel consumption, for the establishment of an emissions "footprint", to optimize operations, and the establishment of goals for improvement and tracking of progress may be considered.

5.37 Renewable energy sources, such as wind, solar (or photovoltaic) cell technology, have improved enormously in the recent years and should be considered for onboard application.

5.38 In some ports shore power may be available for some ships but this is generally aimed at improving air quality in the port area. If the shore-based power source is carbon efficient, there may be a net efficiency benefit. Ships may consider using onshore power if available.

5.39 Even wind assisted propulsion may be worthy of consideration.

---CHUNK---

SOURCE: MEPC.213(63).pdf
efficient, there may be a net efficiency benefit. Ships may consider using onshore power if available.

5.39 Even wind assisted propulsion may be worthy of consideration.

5.40 Efforts could be made to source fuel of improved quality in order to minimize the amount of fuel required to provide a given power output.

Compatibility of measures

5.41 This document indicates a wide variety of possibilities for energy efficiency improvements for the existing fleet. While there are many options available, they are not necessarily cumulative, are often area and trade dependent and likely to require the agreement and support of a number of different stakeholders if they are to be utilized most effectively.

Age and operational service life of a ship

5.42 All measures identified in this document are potentially cost-effective as a result of high oil prices. Measures previously considered unaffordable or commercially unattractive may now be feasible and worthy of fresh consideration. Clearly, this equation is heavily influenced by the remaining service life of a ship and the cost of fuel.

Trade and sailing area

---CHUNK---

SOURCE: MEPC.213(63).pdf
may now be feasible and worthy of fresh consideration. Clearly, this equation is heavily influenced by the remaining service life of a ship and the cost of fuel.

Trade and sailing area

5.43 The feasibility of many of the measur es described in this guidance will be dependent on the trade and sailing area of the vessel. Sometimes ships will change their trade areas as a result of a change in chartering requirements but this cannot be taken as a general assumption. For example, wind-enhanced power s ources might not be feasible for short sea shipping as these ships generally sail in areas with high traffic densities or in restricted waterways. Another aspect is that the world's oceans and seas each have characteristic conditions and so ships designed for specific routes and trades may not obtain the same benefit by adopting the same measures or combination of measures as other ships. It is also likely that some measures will have a greater or lesser effect in different sailing areas.

5.44 The trade a ship is engaged in may determine the feasibility of the efficiency measures under consideration. For example, ship s that perform services at sea (pipe laying,

---CHUNK---

SOURCE: MEPC.213(63).pdf
5.44 The trade a ship is engaged in may determine the feasibility of the efficiency measures under consideration. For example, ship s that perform services at sea (pipe laying, seismic survey, OSVs, dredgers, etc.) may choose different methods of improving energy efficiency when compared to conventional cargo carriers. The length of voyage may also be an important parameter as may trade specific safety considerations. The pathway to the most efficient combination of measures will be unique to each vessel within each shipping company.
RESOLUTION MEPC.213(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR THE DEVELOPMENT OF A
SHIP ENERGY EFFICIENCY MANAGEMENT PLAN (SEEMP)MEPC 63/23
Annex 9, page 12

I:\MEPC\63\23.doc
APPENDIX

A SAMPLE FORM OF A SHIP EFFICIENCY ENERGY MANAGEMENT PLAN

Name of Vessel: GT:
Vessel Type: Capacity:

Date of
Development:

Developed by:
Implementation
Period:
From:
Until:
Implemented
by:

Planned Date of

Next Evaluation:

1 MEASURES

Energy Efficiency
Measures
Implementation
(including the starting date) Responsible Personnel
Weather Routeing
<Example>
Contracted with [Service

---CHUNK---

SOURCE: MEPC.213(63).pdf
From:
Until:
Implemented
by:

Planned Date of
Next Evaluation:

1 MEASURES

Energy Efficiency
Measures
Implementation
(including the starting date) Responsible Personnel
Weather Routeing
<Example>
Contracted with [Service
providers] to use their
weather routeing system and
start using on-trial basis as
of 1 July 2012.
<Example>
The master is responsible for
selecting the optimum route
based on the information
provided by [Service providers].
Speed Optimization
While the design speed
(85% MCR) is 19.0 kt, the
maximum speed is set
at 17.0 kt as of 1 July 2012.
The master is responsible for
keeping the ship's speed. The
log-book entry should be checked
every day.

2 MONITORING

Description of monitoring tools

3 GOAL

Measurable goals

4 EVALUATION

Procedures of evaluation

(Annexes 10 to 34 to the report are contained in document MEPC 63/23/Add.1)

_____

RESOLUTION MEPC.213(63)
Adopted on 2 March 2012
2012 GUIDELINES FOR THE DEVELOPMENT OF A
SHIP ENERGY EFFICIENCY MANAGEMENT PLAN (SEEMP)RESOLUTION MEPC.213(63)
Adopted on 2 March 2012