4.4.1 In cases where a major conversion is made to a ship, the shipowner should submit to a verifier an application for an Additional Survey with the EEDI Technical File duly revised based on the conversion made and other relevant background documents.

---CHUNK---

SOURCE: MEPC.214(63).pdf
to a verifier an application for an Additional Survey with the EEDI Technical File duly revised based on the conversion made and other relevant background documents.

4.4.2 The background documents should include at least but are not limited to:

.1 documents explaining details of the conversion;

.2 EEDI parameters changed after the conversion and the technical justifications for each respective parameter;

.3 reasons for other changes made in the EEDI Technical File, if any; and

.4 calculated value of the attained EEDI with the calculation summary, which should contain, at a minimum, each value of the calculation parameters and the calculation process used to determine the attained EEDI after the conversion.

4.4.3 The verifier should review the revised EEDI Technical File and other documents submitted and verify the calculation process of the attained EEDI to ensure that it is technically sound and reasonable and follows regulation 20 of MARPOL Annex VI and the EEDI Calculation Guidelines.

4.4.4 For verification of the attained EEDI after a conversion, speed trials of the ship are required, as necessary.

RESOLUTION MEPC.214(63)

---CHUNK---

SOURCE: MEPC.214(63).pdf
EEDI Calculation Guidelines.

4.4.4 For verification of the attained EEDI after a conversion, speed trials of the ship are required, as necessary.

RESOLUTION MEPC.214(63)
Adopted on 2 March 2012
2012 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 63/23/Add.1
Annex 10, page 10

I:\MEPC\63\23-Add-1.doc
APPENDIX 1

SAMPLE OF EEDI TECHNICAL FILE

1 Data

1.1 General information

Shipbuilder JAPAN Shipbuilding Company
Hull No. 12345
IMO No. 94111XX
Kind of ship Bulk carrier

1.2 Principal particulars

Length overall 250.0 m
Length between perpendiculars 240.0 m
Breadth, moulded 40.0 m
Depth, moulded 20.0 m
Summer load line draught, moulded 14.0 m
Deadweight at summer load line
draught 150,000 tons

1.3 Main engine

Manufacturer JAPAN Heavy Industries Ltd.
Type 6J70A
Maximum continuous rating (MCR) 15,000 kW x 80 rpm
SFC at 75% MCR 165.0 g/kWh
Number of set 1
Fuel type Diesel Oil

1.4 Auxiliary engine

Manufacturer JAPAN Diesel Ltd.
Type 5J-200
Maximum continuous rating (MCR) 600 kW x 900 rpm
SFC at 50% MCR 220.0 g/kWh
Number of set 3
Fuel type Diesel Oil

1.5 Ship speed

---CHUNK---

SOURCE: MEPC.214(63).pdf
Number of set 1
Fuel type Diesel Oil

1.4 Auxiliary engine

Manufacturer JAPAN Diesel Ltd.
Type 5J-200
Maximum continuous rating (MCR) 600 kW x 900 rpm
SFC at 50% MCR 220.0 g/kWh

Number of set 3
Fuel type Diesel Oil

1.5 Ship speed

Ship speed in deep water at summer
load line draught at 75% of MCR 14.25 knots

RESOLUTION MEPC.214(63)
Adopted on 2 March 2012
2012 GUIDELINES ON SURVEY AND CERTIFICATION OF THE
ENERGY EFFICIENCY DESIGN INDEX (EEDI)MEPC 63/23/Add.1
Annex 10, page 11

I:\MEPC\63\23-Add-1.doc
2 Power Curves

The power curves estimated at the design stage and modified after the speed trials are
shown in figure 2.1.

Figure 2.1: Power curves

Figure 2.1: Power curves