ANNEX 3

DRY FILM THICKNESS MEASUREMENTS

The following verification check points of DFT should be taken:

.1 one gauge reading per 5 m 2 of flat surface areas;

.2 one gauge reading at 2 to 3 m inte rvals and as close as possible to tank boundaries, but not further than 15 mm from edges of tank boundaries;

.3 longitudinal and transverse stiffener members:

One set of gauge readings as shown below, taken at 2 to 3 m run and not less than two sets between primary support members;

Primary support members



Figure 2

Note: Arrows of diagram indicate critical areas and should be understood to mean indication for both sides.

---CHUNK---

SOURCE: MSC.244(83).pdf
Longitudinal and transverse stiffeners
15 mm (Typical from edges)

Figure 2

Note: Arrows of diagram indicate critical areas and should be understood to mean indication for both sides.

.4 three gauge readings for each set of primary support members and two gauge readings for each set of other members as indicated by the arrows in the diagram;

.5 for primary support members (girders and transverses) one set of gauge readings for 2 to 3 m run as shown in figure 3 above but not less than three sets;

.6 around openings one gauge reading from each side of the opening;

.7 five gauge readings per square metre (m 2) but not less than th ree gauge readings taken at complex areas (i.e. large brackets of primary support members); and

.8 additional spot checks s hould be taken to verify co ating thickness for any area considered necessary by the coating inspector.

***
RESOLUTION MSC.244(83)
(adopted on 5 October 2007)
ADOPTION OF PERFORMANCE STANDARD FOR PROTECTIVE
COATINGS FOR VOID SPACES ON BULK CARRIERS AND OIL TANKERS RESOLUTION MSC.244(83)
(adopted on 5 October 2007)

---CHUNK---

SOURCE: MSC.244(83).pdf
***
RESOLUTION MSC.244(83)
(adopted on 5 October 2007)
ADOPTION OF PERFORMANCE STANDARD FOR PROTECTIVE
COATINGS FOR VOID SPACES ON BULK CARRIERS AND OIL TANKERS RESOLUTION MSC.244(83)
(adopted on 5 October 2007)
ADOPTION OF PERFORMANCE STANDARD FOR PROTECTIVE
COATINGS FOR VOID SPACES ON BULK CARRIERS AND OIL TANKERS

---CHUNK---

SOURCE: MSC.245(83).pdf
RESOLUTION MSC.245(83)
(adopted on 12 October 2007)
RECOMMENDATION ON A STANDARD METHOD FOR
EVALUATING CROSS-FLOODING ARRANGEMENTSMSC 83/28/Add.2

I:\MSC\83\28-Add-2.doc

ANNEX 16

RESOLUTION MSC.245(83)
(adopted on 12 October 2007)

RECOMMENDATION ON A STANDARD METHOD FOR EVALUATING
CROSS-FLOODING ARRANGEMENTS

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution A.266(VIII) entitled Recommendation on a standard method for establishing compliance with the re quirements for cross-flooding arrangements in passenger ships, adopted by the Assembly at its eighth session,

NOTING that the above Recommendation does not include provisions for cross-flooding arrangements other than pipes (i .e., cross-flooding times through ducts) or a provision to ensure adequate air ventilation for efficient cross-flooding (i.e., to account for the restrictive effect of air counter pressure during cross-flooding),

NOTING ALSO the revised SOLAS chapte r II-1 subdivision and damage stability

---CHUNK---

SOURCE: MSC.245(83).pdf
adequate air ventilation for efficient cross-flooding (i.e., to account for the restrictive effect of air counter pressure during cross-flooding),

NOTING ALSO the revised SOLAS chapte r II-1 subdivision and damage stability requirements for passenger and cargo ships, adopted by resolution MSC.216(82),

RECOGNIZING the need to establish a methodology for evaluating cross-flooding arrangements on ships subject to the applicable s ubdivision and damage stability requirements of SOLAS chapter II-1 to ensure uniform treatment of cross-flooding and equalization arrangements,

HAVING CONSIDERED the recommendations made by the Sub-Committee on Stability and Load Lines and on Fishing Vessels Safety at its fiftieth session,

1. ADOPTS the Recommendation on a standa rd method for evalua ting cross-flooding arrangements, the text of which is set out in the Annex to the present resolution;

2. INVITES Governments to apply the a nnexed Recommendation to cross-flooding calculations and to bring the Recommendation to the attention of all parties concerned.

RESOLUTION MSC.245(83)
(adopted on 12 October 2007)
RECOMMENDATION ON A STANDARD METHOD FOR

---CHUNK---

SOURCE: MSC.245(83).pdf
calculations and to bring the Recommendation to the attention of all parties concerned.

RESOLUTION MSC.245(83)
(adopted on 12 October 2007)
RECOMMENDATION ON A STANDARD METHOD FOR

RECOMMENDATION ON A STANDARD METHOD FOR EVALUATING CROSS-FLOODING ARRANGEMENTS

Table of contents Page

1 Definitions 3

2 Formulae 4

3 Air pipe venting criteria 5

4 Alternatives 5