having the route check agai nst hazards based on the planned minimum under keel clearance as specified by the mariner,
checking of the route plan against manoeuvr ing limitation, if avai lable in the INS, based on parameters turning radius, rate of turn (ROT), wheel-over and course changing points, speed, time, ETAs,
drafting and refining the rout e plan against meteorological information if available in the INS.

1 Resolution A.893(21) on Guidelines for voyage planning.

7.3 Task “Route monitoring”

7.3.1 ECDIS performance standards related mandatory functions and data

The INS should provide the route monitoring functions and data as specified in Module A and B in the ECDIS performance standards.

7.3.2 Additional mandatory functions

The INS should provide capability for

---CHUNK---

SOURCE: MSC.252(83).pdf
The INS should provide the route monitoring functions and data as specified in Module A and B in the ECDIS performance standards.

7.3.2 Additional mandatory functions

The INS should provide capability for

optionally overlaying radar video data on th e chart to indicate navigational objects, restraints and hazards to own ship in or der to allow position monitoring evaluation and object identification,
determination of deviations between set values and act ual values for measured under-keel clearance and initiating an under-keel clearance alarm, if fitted,
the alphanumeric display the present valu es of Latitude, Long itude, heading, COG, SOG, STW, under-keel clearance, ROT (m easured or derived from change of heading),
AIS reports of AtoNs,

and if track control is integrated into the INS,

it should be possible to incl ude the planned track and to provide, monitor and display the track related and manoeuvring data.

7.3.3 Optional Functions

For navigational purposes, the display of other r oute-related information on the chart display is permitted, e.g.,

tracked radar targets and AIS targets

---CHUNK---

SOURCE: MSC.252(83).pdf
the track related and manoeuvring data.

7.3.3 Optional Functions

For navigational purposes, the display of other r oute-related information on the chart display is permitted, e.g.,

tracked radar targets and AIS targets
AIS binary and safety-related messages
initiation and monitoring of man-over-board and SAR manoeuvres (search and rescue and man-over-board modes)
NAVTEX
tidal and current data
weather data
ice data.

7.3.4 Search and rescue mode

7.3.4.1 If available it should be possible to select on the route monitoring display a predefined display mode for a “search and rescue” situation, that can be accessed upon simple operator command.

7.3.4.2 In the search and rescue mode a superi mposed graphical presentation of the datum (geographic point, line, or area used as a reference in search planning), initial most probable area for search, commence search point and search pa ttern chosen by the operator (expanding square search pattern, sector search pa ttern or parallel track search pa ttern) with track spacing defined by him should be presented.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)

---CHUNK---

SOURCE: MSC.252(83).pdf
search pattern, sector search pa ttern or parallel track search pa ttern) with track spacing defined by him should be presented.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 11

I:\MSC\83\28-Add-3.doc

7.3.5 Man-over-board (MOB) mode

7.3.5.1 If available it should be possible to select on the route monitoring display a predefined display mode for a “man-over-board” situati on, that can be accessed upon simple operator command.

7.3.5.2 In the man-over-board mode a superim posed graphical presen tation of a operator selectable man-over-board manoeuvre should be presented.

7.3.5.3 The man-over-board position should be memorised by a simple operator action.

7.3.5.4 An urgency manoeuvring procedure should be available at the display taking set and drift into consideration.

7.4 Task “Collision Avoidance”

7.4.1 Radar performance standards related mandatory functions and data

The INS should provide the collision avoidance functions and data as specified in Module A and B of the Radar performance standards.

---CHUNK---

SOURCE: MSC.252(83).pdf
7.4 Task “Collision Avoidance”

7.4.1 Radar performance standards related mandatory functions and data

The INS should provide the collision avoidance functions and data as specified in Module A and B of the Radar performance standards.

7.4.2 Additional mandatory functions

7.4.2.1 It should be possible to present less info rmation of ENC database objects than specified in MSC.232(82) for display base.

7.4.2.2 Target association and target data integration

If target information from multiple sensors/source s (radar and AIS; 2 radar sensors) are provided on one task station:

- the possibility of target asso ciation should be provided fo r mutual monitoring and to avoid the presentation of more than one symbol for the same target,
- the association of AIS and ra dar targets should follow the requirements of resolutions MSC.192(79) and MSC.191(79),
- common criteria should be used for raising target related alerts, e.g., CPA/TCPA.

7.4.2.3 Target identifier

For identical targets unique and identical target identifiers shoul d be used for presentation on all INS displays.

---CHUNK---

SOURCE: MSC.252(83).pdf
common criteria should be used for raising target related alerts, e.g., CPA/TCPA.

7.4.2.3 Target identifier

For identical targets unique and identical target identifiers shoul d be used for presentation on all INS displays.

Where a target from more than one source can be presented on one display the identifier should be amended as required. Amended target identifiers should be used for all INS display presentations.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30

7.4.2.4 Combined radar signals

A display may present combined radar signal s from more than one radar source. The malfunctions of this additional facility should not degrade the presentation of the radar source