alert management,

means should be provided to operate the tasks at least at one of the task stations referred to on paragraph 8.2 or at least at another additional task station at the choice of the bridge team and pilot.

8.4 Remote route planning

---CHUNK---

SOURCE: MSC.252(83).pdf
means should be provided to operate the tasks at least at one of the task stations referred to on paragraph 8.2 or at least at another additional task station at the choice of the bridge team and pilot.

8.4 Remote route planning

For the task “Route planning”, a separate remote task station may be provided.

8.5 The allocation of the tasks to the task stations should be sufficiently flexible, to support all navigational situations, and should be suffi ciently simple to support team working and awareness of operator roles. The selection of the task at the task station should be possible by a simple operator action.

8.6 Track control

If the function of track control is implemented in the INS,

8.6.1 it should be possible to display the planned route graphically on the task stations for:

“Route monitoring”, and/or
“Collision avoidance”.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 15

I:\MSC\83\28-Add-3.doc
8.6.2 the control and operation of this function by the user should be possible via the task stations for:

---CHUNK---

SOURCE: MSC.252(83).pdf
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 15

I:\MSC\83\28-Add-3.doc
8.6.2 the control and operation of this function by the user should be possible via the task stations for:

“Route monitoring”, and/or
“Collision avoidance”.

8.7 Automatic control functions

8.7.1 Task station with control

Only one, clearly indicated task station should be in control of an automatic function and only one task station should at any time be assigned to accept control commands. It should clearly be indicated to the bridge team and pilot, if not otherwise obvious, which task station is in control of these functions.

8.7.2 It should be possible to take over the control from a task station. In this case the set control values and limits should remain unchanged.

8.7.3 The information relevant for the selected control function should be available for continuous display, at least upon a single operator command, and should in be presented when an automatic control function is activated or changed.

8.7.4 Override

8.7.4.1 It should be allowed by a single operat or action to override or by-pass any automated

---CHUNK---

SOURCE: MSC.252(83).pdf
automatic control function is activated or changed.

8.7.4 Override

8.7.4.1 It should be allowed by a single operat or action to override or by-pass any automated function, regardless of the operational mode and the failure status of the INS.

8.7.4.2 The INS should resume automatic functi ons only after an appropriate message and intentional operator action, considering all necessary starting conditions.

9 Functional requirements for displays of INS

9.1 General

9.1.1 The INS should comply with the presentation requirements adopted by the Organization 2.

9.1.2 All essential information should be disp layed clearly and continuously. Additional navigational information may be displayed, but should not mask, obscure or degrade essential information required for the display by its prim ary task, as specified in this performance standards.

9.1.3 The INS should be capable of displayi ng data available from the sensors.

9.1.4 The information should be displayed toge ther with the indicat ion of its source (sensor data, result of calculation or manual in put), unit of measurement and status, including mode.

---CHUNK---

SOURCE: MSC.252(83).pdf
9.1.4 The information should be displayed toge ther with the indicat ion of its source (sensor data, result of calculation or manual in put), unit of measurement and status, including mode.

9.1.5 Display and update of essential information av ailable in the equipment as well as safety related automatic functions should not be inhibited due to operation of the equipment.

2 MSC.191(79), SN/Circ.243.

9.2 Default display configura tions and operational modes

9.2.1 The INS should offer default display confi gurations for the tasks route monitoring and collision avoidance selectable at each task station to provide th e bridge team and pilot with a standardized display. This configuration s hould be accessible by a simple operator action. The basic requirements for these display configurations are specified in Appendix 6.

9.2.2 The INS should provide operational modes for open sea, coastal, confined waters

---CHUNK---

SOURCE: MSC.252(83).pdf
The basic requirements for these display configurations are specified in Appendix 6.

9.2.2 The INS should provide operational modes for open sea, coastal, confined waters (pilotage, harbour berthing, anchorage).

9.2.3 User-defined display modes

It is recommended that the INS provides means to generate pre-defined or operator-defined display modes, that are optimally suitable to the navigation task.

9.2.4 When switching the task from one task station to another, the current display configuration should be maintained.

9.3 Mode and status awareness

9.3.1 The operational mode in use should be clearl y indicated to the bridge team and pilot.

9.3.2 If the mode in use is not the normal mode, to fully perform the functions required for the INS, this should be clearly indicated.

Example of modes other than the normal mode are:

degraded condition modes, in which the INS cannot fully perform all functions

“service modes”
simulation mode
training (familiarization) mode
other modes, in which the INS cannot be used for navigation.

9.3.3 If the system is in a degraded condition this should be sufficiently clear that the bridge

---CHUNK---

SOURCE: MSC.252(83).pdf
“service modes”
simulation mode
training (familiarization) mode
other modes, in which the INS cannot be used for navigation.

9.3.3 If the system is in a degraded condition this should be sufficiently clear that the bridge
team and pilot can understand the nature of the failure and its consequences.

9.3.4 The INS should indicate the operational status of automated functions and integrated components, systems and/or subsystems.

9.4 Information display