SOURCE: MSC.252(83).pdf
requirements should remain applicable.

13.4.2 The INS including the sensors for position, sp eed, heading and depth should be supplied:

.1 from both the main and the emergency source of electrical power with automated changeover through a local distribution board with provision to preclude inadvertent shutdown; and

.2 from a transitional source of electrical power for a duration of not less than 45 s.

Refer to publication IEC 60945.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 22

I:\MSC\83\28-Add-3.doc
13.5 Power interruptions and shutdown

13.5.1 After a power interruption full functiona lity of the INS should be available after recovery of all subsystems. The INS should not increase the recovery time of individual subsystem functions after power restoration.

13.5.2 If subjected to a power interruption the INS should, upon re storation of power, maintain the configuration in use and continue automate d operation, as far as practicable. Automatic

---CHUNK---

SOURCE: MSC.252(83).pdf
subsystem functions after power restoration.

13.5.2 If subjected to a power interruption the INS should, upon re storation of power, maintain the configuration in use and continue automate d operation, as far as practicable. Automatic control functions should only be restored upon confirmation by the operator.

13.6 Communication protocols

13.6.1 Standardized and approved communicati on protocols for interfaces should be used where possible.

13.7 Installation

13.7.1 The INS should be installed so that it can meet the requirements of the relevant International Standards.

13.7.2 The INS should be installed taking into account the guidelines in MSC/Circ.982 and relevant guidance on application of SOLAS regulation V/15, adopted by the Organization.

Module C – Alert management

14 Purpose

14.1 The purpose of the alert management is to enhance the handlin g, distribution and presentation of alerts within an INS.

15 Scope

15.1 To enhance the safety of navigation these performance standards provide requirements for the treatment of alerts within an INS and its associated individual operational/

---CHUNK---

SOURCE: MSC.252(83).pdf
presentation of alerts within an INS.

15 Scope

15.1 To enhance the safety of navigation these performance standards provide requirements for the treatment of alerts within an INS and its associated individual operational/ functional-modules and sensor/source-modules.

15.2 The alert management harmonizes the prior ity, classification, handling, distribution and presentation of alerts, to enable the bridge team to devote full a ttention to the safe navigation of the ship and to immediately identify any abnormal situation requiring action to maintain the safe navigation of the ship.

15.3 These performance standards specify a cen tral alert management HMI to support the bridge team in the immediate id entification of any abnormal situat ion, of the source and reason for the abnormal situation and support the bridge team in its decisions for the necessary actions to be taken.

Refer to publication IEC 61162.

---CHUNK---

SOURCE: MSC.252(83).pdf
Refer to publication IEC 61162.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 23

I:\MSC\83\28-Add-3.doc
15.4 The alert management architecture and th e acknowledgement concep t specified, avoid unnecessary distraction of the bridge team by redundant and superfluous audible and visual alarm announcements and reduces the cognitive load on the operator by minimizing the information presented to which is necessary to assess the situation.

15.5 The alert management should support the proper application of SOLAS regulation V/15.

15.6 The architecture of the module of the perfor mance standards is kept extendable to allow to include further alerts on the bridge and the development of performance standards for a bridge alert management.

16 Application

16.1 These performance standards ar e applicable to any navigational aid within an INS and its associated individual operational/functional-modules and sensor/source-modules.

16.2 In addition to meeting the requirements of these performance standards the INS alert

---CHUNK---

SOURCE: MSC.252(83).pdf
associated individual operational/functional-modules and sensor/source-modules.

16.2 In addition to meeting the requirements of these performance standards the INS alert management should comply with the relevant requirements of the Organization3.

16.3 The general principles of these standards as described in paragraphs 19 and 20 of these performance standards should apply to all alerts presented on the bridge, as far as practicable.

17 Definitions

For the purpose of these standards the definitions in Appendix 1 apply.

18 General requirements

18.1 The alert management should provide:

the means used to draw the attention of the bridge team to the existence of abnormal situations,
the means to enable the bridge team to identify and address that condition,
the means for the bridge team and pilot to assess the urgency of different abnormal situations in cases where more than one abnormal situation has to be handled,
the means to enable the bridge team to handle alert announcements, and
the means to manage all alert related stat es in a distributed system structure in consistent manner.

---CHUNK---

SOURCE: MSC.252(83).pdf
the means to enable the bridge team to handle alert announcements, and
the means to manage all alert related stat es in a distributed system structure in consistent manner.

18.2 If practicable, there should be not more than one alert fo r one situation that requires attention.

18.3 The alert management should as a minimum be able to handle a ll alerts required by performance standards adopted by the Organization for navigational equipment comprised by the INS or connected to the INS. The alert management should have the capability to handle all other alerts of navigational equipment comprised by the INS or connected to the INS in identical manner and should incorporate all alerts that are critical to the safety of navigation.

3 MSC.128(75), MSC.191(79).

18.4 The logical architecture of the alert mana gement and the handling concept for alerts

---CHUNK---