18.4 The logical architecture of the alert mana gement and the handling concept for alerts should provide the capability to minimize the number of alerts especially those on a high priority level (e.g. using system knowledge from redundancy concepts inside INS and evaluating inherent necessities for alerts against navigational situat ions, operational modes or activated navigational functions).

18.5 It should be possible to provide the centr al alert management HMI at least on the navigating and manoeuvring workstation and allowing the handling by the bridge team.

18.6 The audible announcement of alerts should en hance the guidance of the bridge team to the task stations or displays which are directly assigned to the function generating the alert and presenting the cause of the announcement and related information for decision support, e.g., dangerous target alarms should appear and have to be acknowledged at the workstation where the collision avoidance function is provided.

---CHUNK---

SOURCE: MSC.252(83).pdf
presenting the cause of the announcement and related information for decision support, e.g., dangerous target alarms should appear and have to be acknowledged at the workstation where the collision avoidance function is provided.

18.7 As alerts can be displayed at several locations , the system should be consistent as far as practicable with respect to how alerts are displayed, silen ced and acknowledged at any one task station of the INS.

19 Priorities and categories

19.1 Priorities of alerts

19.1.1 The alert management should distinguis h between the three priorities listed:

Alarms
Warnings and
Cautions

19.1.2 Alarms should indicate conditions requiri ng immediate attention and action by the bridge team.

19.1.3 Warnings should indicate changed conditions and should be presented for precautionary reasons which are not immediately hazardous but which may become so, if no action is taken.

19.1.4 Cautions should indicate a condition wh ich does not warrant an alarm or warning condition, but still requires attentio n and out of the ordinary consid eration of the situation or of given information.

---CHUNK---

SOURCE: MSC.252(83).pdf
19.1.4 Cautions should indicate a condition wh ich does not warrant an alarm or warning condition, but still requires attentio n and out of the ordinary consid eration of the situation or of given information.

19.1.5 Alerts additional to the alerts required by the organization shoul d be assigned to an priority level using the criteria for classification.

19.2 Criteria for classification of alerts

19.2.1 Criteria for classi fication of alarms:

conditions requiring immediate attention and action by the br idge team to avoid any kind of hazardous situation and to maintain the safe navigation of the ship
or escalation required as alarm from a not acknowledged warning.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 25

I:\MSC\83\28-Add-3.doc

19.2.2 Criteria for classification of warnings:

Conditions or situations whic h require immediate attenti on for precautionary reasons, to make the bridge team aware of conditi ons which are not immediately hazardous, but may become so.

---CHUNK---

SOURCE: MSC.252(83).pdf
19.2.2 Criteria for classification of warnings:

Conditions or situations whic h require immediate attenti on for precautionary reasons, to make the bridge team aware of conditi ons which are not immediately hazardous, but may become so.

19.2.3 Criteria for classification of cautions:

awareness of a condition wh ich still requires atten tion out of the ordinary consideration of the situation or of given information.

19.3 Categories of alerts

19.3.1 Alerts should be separated for the alert ha ndling in INS into two categories of alerts:

19.3.1.1 Category A alerts

Category A alerts are specified as alerts where graphical e.g. ra dar, ECDIS, information at the task station directly assigned to the function generating the alert is necessary, as decision support

for the evaluation the alert related condition.

Category A alerts should include alerts indicating:

danger of collision
danger of grounding.

19.3.1.2 Category B alerts

Category B alerts are specified as alerts where no additional information for decision support is necessary besides the information which can be pr esented at the central alert management HMI.

---CHUNK---

SOURCE: MSC.252(83).pdf
19.3.1.2 Category B alerts

Category B alerts are specified as alerts where no additional information for decision support is necessary besides the information which can be pr esented at the central alert management HMI. Category B alerts are all alerts not falling under Category A.

19.4 A classification in priorities and categorie s of alerts for INS and for alerts of the individual performance standards is attached as Appendix 5.

20 State of alerts

20.1 General

20.1.1 The presentation of alarms and warnings is defined in the performance standards for presentation of navigation -related information on shipborne navigational displays (resolution MSC.191(79)).

20.1.2 The state of an alert should be unambiguous for the alert management, the INS and all associated operational and sensor/source displays.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 26

I:\MSC\83\28-Add-3.doc
20.2 Alarms

20.2.1 The alert management should distinguish be tween different announcement states of each individual alarm:

---CHUNK---

SOURCE: MSC.252(83).pdf
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 26

20.2 Alarms

20.2.1 The alert management should distinguish be tween different announcement states of each individual alarm:

unacknowledged alarm
acknowledged alarm.

20.2.2 When an alarm condition is detected, it should be indicated as unacknowledged alarm:

(a) initiate an audible signal, accomp anied by the visual alarm announcement;

(b) provide a message of sufficient detail to enable the bridge team to identify and address the alarm condition;

(c) may be accompanied by speech outpu t presented at least in English.

20.2.3 An unacknowledged alarm should be clearl y distinguishable from those existing and already acknowledged. Unacknowledged alarms should be indicated flashing and by an audible signal.