20.2.4 The characteristics of the audible alarm signal, whether used singly or in combination with speech, should be such that there is no possib ility of mistaking it for the audible signal used for a warning.

20.2.5 It should be possible to temporarily si lence alarms. If an alarm is not acknowledged

---CHUNK---

SOURCE: MSC.252(83).pdf
with speech, should be such that there is no possib ility of mistaking it for the audible signal used for a warning.

20.2.5 It should be possible to temporarily si lence alarms. If an alarm is not acknowledged within 30 s the audible signal should start again or as specified in the equipment performance standards.

20.2.6 The audible signal, if not temporarily silenced, and the visual signal for an unacknowledged alarm should continue until th e alarm is acknowledged, except specified otherwise in the equipment performance standards.

20.2.7 An acknowledged alarm should be indi cated by a steady visual indication.

20.2.8 The visual signal for an acknowledged al arm should continue until the alarm condition is rectified.

20.3 Warnings

20.3.1 The alert management should distinguish between different announcement states of each individual warning:

unacknowledged warning
acknowledged warning.

---CHUNK---

SOURCE: MSC.252(83).pdf
acknowledged warning.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 27

20.3.2 When a warning condition is detecte d, it should be indicated as unacknowledged warning:

(a) initiate an momentarily audible si gnal, accompanied by the visual warning announcement;

(b) provide a message of sufficient detail to enable the bridge team to identify and address the warning condition;

(c) may be accompanied by speech outpu t presented at least in English.

20.3.3 An unacknowledged warning should be clear ly distinguishable from those existing and already acknowledged. Unacknowledged warnings s hould be indicated by a flashing and by an audible signal.

20.3.4 When a warning occurs a momentar ily audible signal should be given. The characteristics of the audible warning signal, whether used singly or in combination with speech, should be such that there is no possibility of mistaking it for the audible signal used for an alarm.

---CHUNK---

SOURCE: MSC.252(83).pdf
characteristics of the audible warning signal, whether used singly or in combination with speech, should be such that there is no possibility of mistaking it for the audible signal used for an alarm.

20.3.5 The visualization for an unacknowledged wa rning should continue until the warning is acknowledged, except specified otherwise in the equipment performance standards.

20.3.6 An acknowledged warning should be i ndicated by a steady visual indication.

20.3.7 The visual signal for an acknowledged warning should continue until the warning condition is rectified.

20.4 Cautions

20.4.1 A caution should be indicated by a steady visual indication. No acknowledgement should be necessary for a caution.

20.4.2 A caution should be automatically rem oved after the condition is rectified.

20.4.3 A message should be provided of sufficient detail to enable the bridge team to identify and address the caution condition.

20.5 Alert escalation

20.5.1 After a time defined by the user unless otherwise specified by the organization, an unacknowledged alarm should be transferred to th e bridge navigational watch alarm system

---CHUNK---

SOURCE: MSC.252(83).pdf
and address the caution condition.

20.5 Alert escalation

20.5.1 After a time defined by the user unless otherwise specified by the organization, an unacknowledged alarm should be transferred to th e bridge navigational watch alarm system (BNWAS), if available. The unacknowledged alarm should remain visible and audible.

20.5.2 An unacknowledged warning should be ch anged to alarm priori ty, as required by specific requirements for the individual equipment or after 60 s unless otherwise set by the user.

20.5.3 The alert escalation should be in compliant with the alert escalation requirements of the individual performance standards.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 28

I:\MSC\83\28-Add-3.doc
21 Consistent presentation of alerts within the INS

21.1 To ensure a consistent presentation of aler ts and the presentation of a reduced number of high priority alerts within the INS:

.1 the alerts released by navigational func tions, sensors, sources should be presented

---CHUNK---

SOURCE: MSC.252(83).pdf
21.1 To ensure a consistent presentation of aler ts and the presentation of a reduced number of high priority alerts within the INS:

.1 the alerts released by navigational func tions, sensors, sources should be presented as far as practicable, after evaluation w ith the system knowledge of the INS, to reduce the number of high priority alerts;

.2 the priority of the alert is to be define d in compliance with the relevant paragraphs of this performance standards;

.3 the priority of any aler t should be assigned and presente d consistently for all parts of the INS;

.4 the alert releasing sensor/source or f unction (system) should provide the alert related information of the alert message for explanation and decision support, including information for user support in respect to the alert messages, as far as possible;

.5 if additional information regarding deci sion support and user guidance is available with the system knowledge of the INS, th is information should be made available for the user;

.6 HMI’s presenting alert information should have the capability to present the alert

---CHUNK---

SOURCE: MSC.252(83).pdf
with the system knowledge of the INS, th is information should be made available for the user;

.6 HMI’s presenting alert information should have the capability to present the alert information, provided by the alert releas ing sensor/source or function (system) and the information added with system knowledge of the INS.

21.2 The audible announcement of category A alerts should occur at th e task stations or displays which are directly assigned to the function generating the alert.

22 Central alert management HMI

22.1 All alerts should be displayed on th e central alert management HMI.

22.2 The central alert management HMI should of fer the possibility to display category A alerts as “aggregated alerts”, i.e., a single visual indica tion indicates the existence of many alerts on the task station presenting the function, e.g. one alert should indicate the existence of multiple dangerous target alerts existing at the task station for collision avoidance.

22.3 The central alert management HMI should provide the means to announce and indicate