alerts to draw the attention of the bridge team.

---CHUNK---

SOURCE: MSC.252(83).pdf
dangerous target alerts existing at the task station for collision avoidance.

22.3 The central alert management HMI should provide the means to announce and indicate alerts to draw the attention of the bridge team.

22.4 The central alert management HMI should have the capability to substitute the audible alert announcement of the individual equipment, except for category A alerts.

22.5 The central alert management HMI should al low to identify alerts, and enable the immediate identification of the alert releasing function or sensor/source.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 29

I:\MSC\83\28-Add-3.doc
22.6 The central alert management HMI should be designed that alert messages of the different priorities are clearly distinguishable from each other.

22.7 The alert messages should be completed with aids for decision making, as far as practicable. An explanation or justification of an alert should be available on request.

22.8 The central alert management HMI should en able an immediate acknowledgement of the

---CHUNK---

SOURCE: MSC.252(83).pdf
practicable. An explanation or justification of an alert should be available on request.

22.8 The central alert management HMI should en able an immediate acknowledgement of the alarms and warnings by a single operator action, except for category A.

22.9 The central alert management HMI should be able to display at least 20 recent incidents/faults at the same time.

22.10 If the central alert management HMI is such that it can not contai n all active messages requiring the bridge team’s attention, then th ere should be a clear and unambiguous indication that there are additional active messages requiring attention.

22.11 It should be possible to display the additional active messages by a single operator action.

22.12 It should be possible to retu rn to the display containing th e highest priority alerts by a single operator action.

22.13 Silencing of audible alerts

22.13.1 It should be possible to te mporarily silence all audible alerts at the central alert

management HMI.

22.13.2 The audible signal should be reactivated, if the alert ha s not been acknowledged within the specified times in paragraph 20 for alarms and warnings.

---CHUNK---

SOURCE: MSC.252(83).pdf
management HMI.

22.13.2 The audible signal should be reactivated, if the alert ha s not been acknowledged within the specified times in paragraph 20 for alarms and warnings.

22.14 Category B Alert history list

22.14.1 An operator accessible alert history list should be provided by the central alert management HMI.

22.14.2 When a category B alert is no longer active the message should be ke pt with its entire content in an alert history list, with the date and time the alert was raised, acknowledged and rectified.

22.14.3 The messages of the alert history list s hould be displayed in chronological order.

22.14.4 Access to the alert history list and return to the active alert display should be possible by a simple operator action.

22.14.5 The system should provide a clear and una mbiguous indication when the alert history list is being accessed and displayed.

22.14.6 The system should revert automatically to the active alert display when it detects a new alert condition.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30

---CHUNK---

SOURCE: MSC.252(83).pdf
alert condition.
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30

22.14.7 The central alert management HMI shoul d support the search an d identification of alerts in the alert history list.

22.14.8 It should be possible to keep the content of the alert history list at least for 24 h.

23 Acknowledgement and cancellation location

23.1 Acknowledgement

23.1.1 The acknowledgement of alarms and warni ngs should only be possible at a HMI (task station) where an appropriate situation assessment and decision support can be carried out.

24 Self-monitoring of alert management

24.1 The system communication between the alert management and the systems and sources/sensors initiating the alerts should be monitored.

24.2 Provisions should be made for functional testing of alerts, in cluding the system communication between the alert management and the systems and sources/sensors initiating the alerts.

24.3 The alert management should have the capability to provide alerts for failure and loss of

---CHUNK---

SOURCE: MSC.252(83).pdf
communication between the alert management and the systems and sources/sensors initiating the alerts.

24.3 The alert management should have the capability to provide alerts for failure and loss of functions (systems), sources and sensors. Th ese should be indicated at the central alert management HMI.

25 Interface requirements for alert related communication

25.1 Connected sources, sensors and systems taki ng part in the alert related communication should follow a standardized communication concept. Internal alert related communication within an individual source, sensor and equipment may use an alternative communication concept.

25.2 The communication protocol should allow the implementation of the functions described in these standards. In particular, this includes:

25.2.1 Transmission of all relevant alert priori ties, states, associated quality information, additional alert message information for, e.g., explanation of alert, decision support.

25.2.2 Transmission of alert source identity so that originator component and/or function can be determined, as well as it being possible to differentiate between alerts originating from the same

---CHUNK---

SOURCE: MSC.252(83).pdf
25.2.2 Transmission of alert source identity so that originator component and/or function can be determined, as well as it being possible to differentiate between alerts originating from the same device but at different time and also between aler ts indicating different conditions from the same device at the same time.

25.2.3 Transmission of acknowledgement and silence signals between the device where the alert

was silenced or acknowledged and the device where it originates and where it may also have to be silenced/acknowledged.

25.2.4 Transmission mechanisms that avoid that sign als in one or the othe r directions are lost (by fully reliable transmissions or by suitable retransmissions).



25.2.5 Mechanisms that allow consistent reconnect ion of a component of the INS system to the system after disconnect at any time and in any alert condition.

25.2.6 In general, mechanisms that allows consistency in the complete INS with regards to alert management.

---CHUNK---

SOURCE: MSC.252(83).pdf

system after disconnect at any time and in any alert condition.