7.2 Status Information
7.3 Standards
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)

---CHUNK---

SOURCE: MSC.252(83).pdf
6 Ergonomic criteria
B3 Connection to sensors
7.1 Sensors
B4 Failure, back-up and fallback arrangements

8 Fallback arrangements

C Interfacing
7.2 Status Information
7.3 Standards
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 44

I:\MSC\83\28-Add-3.doc
Appendix 5

CLASSIFICATION OF ALERTS

For the purpose of transf erring requirements for alarms and indications of existing individual performance standards into 3 priority classes of alerts within the INS performance standard, the alarms of the individual performance standards are subdivided into two cl asses of alarms being alarms and warnings in the INS performance standard.

Table 1: Classification of INS alerts as specified in these performance standards

Source Cause Alarm Warn. Caut. Categ. A Categ. B
System function lost X X
Integrity verification not possible
(5.5.5) X X
Invalid information for functions in
use (5.3.1.2) X X
Invalid information for functions not
in use (5.3.1.2) X X
Different thresholds entered (5.4.3.3) X X
INS

---CHUNK---

SOURCE: MSC.252(83).pdf
Integrity verification not possible
(5.5.5) X X
Invalid information for functions in

use (5.3.1.2) X X
Invalid information for functions not
in use (5.3.1.2) X X
Different thresholds entered (5.4.3.3) X X
INS

Loss of system communication
(12.6.2) X X

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3
ANNEX 30
Page 45

I:\MSC\83\28-Add-3.doc

Table 2: Classification for INS for alerts specified in the individual equipment
performance standards
Source Cause Alarm Warn. Caut. Categ. A Categ. B
Failure or reduction in power supply X X
Off heading alarm X X Heading control
systems Heading monitor (deviation from second heading source) X X
Early course change indication (track
control via waypoints) X X
Actual course change indication X X
Wheel over line (actual course
change indication not acknowledged)
1) alarm
2) back-up navigator alarm
X X
Failure or reduction in power supply X X
Position monitor X X
Heading monitor X X
Sensor failure (heading, position,
speed)
1) alarm

---CHUNK---

SOURCE: MSC.252(83).pdf
change indication not acknowledged)
1) alarm
2) back-up navigator alarm
X X
Failure or reduction in power supply X X
Position monitor X X
Heading monitor X X
Sensor failure (heading, position,
speed)
1) alarm
2) back-up navigator alarm
X X

Cross-track alarm X X
Course difference (heading deviates from track course) X X
Track Control systems
Low speed alarm X X
Positioning system failure X X
Crossing safety contour X X
Deviation from planned route – off-track alarm X X
Area with special conditions – cross the boundary X* X* X
Approach to critical point X X
Different geodetic datum X X
System malfunction X X

ECDIS (system malfunction of backup device) X X
Target capacity X X
CPA/TCPA alarm X X
Acquisition/activation zone X X
Lost target alarm X X
RADAR/ AIS
Failure of any signal or sensor in use X X
HDOP exceeded X X
No calculation of position X
Loss of position X X
Loss of differential signal X X
Differential corrections not applied X X
GNSS
Differential integrity status X X
RESOLUTION MSC.252(83) (adopted on 8 October 2007)

---CHUNK---

SOURCE: MSC.252(83).pdf
No calculation of position X
Loss of position X X
Loss of differential signal X X
Differential corrections not applied X X
GNSS
Differential integrity status X X
RESOLUTION MSC.252(83) (adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR INTEGRATED NAVIGATION SYSTEMS (INS)MSC 83/28/Add.3

Depth below keel alarm X X Echo
sounder

Failure or reduction in power
supply X X
Gyro
compass

System fault X X
Malfunction X X Bridge watch
alarm
Power supply failure X X

X*: selected by the user.

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR