Appendix 6

DEFAULT DISPLAY CONFIGURATIONS

As required in paragraph 9.2.1, the INS should offe r as basic operational settings the following default display configurations for the tasks route monitoring and collision avoidance.

Task “Route monitoring”

Function Setting
Display category ECDIS Standard display

---CHUNK---

SOURCE: MSC.252(83).pdf
default display configurations for the tasks route monitoring and collision avoidance.

Task “Route monitoring”

Function Setting
Display category ECDIS Standard display
Selected sea area Around own ship with appropriate off-set
Range 3 nm
Orientation True motion, north-up
Manual updates If applied
Operator’s notes If applied
position sensor GNSS (system position provided by INS)
Past track On
Selected route Last selected route, including route parameters
Look-ahead time 6 min

RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR

Task “Collision avoidance”

Function Setting
Band X-band, if selectable
Gain and anti-clutter functions Automatically optimized
Tuning Automatically optimized
Range 6 nm
Fixed rings Off

VRMs One VRM on
EBLs One EBL on
Parallel index lines Off or last setting, if applied
Display mode of the radar picture True motion, north-up
Off-centring Appropriate look-ahead
Target trails On
Past positions Off
Radar target tracking Continued
Vector mode Relative

---CHUNK---

SOURCE: MSC.252(83).pdf
Parallel index lines Off or last setting, if applied
Display mode of the radar picture True motion, north-up
Off-centring Appropriate look-ahead
Target trails On
Past positions Off
Radar target tracking Continued
Vector mode Relative
Vector time 6 min
Automatic radar target acquisition Off
Graphical AIS reported target display On
Radar and AIS Target fusion On
Operational alarms (except collision
warnings) Off
Collision warnings On (limits CPA 2 nm; TCPA 12 min)
Display of maps, navigation lines and
routes Last setting
Display of charts Off

***
RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)RESOLUTION MSC.252(83)
(adopted on 8 October 2007)
ADOPTION OF THE REVISED PERFORMANCE STANDARDS FOR
INTEGRATED NAVIGATION SYSTEMS (INS)

---CHUNK---

SOURCE: MSC.253(83).pdf
RESOLUTION MSC.253(83)
(adopted on 8 October 2007)
ADOPTION OF THE PERFORMANCE STANDARDS FOR
NAVIGATION LIGHTS, NAVIGATION LIGHT CONTROLLERS
AND ASSOCIATED EQUIPMENTMSC 83/28/Add.3

I:\MSC\83\28-Add-3.doc
ANNEX 31

RESOLUTION MSC.253(83)

(adopted on 8 October 2007)

ADOPTION OF THE PERFORMANCE STANDARDS FOR NAVIGATION LIGHTS, NAVIGATION LIGHT CONTROLLERS AND ASSOCIATED EQUIPMENT

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution A.886(21), by which the Assembly resolved that the function of adopting performance standards and technical specifications, as well as amendments thereto shall be performed by the Maritime Safety Committee and/or the Marine Environment Protection Committee, as appropriate, on behalf of the Organization,

RECALLING FURTHER Rule 21, Rule 23 and Rule 34(b) of the Convention on the International Regulations for Preventing Coll isions at sea (COLRE Gs), 1972, concerning the requirements on the use of Navigation Lights,

---CHUNK---

SOURCE: MSC.253(83).pdf
RECALLING FURTHER Rule 21, Rule 23 and Rule 34(b) of the Convention on the International Regulations for Preventing Coll isions at sea (COLRE Gs), 1972, concerning the requirements on the use of Navigation Lights,

NOTING that that the purpose of Navigation Li ghts is to identify ships and to notify their intentions at sea and that the purpose of Navigation Light Contro llers is to provide means of control and monitoring of the stat us of navigation lights onboard th e vessel to the Officer of the Watch (OOW),

RECOGNIZING the need to develop performance standards for Navigation Lights, Navigation Light Controllers and associated equipment to be fitted onboard vessels in accordance with COLREGs,

HAVING CONSIDERED the recommendation made by the Sub-Committee on Safety of Navigation at its fifty-third session, and the Maritime Safety Committee at its eighty-third session,

1. ADOPTS the Recommendation on Performa nce Standards for Navigation Lights, Navigation Light Controllers and associated equipment, set out in the annex to the present resolution;

2. RECOMMENDS Governments ensure that Navigation Lights, Navigation Light

---CHUNK---

SOURCE: MSC.253(83).pdf
Navigation Light Controllers and associated equipment, set out in the annex to the present resolution;

2. RECOMMENDS Governments ensure that Navigation Lights, Navigation Light Controllers and associated equipment inst alled on or after 1 January 2009 conform to performance standards not inferior to those specified in the annex to the present resolution.

RESOLUTION MSC.253(83)
(adopted on 8 October 2007)
ADOPTION OF THE PERFORMANCE STANDARDS FOR
NAVIGATION LIGHTS, NAVIGATION LIGHT CONTROLLERS
AND ASSOCIATED EQUIPMENTMSC 83/28/Add.3
ANNEX 31

I:\MSC\83\28-Add-3.doc
ANNEX

PERFORMANCE STANDARDS FOR NAVIGATION LIGHTS,
NAVIGATION LIGHT CONTROLLERS AND ASSOCIATED EQUIPMENT

1 Scope

These performance standards apply to Navigati on Lights (NLs), Navigation Light Controllers (NLCs) and associated equipment to be fitted onboard vessels in accordance with COLREGs.