---CHUNK---

SOURCE: MSC.253(83).pdf
5.5 An NLC on board a ship not less than 50 m in length should present the status of all NLs in a logical presentation, meeting the requ irements set out in resolution MSC.191(79), e.g ., by symbol marks on a display.

5.6 All indicators of an NLC should be dimmable to ensure easy reading without disturbing the night vision of the Officer of the Watch. Th e brightness of a display, if fitted, of an NLC should be controllable.

5.7 An NLC should support the use of standardized serial interfaces for marine navigation and communication systems2.

5.8 The NLC should have a bi-directional interface to transfer alarms to external systems and receive acknowledgements of alarms from extern al systems. The interface should comply with the relevant international standards2.

6 Power supply and fallback arrangements

6.1 Each NL should be connected, via separate circuits, to a NLC located on the bridge in order to avoid any NL failure, including short circ uit, that affect any other NLs connected to the NLC. A NLC may only be additionally connected to special signal lights such as lights required by canal authorities.

---CHUNK---

SOURCE: MSC.253(83).pdf
order to avoid any NL failure, including short circ uit, that affect any other NLs connected to the NLC. A NLC may only be additionally connected to special signal lights such as lights required by canal authorities.

2 Refer to IEC 61162 series.

6.2 It should be possible to operate the NLC a nd NLs when supplied by an emergency source of electrical power in accordance with the appropriate requirements of chapte r II-1 of the 1974 SOLAS Convention, as amended.

6.3 Automatic switch over to the alternative source of power is permitted.

7 Associated equipment

Screens for sidelight may be a part of a ships structure. All associated equipment should be produced in a robust, non-corroding material, which should ensure a long-term durability for the

relevant operation.

8 Marking

Each NL should be marked with:

.1 the manufacturers name or symbol, and designation of type;

---CHUNK---

SOURCE: MSC.253(83).pdf
produced in a robust, non-corroding material, which should ensure a long-term durability for the relevant operation.

8 Marking

Each NL should be marked with:

.1 the manufacturers name or symbol, and designation of type;

.2 the type/category of the NL in accordance with COLREGs;

.3 serial and certificate number;

.4 head line directions;

.5 range in nautical miles; and

.6 nominal wattage of the light source in watts, if different values lead to different ranges.

9 Installation of navigation lights and associated equipment

In addition to the relevant requirements of COLREGs, the installation of NLs and associated equipment should comply with the following requirements:

.1 The manufacturer of NLs should provide guidance on the installation of NLs and the design and installation of screens for sidelights, as required by COLREGs;

.2 NLs should be installed in such a way so as to prevent navigation watch keeping personnel from direct or reflected undue glare;

.3 NLs should be installed in such way as to ensure that the light shows over the required arcs of visibility, and should sa tisfy the required vertical separation and

---CHUNK---

SOURCE: MSC.253(83).pdf
personnel from direct or reflected undue glare;

.3 NLs should be installed in such way as to ensure that the light shows over the required arcs of visibility, and should sa tisfy the required vertical separation and location requirements in all normal operating trim conditions; and

.4 Equipment for operation of the manoeuvring light, mounted in accordance with COLREGs, should be located at conning position. The equipment may be located near the steering wheel or the autopilot/track control.

10 Maintenance

10.1 NLs should be so designed that the lamp sp ecified by the manufacturer can be efficiently and readily replaced, without elaborate recalibration or readjustment.

10.2 NLs, NLCs and associated equipment s hould be so constructed and installed, as necessary, that they are readily accessible for inspection and maintenance purposes.

***

RESOLUTION MSC.253(83)
(adopted on 8 October 2007)

---CHUNK---

SOURCE: MSC.253(83).pdf

10.2 NLs, NLCs and associated equipment s hould be so constructed and installed, as necessary, that they are readily accessible for inspection and maintenance purposes.

***

RESOLUTION MSC.253(83)
(adopted on 8 October 2007)
ADOPTION OF THE PERFORMANCE STANDARDS FOR
NAVIGATION LIGHTS, NAVIGATION LIGHT CONTROLLERS
AND ASSOCIATED EQUIPMENTRESOLUTION MSC.253(83)
(adopted on 8 October 2007)
ADOPTION OF THE PERFORMANCE STANDARDS FOR
NAVIGATION LIGHTS, NAVIGATION LIGHT CONTROLLERS
AND ASSOCIATED EQUIPMENT

---CHUNK---

SOURCE: MSC.254(83).pdf

RESOLUTION MSC.254(83)
(adopted on 12 October 2007)
ADOPTION OF AMENDMENTS TO THE
PERFORMANCE STANDARDS AND FUNCTIONAL REQUIREMENTS FOR THE
LONG-RANGE IDENTIFICATION AND TRACKING OF SHIPSMSC 83/28/Add.3

ANNEX 37

RESOLUTION MSC.254(83)

(adopted on 12 October 2007)

ADOPTION OF AMENDMENTS TO THE
PERFORMANCE STANDARDS AND FUNCTIONAL REQUIREMENTS FOR THE
LONG-RANGE IDENTIFICATION AND TRACKING OF SHIPS

THE MARITIME SAFETY COMMITTEE,

RECALLING Article 28(b) of the Convention on the International Maritime Organization concerning the functions of the Committee,

RECALLING ALSO resolution A.886(21) on Procedure for the adoption of, and amendments to, performance standards and t echnical specifications, by which the Assembly resolved that the function of adopting performance standards and technical specifications, as well as amendments thereto shall be performed by the Maritime Safety Committee,

RECALLING FURTHER the provisions of th e regulation V/19-1 of the International Convention for the Safety of Life at Sea, 1974, as amended (the Convention), relating to the