Document Scheme A Scheme B
SECP X X
SECC X
ETM Scheme A X
ETM Scheme B X
OMM X X
EGC Record Book or
Electronic Logging System
X X

3 SAFETY NOTE

---CHUNK---

SOURCE: MEPC.259(68).pdf
adjustments, maintenance and service records as appropriate

Document Scheme A Scheme B
SECP X X
SECC X
ETM Scheme A X
ETM Scheme B X
OMM X X
EGC Record Book or
Electronic Logging System
X X

3 SAFETY NOTE

Due attention is to be given to the safety implications related to the handling and proximity of exhaust gases, the measurement equipment and the storage and use of pressurized containers of pure and calibration gases. Sampling positions and permanent access platforms should be such that this monitoring may be performed safely. In locating discharge outlet of washwater used in the EGC unit, due consideration should be given to the location of the

ship's seawater inlet. In all operating conditions the pH should be maintained at a level that avoids damage to the vessels anti -fouling system, the propeller, rudder and other components that may be vulnerable to acidic discharges, potentially causing accelerated

---CHUNK---

SOURCE: MEPC.259(68).pdf
avoids damage to the vessels anti -fouling system, the propeller, rudder and other components that may be vulnerable to acidic discharges, potentially causing accelerated
corrosion of critical metal components.

4 SCHEME A EGC SYSTEM APPROVAL, SURVEY AND CERTIFICATION USING

PARAMETER AND EMISSION CHECKS

4.1 Approval of EGC systems

4.1.1 General

Options under Scheme A of these guidelines provide for:

.1 unit approval;

.2 serially manufactured units; and

.3 production range approval.

4.1.2 Unit approval

4.1.2.1 An EGC unit should be certified as capable of meeting the limit value, (the Certified Value), specified by the manufacturer (e.g. the emission level the unit is capable of achieving on a continuous basis) with fuel oils of the manufacturers specified maximum % m/m sulphur content and for the range of operating parameters, as listed in paragraph 4.2.2.1 .2, for which they are to be approved. The Certified Value should at least be suitable for ship operations under requirements given by MARPOL Annex VI regulations 14.1 and/or 14.4.

4.1.2.2 Where testing is not to be undertaken with fuel oils of the manufacturer's specified

---CHUNK---

SOURCE: MEPC.259(68).pdf
under requirements given by MARPOL Annex VI regulations 14.1 and/or 14.4.

4.1.2.2 Where testing is not to be undertaken with fuel oils of the manufacturer's specified maximum % m/m sulphur content, the use of two test fuels with a lower % m/m sulphur content is permitted. The two fuels selected should have a difference in % m/m sulphur content sufficient to demonstrate the operational behaviour of the EGC unit and to demonstrate that the Certified Value can be met if the EGC unit were to be operated with a fuel of the manufacturer's specified maximum % m/m sulphur content. In such cases a minimum of two tests, in accordance with section 4.3 as appropriate, should be performed. These need not be sequential and could be undertaken on two different, but identical, EGC units.

4.1.2.3 The maximum and, if applicable, minimum exhaust gas mass flow rate of the unit should be stated. The effect of variation of the other parameters defined in paragraph 4.2.2.1.2 should be justified by the equipment manufacturer. The effect of variations in these factors should be assessed by testing or otherwise as appropriate. No

---CHUNK---

SOURCE: MEPC.259(68).pdf
paragraph 4.2.2.1.2 should be justified by the equipment manufacturer. The effect of variations in these factors should be assessed by testing or otherwise as appropriate. No variation in these factors, or combination of variations in these factors, should be such that the emission value of the EGC unit would be in excess of the Certified Value.

4.1.2.4 Data obtained in accordance with this section should be submitted to the

Administration for approval together with the ETM-A.

4.1.3 Serially manufactured units

In the case of nominally similar EGC units of the same mass flow ratings as that certified under 4.1.2, and to avoid the testing of each EGC unit, the equipment manufacturer may submit, for acceptance by the Administration, a conformity of production arrangement. The

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
certification of each EGC unit under this arrangement should be subject to such surveys that the Administration may consider necessary as to assure that each EGC unit has an emission

---CHUNK---

SOURCE: MEPC.259(68).pdf
certification of each EGC unit under this arrangement should be subject to such surveys that the Administration may consider necessary as to assure that each EGC unit has an emission value of not more than the Certified Value when operated in accordance with the parameters defined in paragraph 4.2.2.1.2.

4.1.4 Product range approval

4.1.4.1 In the case of an EGC unit of the same design, but of different maximum exhaust gas mass flow capacities, the Administration may accept, in lieu of tests on an EGC unit of all capacities in accordance with section 4.1.2, tests of EGC systems of three different capacities provided that the three tests are performed at intervals including the highest, lowest and one intermediate capacity rating within the range.

4.1.4.2 Where there are significant differences in the design of EGC units of different capacities, this procedure should not be applied unless it can be shown, to the satisfaction of the Administration, that in practice those differences do not materially alter the performance between the various EGC unit types.

4.1.4.3 For EGC units of different capacities, the sensitivity to variations in the type of
SOURCE: MEPC.259(68).pdf
the Administration, that in practice those differences do not materially alter the performance between the various EGC unit types.

4.1.4.3 For EGC units of different capacities, the sensitivity to variations in the type of combustion machinery to which they are fitted should be detailed together with sensitivity to the variations in the parameters listed in paragraph 4.2.2.1 .2. This should be on the basis of testing, or other data as appropriate.

4.1.4.4 The effect of changes of EGC unit capacity on washwater characteristics should be detailed.

4.1.4.5 All supporting data obtained in accordance with this section, together with the ETM-A for each capacity unit, should be submitted to the Administration for approval.

4.2 Survey and certification

4.2.1 Procedures for the certification of an EGC unit

4.2.1.1 In order to meet the requirements of section 4.1 either prior to, or after installation on board, each EGC unit should be certified as meeting the Certified Value specified by the manufacturer (e.g. the emission level the unit is capable of achieving on a continuous basis)

---CHUNK---

SOURCE: MEPC.259(68).pdf
board, each EGC unit should be certified as meeting the Certified Value specified by the manufacturer (e.g. the emission level the unit is capable of achieving on a continuous basis) under the operating conditions and restrictions as given by the EGC Technical Manual (ETM-A) as approved by the Administration.

4.2.1.2 Determination of the Certified Value should be in accordance with the provisions of these guidelines.

4.2.1.3 Each EGC unit meeting the requirements of paragraph 4.2.1.1 should be issued with a SECC by the Administration. The form of the SECC is given in appendix 1.

4.2.1.4 Application for an SECC should be made by the EGC system manufacturer,