water content (e.g. dry or with the same wetness fraction).

6.9 In justified cases where the CO 2 concentration is reduced by the EGC unit, the CO 2

---CHUNK---

SOURCE: MEPC.259(68).pdf
analysed.

6.8 The SO 2 and CO 2 values should be compared on the basis of the same residual water content (e.g. dry or with the same wetness fraction).

6.9 In justified cases where the CO 2 concentration is reduced by the EGC unit, the CO 2 concentration can be measured at the EGC unit inlet, provided that the correctness of such a methodology can be clearly demonstrated. In such cases the SO 2 and CO2 values should be compared on a dry basis. If measured on a wet basis the water content in the exhaust gas stream at those points should also be determined in order to correct the readings to dry basis values. For calculation of the CO 2 value on a dry basis, the dry/wet correction factor may be calculated in accordance with paragraph 5.12.3.2.2 of the NOX Technical Code 2008.

7 DATA RECORDING AND PROCESSING DEVICE

7.1 The recording and processing device should be of robust, tamper-proof design with read-only capability.

7.2 The recording and processing device should record the data required by sections 4.4.7, 5.4.2, and 10.3 against UTC and ships position by a Global Navigational Satellite System (GNSS).

---CHUNK---

SOURCE: MEPC.259(68).pdf
read-only capability.

7.2 The recording and processing device should record the data required by sections 4.4.7, 5.4.2, and 10.3 against UTC and ships position by a Global Navigational Satellite System (GNSS).

7.3 The recording and processing device should be capable of preparing reports over specified time periods.

7.4 Data should be retained for a period of not less than 18 months from the date of recording. If the unit is changed over that period, the shipowner should ensure that the required data is retained on board and available as required.

7.5 The device should be capable of downloading a copy of the recorded data and reports in a readily useable format. Such copy of the data and reports should be available to the Administration or port State authority as requested.

8 ONBOARD MONITORING MANUAL (OMM)

8.1 An OMM should be prepared to cover each EGC unit installed in conjunction with fuel oil combustion equipment, which should be identified, for which compliance is to be demonstrated.

8.2 The OMM should, as a minimum, include:

.1 the sensors to be used in evaluating EGC system performance and

---CHUNK---

SOURCE: MEPC.259(68).pdf
fuel oil combustion equipment, which should be identified, for which compliance is to be demonstrated.

8.2 The OMM should, as a minimum, include:

.1 the sensors to be used in evaluating EGC system performance and washwater monitoring, their service, maintenance and calibration requirements;

RESOLUTION MEPC.259(68)
(adopted on 15 May 2015)
2015 GUIDELINES FOR EXHAUST GAS CLEANING SYSTEMSMEPC 68/21/Add.1
Annex 1, page 13

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
.2 the positions from which exhaust emission measurements and washwater monitoring are to be taken together with details of any necessary ancillary services such as sample transfer lines and sample treatment units and any related service or maintenance requirements;

.3 the analysers to be used, their service, maintenance, and calibration requirements;

.4 analyser zero and span check procedures; and

.5 other information or data relevant to the correct functioning of the monitoring systems or its use in demonstrating compliance.

8.3 The OMM should specify how the monitoring is to be surveyed.

8.4 The OMM should be approved by the Administration.

---CHUNK---

SOURCE: MEPC.259(68).pdf
monitoring systems or its use in demonstrating compliance.

8.3 The OMM should specify how the monitoring is to be surveyed.

8.4 The OMM should be approved by the Administration.

9 SHIP COMPLIANCE

9.1 SOX Emissions Compliance Plan (SECP)

9.1.1 For all ships which are to use an EGC unit, in part or in total, in order to comply with the requirements of regulations 14.1 and 14.4 of MARPOL Annex VI there should be an SECP for the ship, approved by the Administration.

9.1.2 The SECP should list each item of fuel oil combustion equipment which is to meet the requirements for operating in accordance with the requirements of regulations 14.1 and/or 14.4 of MARPOL Annex VI.

9.1.3 Under Scheme A, the SECP should present how continuous monitoring data will demonstrate that the parameters in paragraph 4.4.7 are maintained within the manufacturer's recommended specifications. Under Scheme B, this would be demonstrated using daily recordings of key parameters.

9.1.4 Under Scheme B, the SECP should present how continuous exhaust gas emissions monitoring will demonstrate that the ship total SO2(ppm)/CO2(%) ratio is comparable to the

---CHUNK---

SOURCE: MEPC.259(68).pdf
recordings of key parameters.

9.1.4 Under Scheme B, the SECP should present how continuous exhaust gas emissions monitoring will demonstrate that the ship total SO2(ppm)/CO2(%) ratio is comparable to the requirements of regulation 14.1 and/or 14.4 of MARPOL Annex VI or below as prescribed in paragraph 1.3. Under Scheme A, this would be demonstrated using daily exhaust gas emission recordings.

9.1.5 There may be some equipment such as small engines and boilers to which the fitting of EGC units would not be practical, particularly where such equipment is located in a position remote from the main machinery spaces. All such fuel oil combustion units should be listed in the SECP. For these fuel oil combustion units which are not to be fitted with EGC units, compliance may be achieved by means of regulations 14.1 and/or 14.4 of MARPOL Annex VI.

9.2 Demonstration of complia nce

9.2.1 Scheme A

9.2.1.1 The SECP should refer to, not reproduce, the ETM-A, EGC Record Book or Engine-Room logger system and OMM as specified under Scheme A. It should be noted that as an alternative, the maintenance records may be recorded in the ship's planned

---CHUNK---

SOURCE: MEPC.259(68).pdf
9.2.1.1 The SECP should refer to, not reproduce, the ETM-A, EGC Record Book or Engine-Room logger system and OMM as specified under Scheme A. It should be noted that as an alternative, the maintenance records may be recorded in the ship's planned maintenance record system, as allowed by the Administration.

https://edocs.imo.org/Final Documents/English/MEPC 68-21-ADD.1 (E).doc
9.2.1.2 For all fuel oil combustion equipment listed under paragraph 9.1.2, details should be provided demonstrating that the rating and restrictions for the EGC unit as approved, paragraph 4.2.2.1.2, are complied with.

9.2.1.3 Required parameters should be monitored and recorded as required under paragraph 4.4.7 when the EGC is in operation in order to demonstrate compliance.

9.2.2 Scheme B

The SECP should refer to, not reproduce, the ETM-B, EGC Record Book or Engine-Room logger system and OMM as specified under Scheme B.

10 WASHWATER

10.1 Washwater discharge criteria 1

---CHUNK---

SOURCE: MEPC.259(68).pdf
9.2.2 Scheme B