operable, and that means of escape remain available so that persons on board can safely and swiftly escape to the lifeboat and liferaft embarkation deck under the expected environmental conditions.

RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 21 -

7.2 Functional requirements

7.2.1 In order to achieve the goal set out in paragraph 7.1 above, the following functional requirements are embodied in the regulations of this chapter:

.1 all components of fire safety systems and appliances if installed in exposed positions shall be protected from ice accretion and snow accumulation;

.2 local equipment and machinery controls shall be arranged so as to avoid freezing, snow accumulation and ice accretion and their location to remain accessible at all time;

---CHUNK---

SOURCE: MEPC.264(68).pdf
.2 local equipment and machinery controls shall be arranged so as to avoid freezing, snow accumulation and ice accretion and their location to remain accessible at all time;

.3 the design of fire safety systems and appliances shall take into consideration the need for persons to wear bulky and cumbersome cold weather gear, where appropriate;

.4 means shall be provided to remove or prevent ice and snow accretion from accesses; and

.5 extinguishing media shall be suitable for intended operation.

7.2.2 In addition, for ships intended to operate in low air temperature, the following applies:

.1 all components of fire safety systems and appliances shall be designed to ensure availability and effectiveness at the PST; and

.2 materials used in exposed fire safety systems shall be suitable for operation at the PST.

7.3 Regulations

7.3.1 In order to comply with the requirement of paragraph 7.2.1.1, the following applies:

.1 isolating and pressure/vacuum valves in exposed locations shall be protected from ice accretion and remain accessible at all times; and

.2 all two-way portable radio communication equipment shall be operable at the PST.

---CHUNK---

SOURCE: MEPC.264(68).pdf
.1 isolating and pressure/vacuum valves in exposed locations shall be protected from ice accretion and remain accessible at all times; and

.2 all two-way portable radio communication equipment shall be operable at the PST.

7.3.2 In order to comply with the requirement of paragraph 7.2.1.2, the following applies:

.1 fire pumps, including emergency fire pumps, water mist and water spray pumps, shall be located in compartments maintained above freezing;

.2 the fire main is to be arranged so that exposed sections can be isolated and means of draining of exposed sections shall be provided. Fire hoses and nozzles need not be connected to the fire main at all times, and may be stored in protected locations near the hydrants;

.3 firefighter's outfits shall be stored in warm locations on the ship; and

.4 where fixed water-based firefighting systems are located in a space separate from the main fire pumps and use their own independent sea suction, this sea suction shall also be capable of being cleared of ice accumulation.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 22 -

---CHUNK---

SOURCE: MEPC.264(68).pdf
sea suction shall also be capable of being cleared of ice accumulation.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 22 -

7.3.3 In addition, for ships intended to operate in low air temperature, the following applies:

.1 in order to comply with the requirement of paragraph 7.2.2.1, portable and semi-portable extinguishers shall be located in positions protected from freezing temperatures, as far as practical. Locations subject to freezing are to be provided with extinguishers capable of operation at the PST; and

.2 in order to comply with the functional requirements of paragraph 7.2.2.2 above, materials of exposed fire safety systems shall be approved by the Administration, or a recognized organ ization accepted by it, taking into account standards acceptable to the Organization or other standards offering an equivalent level of safety based on the PST.

CHAPTER 8 LIFE-SAVING APPLIANCES AND ARRANGEMENTS

8.1 Goal

The goal of this chapter is to provide for safe escape, evacuation and survival.

8.2 Functional requirements

---CHUNK---

SOURCE: MEPC.264(68).pdf
an equivalent level of safety based on the PST.

CHAPTER 8 LIFE-SAVING APPLIANCES AND ARRANGEMENTS

8.1 Goal

The goal of this chapter is to provide for safe escape, evacuation and survival.

8.2 Functional requirements

In order to achieve the goal set out in paragraph 8.1 above, the following functional requirements are embodied in the regulations of this chapter:

8.2.1 Escape

8.2.1.1 Exposed escape routes shall remain accessible and safe, taking into consideration the potential icing of structures and snow accumulation.

8.2.1.2 Survival craft and muster and embarkation arrangements shall provide safe abandonment of ship, taking into consi deration the possible adverse environmental conditions during an emergency.

8.2.2 Evacuation

All life-saving appliances and associated equipment shall provide safe evacuation and be functional under the possible adverse environmental conditions during th e maximum expected time of rescue.

8.2.3 Survival

8.2.3.1 Adequate thermal protection shall be provided for all persons on board, taking into account the intended voyage, the anticipated weather conditions (cold and wind) and the

---CHUNK---

SOURCE: MEPC.264(68).pdf
expected time of rescue.

8.2.3 Survival

8.2.3.1 Adequate thermal protection shall be provided for all persons on board, taking into account the intended voyage, the anticipated weather conditions (cold and wind) and the potential for immersion in polar water, where applicable.

8.2.3.2 Life-saving appliances and associated equipment shall take account of the potential of operation in long periods of darkness, taking into consideration the intended voyage.

8.2.3.3 Taking into account the presence of any hazards, as identified in the assessment in chapter 1, resources shall be provided to support survival following abandoning ship, whether to the water, to ice or to land, for the maximum expected time of rescue. These resources shall provide:

.1 a habitable environment;

.2 protection of persons from the effects of cold, wind and sun;

.3 space to accommodate persons equipped with thermal protection adequate for the environment;

.4 means to provide sustenance;

.5 safe access and exit points; and