9.2.2.1 The navigational equipment and systems shall be designed, constructed, and installed to retain their functionality under the expected e nvironmental conditions in the area of operation.

9.2.2.2 Systems for providing reference headings and position fixing shall be suitable for the intended areas.

9.2.3 Additional navigational equipment

9.2.3.1 Ships shall have the ability to visually detect ice when operating in darkness.

9.2.3.2 Ships involved in operations with an icebreaker escort shall have suitable means to indicate when the ship is stopped.

---CHUNK---

SOURCE: MEPC.264(68).pdf
9.2.3.1 Ships shall have the ability to visually detect ice when operating in darkness.

9.2.3.2 Ships involved in operations with an icebreaker escort shall have suitable means to indicate when the ship is stopped.

9.3 Regulations

9.3.1 Nautical information

In order to comply with the functional requirement of paragraph 9.2.1 above, ships shall have means of receiving and displaying current information on ice conditions in the area of operation.

9.3.2 Navigational equipment functionality

9.3.2.1 In order to comply with the functional requirement of paragraph 9.2.2.1 above, the following applies:

.1 ships constructed on or after 1 January 2017, ice strengthened in accordance with chapter 3, shall have either two independent echo-sounding devices or one echo-sounding device with two separate independent transducers;

.2 ships shall comply with SOLAS regulation V/22.1.9.4, irrespective of the date of construction and the size and, depending on the bridge configuration, have a clear view astern;

RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 26 -

---CHUNK---

SOURCE: MEPC.264(68).pdf
date of construction and the size and, depending on the bridge configuration, have a clear view astern;

.3 for ships operating in areas and during periods where ice accretion is likely to occur, means to prevent the accumulation of ice on antennas required for navigation and communication shall be provided; and

.4 in addition, for ships ice strengthened in accordance with chapter 3, the following applies:

.1 where equipment required by SOLAS chapter V or this chapter has sensors that project below the hull, such sensors shall be protected against ice; and

.2 in category A and B ships constructed on or after 1 January 2017, the bridge wings shall be enclosed or designed to protect navigational equipment and operating personnel.

9.3.2.2 In order to comply with the functional requirement of paragraph 9.2.2.2 above, the following applies:

.1 ships shall have two non -magnetic means to determine and display their heading. Both means shall be independent and shall be connected to the ship's main and emergency source of power; and

---CHUNK---

SOURCE: MEPC.264(68).pdf
following applies:

.1 ships shall have two non -magnetic means to determine and display their heading. Both means shall be independent and shall be connected to the ship's main and emergency source of power; and

.2 ships proceeding to latitudes over 80° shall be fitted with at least one GNSS compass or equivalent, which shall be connected to the ship's main and emergency source of power.

9.3.3 Additional navigational equipment

9.3.3.1 In order to comply with the functional requirement of paragraph 9.2.3.1, ships, with the exception of those solely operating in areas with 24 h daylight, shall be equipped with two remotely rotatable, narrow-beam search lights controllable from the bridge to provide lighting over an arc of 360°, or other means to visually detect ice.

9.3.3.2 In order to comply with the functional requirement of paragraph 9.2.3.2, ship s involved in operations with an icebreaker escort shall be equipped with a manually initiated flashing red light visible from astern to indicate when the ship is stopped. This light shall have a range of visibility of at least two nautical miles, and the horizontal and vertical arcs of

---CHUNK---

SOURCE: MEPC.264(68).pdf
flashing red light visible from astern to indicate when the ship is stopped. This light shall have a range of visibility of at least two nautical miles, and the horizontal and vertical arcs of visibility shall conform to the stern light specifications required by the International Regulations for Preventing Collisions at Sea.

CHAPTER 10 COMMUNICATION

10.1 Goal

The goal of this chapter is to provide for effective communication for ships and survival craft during normal operation and in emergency situations.

10.2 Functional requirements

In order to achieve the goal set out in paragraph 10.1 above, the following functional requirements are embodied in the regulations of this chapter.

RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 27 -

10.2.1 Ship communication

10.2.1.1 Two-way voice and/or data communications ship- to-ship and ship-to-shore shall be available at all points along the intended operating routes.

10.2.1.2 Suitable means of communications shall be provided where escort and convoy operations are expected.

---CHUNK---

SOURCE: MEPC.264(68).pdf
available at all points along the intended operating routes.

10.2.1.2 Suitable means of communications shall be provided where escort and convoy operations are expected.

10.2.1.3 Means for two-way on-scene and SAR coordination communications for search and rescue purposes including aeronautical frequencies shall be provided.

10.2.1.4 Appropriate communication equipment to enable telemedical assistance in polar areas shall be provided.

10.2.2 Survival craft and rescue boat communications capabilities

10.2.2.1 For ships intended to operate in low air temperature, all rescue boats and lifeboats, whenever released for evacuation, shall maintain capability for distress alerting, locating and on-scene communications.

10.2.2.2 For ships intended to operate in low air temperature, all other survival craft, whenever released, shall maintain capability for transmitting signals for location and for communication.

10.2.2.3 Mandatory communication equipment for use in survival craft, including liferafts and rescue boats, shall be capable of operation during the maximum expected time of rescue.

10.3 Regulations

10.3.1 Ship communication

---CHUNK---

SOURCE: MEPC.264(68).pdf
10.2.2.3 Mandatory communication equipment for use in survival craft, including liferafts and rescue boats, shall be capable of operation during the maximum expected time of rescue.

10.3 Regulations

10.3.1 Ship communication

10.3.1.1 In order to comply with the functional requirements of paragraph 10.2.1.1 above, communication equipment on board shall have the capabilities for ship- to-ship and ship-to-shore communication, taking into account the limitations of communications systems in high latitudes and the anticipated low temperature.