Oil Record Books, manuals and the shipboard oil pollution eme rgency plan or the shipboard marine pollution emergency plan as required by MARPOL Annex I.

1.2 Structural requirements

---CHUNK---

SOURCE: MEPC.264(68).pdf
Oil Record Books, manuals and the shipboard oil pollution eme rgency plan or the shipboard marine pollution emergency plan as required by MARPOL Annex I.

1.2 Structural requirements

1.2.1 For category A and B ships constructed on or after 1 January 2017 with an aggregate oil fuel capacity of less than 600 m 3, all oil fuel tanks shall be separated from the outer shell by a distance of not less than 0.76 m. This provision does not apply to small oil fuel tanks with a maximum individual capacity not greater than 30 m3.

1.2.2 For category A and B ships other than oil tankers constructed on or after 1 January 2017, all cargo tanks constructed and utilized to carry oil shall be separated from the outer shell by a distance of not less than 0.76 m.

1.2.3 For category A and B oil tankers of less than 5,000 tonnes deadweight constructed on or after 1 January 2017, the entire cargo tank length shall be protected with:

.1 double bottom tanks or spaces complying with the applicable requirements of regulation 19.6.1 of MARPOL Annex I; and

.2 wing tanks or spaces arranged in accordance with regulation 19.3.1 of

---CHUNK---

SOURCE: MEPC.264(68).pdf
.1 double bottom tanks or spaces complying with the applicable requirements of regulation 19.6.1 of MARPOL Annex I; and

.2 wing tanks or spaces arranged in accordance with regulation 19.3.1 of MARPOL Annex I and complying with the applicable requirements for distance referred to in regulation 19.6.2 of MARPOL Annex I.

1.2.4 For category A and B ships constructed on or after 1 January 2017 all oil residue (sludge) tanks and oily bilge water holding tanks shall be separated from the outer shell by a distance of not less than 0.76 m. This provision does not apply to small tanks with a maximum individual capacity not greater than 30 m3.

RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 41 -

CHAPTER 2 CONTROL OF POLLUTION BY NOXIOUS LIQUID SUBSTANCES IN BULK

2.1 Operational requirements

2.1.1 In Arctic waters any discharge into the sea of noxious liquid substances (NLS), or mixtures containing such substances, shall be prohibited.

2.1.2 Operation in polar waters shall be taken into account, as appropriate, in the

---CHUNK---

SOURCE: MEPC.264(68).pdf
2.1.1 In Arctic waters any discharge into the sea of noxious liquid substances (NLS), or mixtures containing such substances, shall be prohibited.

2.1.2 Operation in polar waters shall be taken into account, as appropriate, in the Cargo Record Book, the Manual and the shipboard marine pollution emergency plan for noxious liquid substances or the shipboard marine pollution emergency plan as required by MARPOL Annex II.

2.1.3 For category A and B ships constructed on or after 1 January 2017, the carriage of NLS identified in chapter 17, column e, as ship type 3 or identified as NLS in chapter 18 of the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk , in cargo tanks of type 3 ships shall be subject to the approval of the Administration. The results shall be reflected on the International Pollution Prevention Certificate for the Carriage of Noxious Liquid Substances in Bulk or Certificate of Fitness identifying the operation in polar waters.

CHAPTER 3 PREVENTION OF POLLUTION BY HARMFUL SUBSTANCES CARRIED BY SEA IN PACKAGED FORM

Kept blank intentionally.

---CHUNK---

SOURCE: MEPC.264(68).pdf
identifying the operation in polar waters.

CHAPTER 3 PREVENTION OF POLLUTION BY HARMFUL SUBSTANCES CARRIED BY SEA IN PACKAGED FORM

Kept blank intentionally.

CHAPTER 4 PREVENTION OF POLLUTION BY SEWAGE FROM SHIPS

4.1 Definitions

4.1.1 Constructed means a ship the keel of which is laid or which is at a similar stage of construction.

4.1.2 Ice-shelf means a floating ice sheet of considerable thickness, showing 2 to 50 m or more above sea-level, attached to the coast.

4.1.3 Fast ice means sea ice which forms and remains fast along the coast, where it is attached to the shore, to an ice wall, to an ice front, between shoals or grounded icebergs.

4.2 Operational requirements

4.2.1 Discharges of sewage within polar waters are prohibited except when performed in accordance with MARPOL Annex IV and the following requirements:

.1 the ship is discharging comminuted and disinfected sewage in accordance with regulation 11.1.1 of MARPOL Annex IV at a distance of more than three nautical miles from any ice-shelf or fast ice and shall be as far as practicable from areas of ice concentration exceeding 1/10; or

---CHUNK---

SOURCE: MEPC.264(68).pdf
with regulation 11.1.1 of MARPOL Annex IV at a distance of more than three nautical miles from any ice-shelf or fast ice and shall be as far as practicable from areas of ice concentration exceeding 1/10; or

.2 the ship is discharging sewage that is not comminuted or disinfected in accordance with regulation 11.1.1 of MARPOL Annex IV and at a distance of more than 12 nautical miles from any ice-shelf or fast ice and shall be as far as practicable from areas of ice concentration exceeding 1/10; or

.3 the ship has in operation an approved sewage treatment plant certified by the Administration to meet the operational requirements in either regulation 9.1.1 or 9.2.1 of MARPOL Annex IV, and discharges sewage in accordance with regulation 11.1.2 of Annex IV and shall be as far as practicable from the nearest land, any ice-shelf, fast ice or areas of ice concentration exceeding 1/10.

4.2.2 Discharge of sewage into the sea from category A and B ships constructed on or

---CHUNK---

SOURCE: MEPC.264(68).pdf
practicable from the nearest land, any ice-shelf, fast ice or areas of ice concentration exceeding 1/10.

4.2.2 Discharge of sewage into the sea from category A and B ships constructed on or after 1 January 2017 and all passenger ships constructed on or after 1 January 2017 is prohibited, except when such discharges are in compliance with paragraph 4.2.1.3 of this chapter.

4.2.3 Notwithstanding the requirements of paragraph 4.2.1, category A and B ships that operate in areas of ice concentrations exceeding 1/10 for extended periods of time, may only discharge sewage using an approved sewage treatment plant certified by the Administration to meet the operational requirements in regulation 9.1.1 or 9.2.1 of MARPOL Annex IV. Such discharges shall be subject to approval by the Administration.

CHAPTER 5 PREVENTION OF POLLUTION BY GARBAGE FROM SHIPS

5.1 Definitions

5.1.1 Ice-shelf means a floating ice sheet of considerable thickness, showing 2 to 50 m or more above sea-level, attached to the coast.

5.1.2 Fast ice means sea ice which forms and remains fast along the coast, where it is

---CHUNK---

SOURCE: MEPC.264(68).pdf
5.1 Definitions

5.1.1 Ice-shelf means a floating ice sheet of considerable thickness, showing 2 to 50 m or more above sea-level, attached to the coast.

5.1.2 Fast ice means sea ice which forms and remains fast along the coast, where it is attached to the shore, to an ice wall, to an ice front, between shoals or grounded icebergs

5.2 Operational requirements

5.2.1 In Arctic waters, discharge of garbage into the sea permitted in accordance with