regulation 4 of MARPOL Annex V shall meet the following additional requirements:

.1 discharge into the sea of food wastes is only permitted when the ship is as far as practicable from areas of ice concentration exceeding 1/10, but in any case not less than 12 nautical miles from the nearest land, nearest ice-shelf, or nearest fast ice;

.2 food wastes shall be comminuted or ground and shall be capable of passing through a screen with openings no greater than 25 mm. Food wastes shall not be contaminated by any other garbage type;

.3 food wastes shall not be discharged onto the ice;

.4 discharge of animal carcasses is prohibited; and

.5 discharge of cargo residues that cannot be recovered using commonly

---CHUNK---

SOURCE: MEPC.264(68).pdf
wastes shall not be contaminated by any other garbage type;

.3 food wastes shall not be discharged onto the ice;

.4 discharge of animal carcasses is prohibited; and

.5 discharge of cargo residues that cannot be recovered using commonly available methods for unloading shall only be permitted while the ship is en route and where all of the following conditions are satisfied:

.1 cargo residues, cleaning agents or additives, contained in hold washing water do not include any substances classified as harmful to the marine environment, taking into account guidelines developed by the Organization;

.2 both the port of departure and the next port of destination are within Arctic waters and the ship will not transit outside Arctic waters between those ports;

.3 no adequate reception facilities are available at those por ts, taking into account guidelines developed by the Organization; and

.4 where the conditions of subparagraphs 5.2.1.5.1, 5.2.1.5.2 and 5.2.1.5.3 of this paragraph have been fulfilled, discharge of

---CHUNK---

SOURCE: MEPC.264(68).pdf
into account guidelines developed by the Organization; and

.4 where the conditions of subparagraphs 5.2.1.5.1, 5.2.1.5.2 and 5.2.1.5.3 of this paragraph have been fulfilled, discharge of cargo hold washing water containing residues shall be made as far as practicable from areas of ice concentration exceeding 1/10, but in any case not less than 12 nautical miles from the nearest land, nearest ice shelf, or nearest fast ice.

5.2.2 In the Antarctic area, discharge of garbage into the sea permitted in accordance with regulation 6 of MARPOL Annex V shall meet the following additional requirements:

.1 discharges under regulation 6.1 of MARPOL Annex V shall be as far as practicable from areas of ice concentration exceeding 1/10, but in any case not less than 12 nautical miles from the nearest fast ice; and

.2 food waste shall not be discharged onto ice.

5.2.3 Operation in polar waters shall be taken into account, as appropriate, in the Garbage Record Book, Garbage Management Plan and the placards as required by MARPOL Annex V.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 44 -

---CHUNK---

SOURCE: MEPC.264(68).pdf
Garbage Record Book, Garbage Management Plan and the placards as required by MARPOL Annex V.
RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)
INTERNATIONAL CODE FOR SHIPS OPERATING IN POLAR WATERS (POLAR CODE)- 44 -

PART II-B

ADDITIONAL GUIDANCE REGARDING THE PROVISIONS OF THE INTRODUCTION AND PART II-A

1 Additional guidance to chapter 1

1.1 Ships are encouraged to apply regulation 43 of MARPOL Annex I when operating in Arctic waters.

1.2 Non-toxic biodegradable lubricants or water-based systems should be considered in lubricated components located outside the underwater hull with direct seawater interfaces, like shaft seals and slewing seals.

2 Additional guidance to chapter 2

Category A and B ships, constructed on or after 1 January 2017 and certified to carry noxious liquid substances (NLS), are encouraged to carry NLS identified in chapter 17, column e, as ship type 3 or identified as NLS in chapter 18 of the International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk , in tanks separated from the outer shell by a distance of not less than 760 mm.

3 Additional guidance to chapter 5

---CHUNK---

SOURCE: MEPC.264(68).pdf
Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk , in tanks separated from the outer shell by a distance of not less than 760 mm.

3 Additional guidance to chapter 5

In order to minimize the risks associated with animal cargo mortalities, consideration should be given to how animal carcasses will be managed, treated and stored on board when ships carrying such cargo are operating in polar waters. Reference is made in particular to the 2012 Guidelines for the implementation of MARPOL Annex V (resolution MEPC.219(63), as amended by resolution MEPC.239(65)) and the 2012 Guidelines for the development of garbage management plans (resolution MEPC.220(63)).

4 Additional guidance under other environmental conventions and guidelines

4.1 Until the International Convention for the Control and Management of Ships ' Ballast Water and Sediments enters into force, the ballast water management provisions of the ballast water exchange standard, set out in regulation D-1, or the ballast wat er performance standard, set out in regulation D -2 of the Convention should be considered as appropriate.

---CHUNK---

SOURCE: MEPC.264(68).pdf
ballast water exchange standard, set out in regulation D-1, or the ballast wat er performance standard, set out in regulation D -2 of the Convention should be considered as appropriate. The provisions of the Guidelines for ballast water exchange in the Antarctic treaty area (resolution MEPC.163(56)) should be taken into consideration , along with other relevant guidelines developed by the Organization.

4.2 In selecting the ballast water management system, attention should be paid to limiting conditions specified in the appendix of the Type Approval Certificate and the temperature under which the system has been tested, in order to ensure its suitability and effectiveness in polar waters.

4.3 In order to minimize the risk of invasive aquatic species transfers via biofouling, measures should be considered to minimize the risk of more rapid degradation of anti-fouling coatings associated with polar ice operations. Reference is made in particular to the 2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC.207(62)).

RESOLUTION MEPC.264(68)
(adopted on 15 May 2015)

---CHUNK---

SOURCE: MEPC.264(68).pdf
2011 Guidelines for the control and management of ships ' biofouling to minimize the transfer of invasive aquatic species (resolution MEPC.207(62)).

Table: Example of matters related to anti-fouling systems taken into consideration by some ice-going ships
(this table is used by some operators of ice-going ships)

Hull Sea chest	
Year round operation in ice-covered polar waters	Abrasion resistant coating. Compliant with the AFS Convention. Thickness of anti-fouling system to be decided by shipowner.
Intermittent operation in	