Reference line value = a · bc

where a, b and c are the parameters given in table 2.

Table 2 - Parameters for the determination of reference values for the different ship types

Ship type defined in regulation 2 a b c

---CHUNK---

SOURCE: MEPC.328(76).pdf
Reference line value = a · bc

where a, b and c are the parameters given in table 2.

Table 2 - Parameters for the determination of reference values for the different ship types

Ship type defined in regulation 2 a b c
2.2.5 Bulk carrier 961.79 DWT of the ship
where
DWT279,000

279,000 where
DWT > 279,000
0.477
2.2.7 Combination carrier 1,219.00 DWT of the ship 0.488
2.2.9 Containership 174.22 DWT of the ship 0.201
2.2.11 Cruise passenger ship
having non-conventional
propulsion
170.84 GT of the ship 0.214
2.2.14 Gas carrier 1,120.00 DWT of the ship 0.456
2.2.15 General cargo ship 107.48 DWT of the ship 0.216
2.2.16 LNG carrier 2,253.7 DWT of the ship 0.474
2.2.22 Refrigerated cargo carrier 227.01 DWT of the ship 0.244
2.2.26 Ro-ro cargo ship 1405.15 DWT of the ship

0.498
1686.17* DWT of the ship
where
DWT17,000*

17,000 where
DWT > 17,000*
2.2.27 Ro -ro cargo ship (vehicle
carrier)
(DWT/GT)-
0.7 · 780.36
where DWT/GT < 0.3
1,812.63
where DWT/GT 0.3
DWT of the ship

0.471
2.2.28 Ro-ro passenger ship 752.16 DWT of the ship

0.381
902.59* DWT of the ship
where
DWT10,000*

10,000 where
DWT > 10,000*

---CHUNK---

SOURCE: MEPC.328(76).pdf
(DWT/GT)-
0.7 · 780.36
where DWT/GT < 0.3
1,812.63
where DWT/GT 0.3
DWT of the ship

0.471
2.2.28 Ro-ro passenger ship 752.16 DWT of the ship

0.381
902.59* DWT of the ship
where
DWT10,000*

10,000 where
DWT > 10,000*
2.2.29 Tanker 1,218.80 DWT of the ship 0.488
* to be used from phase 2 and thereafter.

4 If the design of a ship allows it to fall into more than one of the ship type definitions specified in table 2, the required EEDI for the ship shall be the most stringent (the lowest) required EEDI.

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 40 -

5 For each ship to which this regulation applies, the installed propulsion power shall not be less than the propulsion power needed to maintain the manoeuvrability of the ship under adverse conditions as defined in the guidelines to be developed by the Organization.

6 At the beginning of phase 1 and at the midpoint of phase 2, the Organization shall

---CHUNK---

SOURCE: MEPC.328(76).pdf
adverse conditions as defined in the guidelines to be developed by the Organization.

6 At the beginning of phase 1 and at the midpoint of phase 2, the Organization shall review the status of technological developments and, if proven necessary, amend the time periods, the EEDI reference line parameters for relevant ship types and reduction rates set out in this regulation.

Regulation 25
Required EEXI

1 For:

.1 each ship; and

.2 each ship which has undergone a major conversion

which falls into one of the categories in regulations 2.2.5, 2.2.7, 2.2.9, 2.2.11, 2.2.14 to 2.2.16, 2.2.22, and 2.2.26 to 2.2.29 and to which this chapter is applicable, the attained EEXI shall be as follows:

Attained EEXI Required EEXI = (1
Y
100) EEDI reference line value

where Y is the reduction factor specified in Table 3 for the required EEXI compared to the EEDI reference line.

Table 3 - Reduction factors (in percentage) for the EEXI relative to the EEDI reference line

Ship type Size Reduction factor
Bulk carrier
200,000 DWT and above 15
20,000 and above but less than 200,000 DWT 20
10,000 and above but less than 20,000 DWT 0-20*
Gas carrier

---CHUNK---

SOURCE: MEPC.328(76).pdf
line

Ship type Size Reduction factor
Bulk carrier
200,000 DWT and above 15
20,000 and above but less than 200,000 DWT 20
10,000 and above but less

than 20,000 DWT 0-20*
Gas carrier
15,000 DWT and
above 30
10,000 and above but less
than 15,000 DWT 20
2,000 and above but less
than 10,000 DWT 0-20*
Tanker
200,000 DWT and
above 15
20,000 and above but less
than 200,000 DWT 20
4,000 and above but less
than 20,000 DWT
0-20*

Containership 200,000 DWT and above 50
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 41 -