.7 a description of the control measures taken by the proposing Party or Parties addressing land-based sources of NO x, SO x and particulate matter emissions affecting the human populations and environmental areas at risk that are in place and operating concurrently with the consideration of measures to be adopted in relation to provisions of regulations 13 and 14 of Annex VI; and

.8 the relative costs of reducing emissions from ships when compared with land-based controls, and the economic impacts on shipping engaged in international trade.

3.2 The geographical limits of an emission control area will be based on the relevant criteria outlined above, including emissions and deposition from ships navigating in the proposed area, traffic patterns and density, and wind conditions.

---CHUNK---

SOURCE: MEPC.328(76).pdf
3.2 The geographical limits of an emission control area will be based on the relevant criteria outlined above, including emissions and deposition from ships navigating in the proposed area, traffic patterns and density, and wind conditions.

4 Procedures for the assessment and adoption of emission control areas by the Organization

4.1 The Organization shall consider each proposal submitted to it by a Party or Parties.

4.2 In assessing the proposal, the Organization shall take into account the criteria that are to be included in each proposal for adoption as set forth in section 3 above.

4.3 An emission control area shall be designated by means of an amendment to this Annex, considered, adopted and brought into force in accordance with article 16 of the present Convention.

5 Operation of emission control areas

5.1 Parties that have ships navigatin g in the area are encouraged to bring to the Organization any concerns regarding the operation of the area.

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS,

---CHUNK---

SOURCE: MEPC.328(76).pdf
Organization any concerns regarding the operation of the area.

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS,
1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 60 -

Appendix IV

Type approval and operating limits for shipboard incinerators (regulation 16)

1 Shipboard incinerators described in regulation 16.6.1 shall possess an IMO Type Approval Certificate for each incinerator. In order to obtain such certificate, the incinerator shall be designed and built to an approved standard as described in regulation 16.6.1. Each model shall be subject to a specified type approval test operation at the factory or an approved test facility, and under the responsibility of the Administration, using the following standard fuel/waste specification for the type approval test for determining whether the incinerator operates within the limits specified in paragraph 2 of this appendix:

Sludge oil consisting of: 75% sludge oil from heavy fuel oil (HFO);
5% waste lubricating oil; and
20% `emulsified water.

Solid waste consisting of: 50% food waste;

---CHUNK---

SOURCE: MEPC.328(76).pdf
operates within the limits specified in paragraph 2 of this appendix:

Sludge oil consisting of: 75% sludge oil from heavy fuel oil (HFO);
5% waste lubricating oil; and
20% `emulsified water.

Solid waste consisting of: 50% food waste;
50% rubbish containing:
approx. 30% paper,
  " 40% cardboard,
  " 10% rags,
  " 20% plastic.

 The mixture will have up to 50% moisture and
7% incombustible solids.

2 Incinerators described in regulation 16.6.1 shall operate within the following limits:

O2 in combustion chamber:

6 -12%
CO in flue gas maximum average:

200 mg/MJ
Soot number maximum average: Bacharach 3 or Ringelmann 1
(20% opacity) (a higher soot number is
acceptable only during very short periods
such as starting up)

Unburned components in ash residues:

Maximum 10% by weight
Combustion chamber flue gas outlet
temperature range:

850 -1200°C

RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 61 -

Appendix V

---CHUNK---

SOURCE: MEPC.328(76).pdf
RESOLUTION MEPC.328(76)
AMENDMENTS TO THE ANNEX OF THE PROTOCOL OF 1997 TO AMEND THE INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM SHIPS, 1973, AS MODIFIED BY THE PROTOCOL OF 1978 RELATING THERETO- 61 -

Appendix V

Information to be included in the bunker delivery note (regulation 18.5)

1 Name and IMO number of receiving ship

2 Port

3 Date of commencement of delivery

4 Name, address and telephone number of marine fuel oil supplier

5 Product name(s)

6 Quantity in metric tonnes

7 Density at 15°C (kg/m3)

8 Sulphur content (% m/m)

9 A declaration signed and certified by the fuel oil supplier's representative that the fuel oil supplied is in conformity with regulation 18.3 of this Annex and that the sulphur content of the fuel oil supplied does not exceed:

the limit value given by regulation 14.1 of this Annex;

the limit value given by regulation 14.4 of this Annex; or

the purchaser's specified limit value of _____ (% m/m), as completed by the fuel oil supplier 's representative and on the basis of the purchaser 's notification that the fuel oil:

---CHUNK---

SOURCE: MEPC.328(76).pdf
the purchaser's specified limit value of _____ (% m/m), as completed by the

fuel oil supplier 's representative and on the basis of the purchaser 's notification that the fuel oil:

.1 is intended to be used in combinat ion with an equivalent means of compliance in accordance with regulation 4 of this Annex; or

.2 is subject to a relevant exemption for a ship to conduct trials for sulphur oxides emission reduction and control technology research in accordance with regulation 3.2 of this Annex.

The declaration shall be completed by the fuel oil supplier's representative by marking the applicable box(es) with a cross (x).

Appendix VI

Verification procedures for a MARPOL Annex VI fuel oil sa mple (regulation 18.8.2 or regulation 14.8)

The following relevant verification procedure shall be used to determine whether the fuel oil