Required
EEDI
Attained
EEDI
Vref
(knot)

(9)
PME
(kW)

(10)
Type

---CHUNK---

SOURCE: MEPC.332(76).pdf
IMO
Number

(1)
Type
of
ship

(2)
Common
commercial
size

(3)
Capacity

(4)
Dimensional
parameters
Year of
delivery
Applicable
phase
Required
EEDI
Attained
EEDI
Vref
(knot)

(9)
PME
(kW)

(10)

Type
of
fuel

(11)
fDF
gas

(12)
Ice
class

(13)
EEDI 4th term
(Installation of
innovative electrical
technology)
EEDI 5th term
(Installation of
innovative
mechanical
technology)
Short
statement
as
appropriate
describing
the principal
design
elements or
changes
employed to
achieve the
attained
EEDI

(15)
DWT
GT

(5)
Lpp
(m)

(6)
Bs
(m)

(7)
Draught
(m)

(8)
Yes/

No
Name,
outline and
means/
ways of
performance
of
technology
(14)
Yes/
No
Name,
outline
and
means/
ways of
performan
ce of
technology
(14)

Note:
(1) IMO number to be submitted for Secretariat use only.
(2) As defined in regulation 2 of MARPOL Annex VI.
(3) Common commercial size reference (TEU for containership, CEU (RT43) for ro-ro cargo ship (vehicle carrier), cubic meter for gas carrier and LNG carrier), if available, should be provided.

---CHUNK---

SOURCE: MEPC.332(76).pdf
(2) As defined in regulation 2 of MARPOL Annex VI.
(3) Common commercial size reference (TEU for containership, CEU (RT43) for ro-ro cargo ship (vehicle carrier), cubic meter for gas carrier and LNG carrier), if available, should be provided.
(4) The exact DWT or GT, as appropriate, should be provided. The Secretariat should round the DWT or GT data up to the nearest 500 when these data are subsequently provided to MEPC.
(For containerships, 100% DWT should be provided while 70% of DWT should be used when calculating the EEDI value).
(5) GT should be provided for a cruise passenger ship having non-conventional propulsion as defined in regulations 2.2.11and 2.2.19, respectively, of MARPOL Annex VI.
Both DWT and GT should be provided for a ro-ro cargo ship (vehicle carrier) as defined in regulation 2.2.27 of MARPOL Annex VI.
(6) As defined in paragraph 2.2.13 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended).
The exact Lpp should be provided. The Secretariat will round the Lpp data up to the nearest 10 when these data are subsequently provided to MEPC.

---CHUNK---

SOURCE: MEPC.332(76).pdf
The exact Lpp should be provided. The Secretariat will round the Lpp data up to the nearest 10 when these data are subsequently provided to MEPC.
(7) As defined in paragraph 2.2.16 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency

Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended).
The exact Bs should be provided. The Secretariat will round the Bs data up to the nearest 1 when these data are subsequently provided to MEPC.
(8) As defined in paragraph 2.2.15 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended).
The exact draught should be provided. The Secretariat will round the draught data up to the nearest 1 when these data are subsequently provided to MEPC.
(9) As defined in paragraph 2.2.2 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended).
The exact Vref should be provided. The Secretariat will round the Vref data up to the nearest 0.5 when these data are subsequently provided to MEPC.

---CHUNK---

SOURCE: MEPC.332(76).pdf
The exact Vref should be provided. The Secretariat will round the Vref data up to the nearest 0.5 when these data are subsequently provided to MEPC.
(10) As defined in paragraph 2.2.5.1 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended).
The exact PME should be provided. The Secretariat will round the PME data up to the nearest 100 when these data are subsequently provided to MEPC.
(11) As defined in paragraph 2.2.1 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308(73), as amended) or other (to be stated).
In case of a ship equipped with a dual-fuel engine, type of "primary fuel" should be provided.
(12) As defined in paragraph 2.2.1 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308 (73), as amended), if applicable.

---CHUNK---

SOURCE: MEPC.332(76).pdf
(12) As defined in paragraph 2.2.1 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design Index (EEDI) for new ships (resolution MEPC.308 (73), as amended), if applicable.
(13) Ice class, which was used to calculate correction factors for ice-classed ships as defined in paragraphs 2.2.8.1 and 2.2.11.1 of the 2018 Guidelines on the method of calculation of the attained Energy Efficiency Design
Index (EEDI) for new ships (resolution MEPC.308(73), as amended), if applicable, should be provided.
(14) In the case that the innovative energy efficiency technologies are already included in the 2013 Guidance on treatment of innovative energy efficiency technologies for calculation and verification of the attained EEDI
(MEPC.1/Circ.815), the name of technology should be identified. Otherwise, name, outline and means/ways of performance of the technology should be identified.
(15) To assist the IMO in assessing relevant design trends, provide a short statement as appropriate, describing the principal design elements or changes employed to achieve the attained EEDI.
"
***
RESOLUTION MEPC.332(76) (adopted on 17 June 2021)

---CHUNK---

SOURCE: MEPC.332(76).pdf