DWTS,service is the deadweight under the design load draught;

PS,service is the power of the main engine corresponding to VS,service;

k is the scale coefficient, which should be:

.1 0.95 for containerships with 120,000 DWT or less;

.2 0.93 for containerships with more than 120,000 DWT;

.3 0.97 for bulk carrier with 200,000 DWT or less;

.4 1.00 for bulk carrier with more than 200,000 DWT;

.5 0.97 for tanker with 100,000 DWT or less; and

.6 1.00 for tanker with more than 100,000 DWT.

---CHUNK---

SOURCE: MEPC.333(76).pdf
.3 0.97 for bulk carrier with 200,000 DWT or less;

.4 1.00 for bulk carrier with more than 200,000 DWT;

.5 0.97 for tanker with 100,000 DWT or less; and

.6 1.00 for tanker with more than 100,000 DWT.

2.2.3.5 In cases where the speed-power curve is not available or the sea trial report does not contain the EEDI or design load draught condition, the ship speed V ref can be approximated by Vref,app to be obtained from statistical mean of distribution of ship speed and engine power, as defined below:

, = (,) ×

0.75×

1
3
[knot]

For LNG carriers having diesel electric propulsion system and cruise passenger ship having non-conventional propulsion,

, = (,) ×

1
3
[knot]

where,

Vref,avg is a statistical mean of distribution of ship speed in given ship type and

---CHUNK---

SOURCE: MEPC.333(76).pdf
Annex 7, page 6

I:\MEPC\76\MEPC 76-15-Add.2.docx
where,

Vref,avg is a statistical mean of distribution of ship speed in given ship type and ship size, to be calculated as follows:

, = ×

wher
e

A, B and C are the parameters given in the appendix;

mV is a performance margin of a ship, which should be 5% of Vref,avg or one knot, whichever is lower; and

MCRavg is a statistical mean of distribution of MCRs for main engines and MPPavg is a statistical mean of distribution of MPPs for motors in given ship type and ship size, to be calculated as follows:

= ×

wher
e

D, E and F are the parameters given in the appendix;

In cases where the overridable Shaft / Engine Power Limitation is installed, the ship speed Vref approximated by Vref,app should be calculated as follows:

, = (,) ×

0.75×

1
3
[knot]

For LNG carriers having diesel electric propulsion system and cruise passenger ship

having non- conventional propulsion, the ship speed V ref approximated by V ref,app should be calculated as follows:

---CHUNK---

SOURCE: MEPC.333(76).pdf
0.75×

1
3
[knot]

For LNG carriers having diesel electric propulsion system and cruise passenger ship having non- conventional propulsion, the ship speed V ref approximated by V ref,app should be calculated as follows:

, = , ×
1
3

2.2.3.6 Notwithstanding the above, in cases where the energy saving device * is installed, the effect of the device may be reflected in the ship speed V ref with the approval of the verifier, based on the following methods in accordance with defined quality and technical standards:

.1 sea trials after installation of the device; and/or

.2 dedicated model tests; and/or

.3 numerical calculations.

* Devices that shift the power curve, which results in the change of PP and Vref, as specified in MEPC.1/Circ.815 on 2013 Guidance on treatment of innovative energy efficiency technologies for calculation and verification of the attained EEDI.
RESOLUTION MEPC.333(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 7, page 7

---CHUNK---

SOURCE: MEPC.333(76).pdf
the attained EEDI.
RESOLUTION MEPC.333(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 7, page 7

I:\MEPC\76\MEPC 76-15-Add.2.docx
2.2.4 SFC; Certified specific fuel consumption

In cases where overridable Shaft / Engine Power Limitation is installed, the SFC corresponding to the PME should be interpolated by using SFCs listed in an applicable test report included in

an approved NOX Technical File of the main engine as defined in paragraph 1.3.15 of the NOX Technical Code.

Notwithstanding the above, the SFC specified by the manufacturer or confirmed by the verifier may be used.

For those engines which do not have a test report included in the NOX Technical File and which do not have the SFC specified by the manufacturer or confirmed by the verifier, the SFC can be approximated by SFCapp defined as follows:

, = 190 [ ]

, = 215 [ ]

2.2
.5 CF ; Conversion factor between fuel consumption and CO2 emission

---CHUNK---

SOURCE: MEPC.333(76).pdf
be approximated by SFCapp defined as follows:

, = 190 [ ]

, = 215 [ ]