2.2
.5 CF ; Conversion factor between fuel consumption and CO2 emission

For those engines which do not have a test report included in the NOX Technical File and which do not have the SFC specified by the manufacturer, the CF corresponding to SFCapp should be defined as follows:

= 3.114 [2/] f or diesel ships (incl. HFO use in practice)

Ot
herwise, paragraph 2.2.1 of the EEDI Calculation Guidelines applies.

2.2.6 Correction factor for ro-ro cargo and ro-ro passenger ships (fjRoRo)

For ro-ro cargo and ro-ro passenger ships, fjRoRo is calculated as follows:

=
1
1 3 ; if fjRoRo > 1 then fj = 1

wher
e the Froude number, , is defined as:

=
0.5144,

where , is the ship design speed corresponding to 75% of MCRME.:

and the exponents , , and are defined as follows:

Ship type Exponent:

Ro-ro cargo ship 2.00 0.50 0.75 1.00

---CHUNK---

SOURCE: MEPC.333(76).pdf
0.5144,

where , is the ship design speed corresponding to 75% of MCRME.:

and the exponents , , and are defined as follows:

Ship type Exponent:

Ro-ro cargo ship 2.00 0.50 0.75 1.00
Ro-ro passenger ship 2.50 0.75 0.75 1.00

2.2.7 Cubic capacity correction factor for ro-ro cargo ships (vehicle carrier) (fcVEHICLE)

For ro-ro cargo ships (vehicle carrier) having a DWT/GT ratio of less than 0.35, the following cubic capacity correction factor, fcVEHICLE, should apply:

=
0.35 0,8

Where DWT is the capacity and GT is the gross tonnage in accordance with the International Convention of Tonnage Measurement of Ships 1969, annex I, regulation 3.

---CHUNK---

SOURCE: MEPC.333(76).pdf
RESOLUTION MEPC.333(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 7, page 9

I:\MEPC\76\MEPC 76-15-Add.2.docx
APPENDIX

Parameters to calculate Vref,avg

Ship type A B C
Bulk carrier 10.6585 DWT of the ship 0.02706
Gas carrier 7.4462 DWT of the ship 0.07604
Tanker 8.1358 DWT of the ship 0.05383
Containership 3.2395
DWT of the ship
where DWT 80,000
80,000
where DWT > 80,000
0.18294
General cargo ship 2.4538 DWT of the ship 0.18832
Refrigerated cargo carrier 1.0600 DWT of the ship 0.31518
Combination carrier 8.1391 DWT of the ship 0.05378
LNG carrier 11.0536 DWT of the ship 0.05030
Ro-ro cargo ship (vehicle carrier) 16.6773 DWT of the ship 0.01802
Ro-ro cargo ship 8.0793 DWT of the ship 0.09123
Ro-ro passenger ship 4.1140 DWT of the ship 0.19863
Cruise passenger ship having
non-conventional propulsion 5.1240 GT of the ship 0.12714

Parameters to calculate MCRavg or MPPavg (= D x EF)

Ship type D E F
Bulk carrier 23.7510 DWT of the ship 0.54087
Gas carrier 21.4704 DWT of the ship 0.59522
Tanker 22.8415 DWT of the ship 0.55826

---CHUNK---

SOURCE: MEPC.333(76).pdf
Parameters to calculate MCRavg or MPPavg (= D x EF)

Ship type D E F
Bulk carrier 23.7510 DWT of the ship 0.54087
Gas carrier 21.4704 DWT of the ship 0.59522
Tanker 22.8415 DWT of the ship 0.55826
Containership 0.5042
DWT of the ship
where DWT 95,000
95,000
where DWT > 95,000
1.03046
General cargo ship 0.8816 DWT of the ship 0.92050
Refrigerated cargo carrier 0.0272 DWT of the ship 1.38634
Combination carrier 22.8536 DWT of the ship 0.55820
LNG carrier 20.7096 DWT of the ship 0.63477
Ro-ro cargo ship (vehicle carrier) 262.7693 DWT of the ship 0.39973
Ro-ro cargo ship 37.7708 DWT of the ship 0.63450
Ro-ro passenger ship 9.1338 DWT of the ship 0.91116
Cruise passenger ship having non -
conventional propulsion 1.3550 GT of the ship 0.88664

RESOLUTION MEPC.333(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE METHOD OF CALCULATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 7, page 10

I:\MEPC\76\MEPC 76-15-Add.2.docx
Calculation of parameters to calculate Vref,avg and MCRavg

Data sources

1 IHS Fairplay (IHSF) database with the following conditions are used.

Ship type Ship size Delivered period

---CHUNK---

SOURCE: MEPC.333(76).pdf
Annex 7, page 10

I:\MEPC\76\MEPC 76-15-Add.2.docx
Calculation of parameters to calculate Vref,avg and MCRavg

Data sources

1 IHS Fairplay (IHSF) database with the following conditions are used.

Ship type	Ship size	Delivered period	Type of propulsion systems	Population
Bulk carrier	10,000 DWT	From 1 January 1999 to 1 January 2009	Conventional	2,433
Gas carrier	2,000 DWT		Conventional	292
Tanker	4,000 DWT		Conventional	3,345
Containership	10,000 DWT		Conventional	2,185
General cargo ship	3,000 DWT		Conventional	1,673
Refrigerated cargo carrier	3,000 DWT		Conventional	53
Combination carrier	4,000 DWT		Conventional	3,351
LNG carrier	10,000 DWT		Conventional, Non-conventional	185
Ro-ro cargo ship (vehicle carrier)	10,000 DWT		Conventional	301
Ro-ro cargo ship	1,000 DWT	From 1 January 1998 to 31 December 2010	Conventional	188
Ro-ro passenger ship	250 DWT		Conventional	350