---CHUNK---

SOURCE: MEPC.334(76).pdf
validated/calibrated against parent hull sea trials and/or model tests, with the approval of the verifier.

2.4 MARPOL means the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocols of 1978 and 1997 relating thereto, as amended.

2.5 For the purpose of these Guidelines, the definitions in MARPOL Annex VI, as amended, apply.

3 APPLICATION

These Guidelines should be applied to ships for which an application for a survey for verification of the ship's EEXI specified in regulation 5 of MARPOL Annex VI has been submitted to a verifier.

4 PROCEDURES FOR SURVEY AND CERTIFICATION

4.1 General

4.1.1 The attained EEXI should be calculated in accordance with regulation 23 of MARPOL Annex VI and the 2021 Guidelines on the method of calculation of the attained Energy Efficiency Existing Ship Index (EEXI) (resolution MEPC.333(76)) (EEXI Calculation Guidelines).

4.1.2 The 2013 Guidance on treatment of innovative energy efficiency technologies for calculation and verification of the attained EEDI (MEPC.1/Circ.815) should be applied for calculation of the attained EEXI, if applicable.

---CHUNK---

SOURCE: MEPC.334(76).pdf
Guidelines).

4.1.2 The 2013 Guidance on treatment of innovative energy efficiency technologies for calculation and verification of the attained EEDI (MEPC.1/Circ.815) should be applied for calculation of the attained EEXI, if applicable.

1 Other terms used in these Guidelines have the same meaning as those defined in the 2018 Guidelines on the method of calculation of the attained EEDI for new ships (resolution MEPC.308(73), as amended) and the 2021 Guidelines on the method of calculation of the attained EEXI (resolution MEPC.333(76)).

4.1.3 The information used in the verification process may contain confidential information of submitters, including shipyards, which requires Intellectual Property Rights (IPR) protection. In the case where the submitter wants a non- disclosure agreement with th e verifier, the additional information should be provided to the verifier upon mutually agreed terms and conditions.

---CHUNK---

SOURCE: MEPC.334(76).pdf
In the case where the submitter wants a non- disclosure agreement with th e verifier, the additional information should be provided to the verifier upon mutually agreed terms and conditions.

4.2 Verification of the attained EEXI

4.2.1 For verification of the attained EEXI, an application for a survey and an EEXI Technical File containing the necessary information for the verification and other relevant background documents should be submitted to a verifier, unless the attained EEDI of the ship satisfies the required EEXI.

4.2.2 The EEXI Technical File should be written at least in English. The EEXI Technical File should include, but not be limited to:

.1 deadweight (DWT) or gross tonnage (GT) for ro-ro passenger ship and cruise passenger ship having non-conventional propulsion;

.2 the rated installed power (MCR) of the main and auxiliary engines;

.3 the limited installed power (MCRlim) in cases where the overridable Shaft / Engine Power Limitation system is installed;

.4 the ship speed (Vref);

.5 the approximate ship speed (Vref,app) for pre-EEDI ships in cases where the

---CHUNK---

SOURCE: MEPC.334(76).pdf
.3 the limited installed power (MCRlim) in cases where the overridable Shaft / Engine Power Limitation system is installed;

.4 the ship speed (Vref);

.5 the approximate ship speed (Vref,app) for pre-EEDI ships in cases where the speed-power curve is not available, as specified in paragraph 2.2.3.5 of the EEXI Calculation Guidelines;

.6 an approved speed- power curve under the EEDI condition as specified in paragraph 2.2 of the EEDI Calculation Guidelines, which is described in the EEDI Technical File, in cases where regulation 22 of MARPOL Annex VI (Attained EEDI) is applied;

.7 an estimated speed- power curve under the EEDI condition, or under a different load draught to be calibrated to the EEDI condition, obtained from tank test and/or numerical calculations, if available;

.8 estimation process and methodology of the power curves, as necessary, including documentation on consistency with the defined quality standards (e.g. ITTC 7.5-03-01-02 and ITTC 7.5-03-01-04 in their latest revisions) and

the verification of the numerical set -up with parent hull or the reference set of comparable ships in case of using numerical calculations;

---CHUNK---

SOURCE: MEPC.334(76).pdf
(e.g. ITTC 7.5-03-01-02 and ITTC 7.5-03-01-04 in their latest revisions) and the verification of the numerical set -up with parent hull or the reference set of comparable ships in case of using numerical calculations;

.9 a sea trial report including sea trial results, which may have been calibrated by the tank test, under the sea condition as specified in paragraph 2.2.2 of the EEDI Calculation Guidelines, if available;

.10 calculation process of Vref,app for pre -EEDI ships in cases where the speed-power curve is not available, as specified in paragraph 2.2.3.5 of the EEXI Calculation Guidelines;

.11 type of fuel;

.12 the specific fuel consumption (SFC) of the main and auxiliary engines, as specified in paragraph 2.2.3 of the EEXI Calculation Guidelines;

.13 the electric power table 2 for certain ship types, as necessary, as defined in the EEDI Calculation Guidelines;

---CHUNK---

SOURCE: MEPC.334(76).pdf
specified in paragraph 2.2.3 of the EEXI Calculation Guidelines;

.13 the electric power table 2 for certain ship types, as necessary, as defined in the EEDI Calculation Guidelines;

.14 the documented record of annual average figure of the auxiliary engine load at sea obtained prior to the date of application for a survey for verification of the ship's EEXI, as specified in paragraph 2.2.2.3 of the EEXI Calculation Guidelines, if applicable;

.15 calculation process of PAE,app, as specified in paragraph 2.2.2.3 of the EEXI Calculation Guidelines, if applicable;

.16 principal particulars, ship type and the relevant information to classify the ship as such a ship type, classification notations and an overview of the propulsion system and electricity supply system on board;

.17 description of energy saving equipment, if available;

.18 calculated value of the attained EEXI, including the calculation summary, which

should contain, at a minimum, each value of the calculation parameters and the calculation process used to determine the attained EEXI; and

.19 for LNG carriers:

.1 type and outline of propulsion systems (such as direct drive diesel, diesel

---CHUNK---

SOURCE: MEPC.334(76).pdf
should contain, at a minimum, each value of the calculation parameters and the calculation process used to determine the attained EEXI; and

.19 for LNG carriers:

.1 type and outline of propulsion systems (such as direct drive diesel, diesel electric, steam turbine);

.2 LNG cargo tank capacity in m 3 and BOR as defined in paragraph 2.2.5.6.3 of the EEDI Calculation Guidelines;

.3 s
haft power of the propeller shaft after transmission gear at 100% of the rated output of motor (MPPMotor) and () for diesel electric;