.4 s
haft power of the propeller shaft after transmission gear at the de-rated output of motor (MPPMotor,lim) in cases where the overridable Shaft / Engine Power Limitation is installed;

.5 maximum continuous rated power (MCRSteamTurbine) for steam turbine;

.6 limited maximum continuous rated power (MCRSteamTurbine,lim) for steam turbine in cases where the overridable Shaft / Engine Power Limitation is installed; and

.7 SFCSteamTurbine for steam turbine, as specified in paragraph 2.2.7.2 of the EEDI Calculation Guidelines. If the calculation is not available from the manufacturer, SFCSteamTurbine may be calculated by the submitter.

---CHUNK---

SOURCE: MEPC.334(76).pdf
is installed; and

.7 SFCSteamTurbine for steam turbine, as specified in paragraph 2.2.7.2 of the EEDI Calculation Guidelines. If the calculation is not available from the manufacturer, SFCSteamTurbine may be calculated by the submitter.

A sample of an EEXI Technical File is provided in the appendix.

2 Electric power tables should be validated separately, taking into account the guidelines set out in appendix 2 of the 2014 Guidelines on survey and certification of the Energy Efficiency Design Index (EEDI) (resolution MEPC.254(67), as amended by resolutions MEPC.261(68) and MEPC.309(73)); consolidated text: MEPC.1/Circ.855/Rev.2, as may be further amended).

4.2.3 The SFC should be corrected to the value corresponding to the ISO standard reference conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and

---CHUNK---

SOURCE: MEPC.334(76).pdf
conditions using the standard lower calorific value of the fuel oil, referring to ISO 15550:2002 and ISO 3046-1:2002. For the confirmation of the SFC, a copy of the approved NOX Technical File and documented summary of the correction calculations should be submitted to the verifier.

4.2.4 For ships equipped with dual-fuel engine(s) using LNG and fuel oil, the CF-factor for gas (LNG) and the specific fuel consumption (SFC) of gas fuel should be used by applying the criteria specified in paragraph 4.2.3 of the 2014 Guidelines on survey and certification of the E nergy Efficiency Design Index (EEDI), as amended,3 as a basis for the guidance of the Administration.

4.2.5 Notwithstanding paragraphs 4.2.3 and 4.2.4, in cases where overridable Shaft / Engine Power Limitation is installed, or in cases where engines do not have a test report included in the NOX

Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory and acceptable to the verifier.

---CHUNK---

SOURCE: MEPC.334(76).pdf
Technical File, SFC should be calculated in accordance with paragraph 2.2.3 of the EEXI Calculation Guidelines. For this purpose, actual performance records of the engine may be used if satisfactory and acceptable to the verifier.

4.2.6 The verifier may request further information from the submitter, as specified in paragraph 4.2.7 of the EEDI Survey and Certification Guidelines, in addition to that contained in the EEXI Technical File, as necessary, to examine the calculation process of the attained EEXI.

4.2.7 In cases where the sea trial report as specified in paragraph 4.2.2.9 is submitted, the verifier should request further information from the submitter to confirm that:

.1 the sea trial was conducted in accordance with the conditions specified in paragraphs 4.3.3, 4.3.4 and 4.3.7 of the EEDI Survey and Certification Guidelines, as applicable;

.2 sea conditions were measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier;

.3 ship speed was measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier; and

---CHUNK---

SOURCE: MEPC.334(76).pdf
equivalent if satisfactory and acceptable to the verifier;

.3 ship speed was measured in accordance with ISO 15016:2002 or the equivalent if satisfactory and acceptable to the verifier; and

.4 the measured ship speed was calibrated, if necessary, by taking into account the effects of wind, tide, waves, shallow water and displacement in accordance with ISO 15016:2002 or the equivalent which may be acceptable provided that the concept of the method is transparent for the verifier and publicly available/accessible.

4.2.8 The estimated speed- power curve obtained from the tank test and/or numerical calculations and/or the sea trial results calibrated by the tank test should be reviewed on the basis of the relevant documents in accordance with the EEDI Survey and Certification Guidelines, the defined quality standards (e.g. ITTC 7.5- 03-01-02 and ITTC 7.5-03-01-04 in their latest revisions) and the verification of the numerical set -up with parent hull or the reference set of comparable ships.

4.2.9 I n cases where the overridable Shaft / Engine Power Limitation system is installed,

---CHUNK---

SOURCE: MEPC.334(76).pdf

their latest revisions) and the verification of the numerical set -up with parent hull or the reference set of comparable ships.

4.2.9 I n cases where the overridable Shaft / Engine Power Limitation system is installed, the verifier should confirm that the system is appropriately installed and sealed in accordance with the 2021 Guidelines on the Shaft / Engine Power Limitation system to comply with the EEXI requirements and use of a power reserve (resolution MEPC.335(76)) and that a verified Onboard Management Manual (OMM) for overridable Shaft / Engine Power Limitation is on board the ship.

3 R esolution MEPC.254(67), as amended.
RESOLUTION MEPC.334(76) (adopted on 17 June 2021)
2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 8, page 7

I:\MEPC\76\MEPC 76-15-Add.2.docx
4.3 Verification of the attained EEXI in case of major conversion

4.3.1 In cases of a major conversion of a ship taking place at or after the completion date of the survey for EEXI verification specified in regulation 5.4.7 of MARPOL Annex VI, the

---CHUNK---

SOURCE: MEPC.334(76).pdf
4.3.1 In cases of a major conversion of a ship taking place at or after the completion date of the survey for EEXI verification specified in regulation 5.4.7 of MARPOL Annex VI, the shipowner should submit to a verifier an application for a general or partial survey with the EEXI Technical File duly revised, based on the conversion made and other relevant background documents.

4.3.2 The background documents should include as a minimum, but are not limited to:

.1 details of the conversion;

.2 EEXI parameters changed after the conversion and the technical justifications for each respective parameter;

.3 reasons for other changes made in the EEXI Technical File, if any; and

.4 calculated value of the attained EEXI with the calculation summary, which should contain, as a minimum, each value of the calculation parameters and the calculation process used to determine the attained EEXI after the conversion.

4.3.3 The verifier should review the revised EEXI Technical File and other documents submitted and verify the calculation process of the attained EEXI to ensure that it is technically

---CHUNK---

SOURCE: MEPC.334(76).pdf
conversion.

4.3.3 The verifier should review the revised EEXI Technical File and other documents

submitted and verify the calculation process of the attained EEXI to ensure that it is technically sound and reasonable and follows regulation 23 of MARPOL Annex VI and the EEXI Calculation Guidelines.

4.3.4 For verification of the attained EEXI after the major conversion, speed trials of the ship may be conducted, as necessary.

APPENDIX

SAMPLE OF EEXI TECHNICAL FILE

1 Data

1.1 General information