Shipowner XXX Shipping Line
Shipbuilder XXX Shipbuilding Company
Hull no. 12345
IMO no. 94112XX
Ship type Bulk carrier

1.2 Principal particulars

Length overall 250.0 m
Length between perpendiculars 240.0 m
Breadth, moulded 40.0 m
Depth, moulded 20.0 m
Summer load line draught, moulded 14.0 m
Deadweight at summer load line draught 150,000 tons

1.3 Main engine

Manufacturer XXX Industries
Type 6J70A

---CHUNK---

SOURCE: MEPC.334(76).pdf
Length between perpendiculars 240.0 m
Breadth, moulded 40.0 m
Depth, moulded 20.0 m
Summer load line draught, moulded 14.0 m
Deadweight at summer load line draught 150,000 tons

1.3 Main engine

Manufacturer XXX Industries
Type 6J70A
Maximum continuous rating (MCRME) 15,000 kW x 80 rpm
Limited maximum continuous rating with the
Engine Power Limitation installed
(MCRME,lim)
9,940 kW x 70 rpm
SFC at 75% of MCRME or 83% of MCRME,lim 166.5 g/kWh
Number of sets 1
Fuel type Diesel Oil

1.4 Auxiliary engine

Manufacturer XXX Industries
Type 5J-200
Maximum continuous rating (MCRAE) 600 kW x 900 rpm
SFC at 50% MCRAE 220.0 g/kWh
Number of sets 3
Fuel type Diesel Oil

1.5 Ship speed

Ship speed (Vref) (with the Engine Power

Limitation installed)
13.20 knots

RESOLUTION MEPC.334(76) (adopted on 17 June 2021)
2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 8, page 9

I:\MEPC\76\MEPC 76-15-Add.2.docx
2 Power curve

(Example 1; case of the EEDI ship)
An approved speed-power curve contained in the EEDI Technical File is shown in figure 2.1.

---CHUNK---

SOURCE: MEPC.334(76).pdf
Annex 8, page 9

I:\MEPC\76\MEPC 76-15-Add.2.docx
2 Power curve

(Example 1; case of the EEDI ship)
An approved speed-power curve contained in the EEDI Technical File is shown in figure 2.1.

(Example 2; case of the pre-EEDI ship)
An estimated speed-power curve obtained from the tank test and/or numerical calculations, if available, is also shown in figure 2.1.

Figure 2.1: Power curve

(Example 3; case of the pre-EEDI ship with sea trial result calibrated to a different load draught)
An estimated speed-power curve under a ballast draught calibrated to the design load draught, obtained from the tank test and/or numerical calculations, if available, is shown in figure 2.2.
RESOLUTION MEPC.334(76) (adopted on 17 June 2021)
2021 GUIDELINES ON SURVEY AND CERTIFICATION OF THE ATTAINED ENERGY EFFICIENCY EXISTING SHIP INDEX (EEXI)MEPC 76/15/Add.2
Annex 8, page 10

I:\MEPC\76\MEPC 76-15-Add.2.docx

Figure 2.2: Power curve

3 Overview of propulsion system and electric power supply system

3.1 Propulsion system

3.1.1 Main engine
Refer to paragraph 1.3 of this appendix.

3.1.2 Propeller

Type Fixed pitch propeller
Diameter 7.0 m

---CHUNK---

SOURCE: MEPC.334(76).pdf
Figure 2.2: Power curve

3 Overview of propulsion system and electric power supply system

3.1 Propulsion system

3.1.1 Main engine
Refer to paragraph 1.3 of this appendix.

3.1.2 Propeller

Type Fixed pitch propeller
Diameter 7.0 m
Number of blades 4
Number of sets 1

3.2 Electric power supply system

3.2.1 Auxiliary engines
Refer to paragraph 1.4 of this appendix.

3.2.2 Main generators

Manufacturer XXX Electric
Rated output 560 kW (700 kVA) x 900 rpm
Voltage AC 450 V
Number of sets 3

Figure 3.1: Schematic figure of propulsion and electric power supply system

4 Estimation process of speed-power curve

(Example; case of pre-EEDI ship)
Speed-power curve is estimated based on model test results and/or numerical calculations, if available. The flow of the estimation processes is shown below.

Figure 4: Flow chart of process for estimating speed-power curve from tank tests

---CHUNK---

SOURCE: MEPC.334(76).pdf
Speed-power curve is estimated based on model test results and/or numerical calculations, if available. The flow of the estimation processes is shown below.

Figure 4: Flow chart of process for estimating speed-power curve from tank tests