.10 administrator of the EPL system.

5 Demonstration of compliance of the SHaPoLi / EPL system

5.1 The demonstration of compliance of the SHaPoLi / EPL system should be verified by an appropriate survey in accordance with regulation 5.4 of MARPOL Annex VI for the verification of the ship's EEXI according to regulation 23. The survey should include the

---CHUNK---

SOURCE: MEPC.335(76).pdf
an appropriate survey in accordance with regulation 5.4 of MARPOL Annex VI for the verification of the ship's EEXI according to regulation 23. The survey should include the verification and validation of the system by addressing the following items:

.1 the verification of compliance of the system with the OMM for SHaPoLi / EPL;

.2 the verification of compliance of the system with the specifications set out in section 2 of these Guidelines; and

.3 the verification of the OMM for SHaPoLi / EPL that the OMM for SHaPoLi / EPL is in compliance with the specifications set out in section 4 of these Guidelines.

5.2 In cases where the SHaPoLi / EPL system is applied and no changes are made to NOX critical settings and/or components * outside what is allowed by the engine technical file as defined in the 2008 NOX Technical Code (NTC 2008), engine re-certification is not needed.

---CHUNK---

SOURCE: MEPC.335(76).pdf
NOX critical settings and/or components * outside what is allowed by the engine technical file as defined in the 2008 NOX Technical Code (NTC 2008), engine re-certification is not needed.

5.3 In cases where the SHaPoLi / EPL system is applied and the NO X critical settings and/or components are altered beyond what is allowed by the engine technical file as defined in NTC 2008, the engine needs to be re- certified. In such a case, for an EEDI -certified ship where the SHaPoLi / EPL system is applied at a power below that required by regulation 24.5 of MARPOL Annex VI (minimum power requirement), the certified engine power should be at the power satisfying that requirement.

***

* NOX critical parameters and components are listed in NOX Technical File under the section "Components, setting and operating values of the engine which may influence its NOX emission".

2021 GUIDELINES ON THE SHAFT / ENGINE POWER LIMITATION SYSTEM TO COMPLY WITH THE EEXI REQUIREMENTS
AND USE OF A POWER RESERVERESOLUTION MEPC.335(76) (adopted on 17 June 2021)

---CHUNK---

SOURCE: MEPC.335(76).pdf
RESOLUTION MEPC.335(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE SHAFT / ENGINE POWER LIMITATION SYSTEM TO COMPLY WITH THE EEXI REQUIREMENTS
AND USE OF A POWER RESERVERESOLUTION MEPC.335(76) (adopted on 17 June 2021)
2021 GUIDELINES ON THE SHAFT / ENGINE POWER LIMITATION SYSTEM TO COMPLY WITH THE EEXI REQUIREMENTS
AND USE OF A POWER RESERVE

---CHUNK---

SOURCE: MEPC.336(76).pdf
RESOLUTION MEPC.336(76) (adopted on 17 June 2021)
2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)MEPC 76/15/Add.2
Annex 10, page 1
I:\MEPC\76\MEPC 76-15-Add.2.docx
ANNEX 10
RESOLUTION MEPC.336(76)
(adopted on 17 June 2021)
2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)
THE MARINE ENVIRONMENT PROTECTION COMMITTEE,
RECALLING Article 38(a) of the Convention on the International Maritime Organization concerning the functions of the Marine Environment Protection Committee conferred upon it by international conventions for the prevention and control of marine pollution from ships,
NOTING that it adopted, by resolution MEPC.328(76), the 2021 revised MARPOL Annex VI , which is expected to enter into force on 1 November 2022 upon its deemed acceptance on 1 May 2022,
NOTING IN PARTICULAR that the 2021 revised MARPOL Annex VI contains amendments concerning mandatory goal -based technical and operational measures to reduce carbon intensity of international shipping,
NOTING FURTHER that regulation 28.1 of MARPOL Annex VI requires ships to which this

---CHUNK---

SOURCE: MEPC.336(76).pdf
concerning mandatory goal -based technical and operational measures to reduce carbon intensity of international shipping,
NOTING FURTHER that regulation 28.1 of MARPOL Annex VI requires ships to which this regulation apply to calculate the attained annual operational CII taking into account the guidelines developed by the Organization,
RECOGNIZING that the aforementioned amendments to MARPOL Annex VI require relevant guidelines for uniform and effective implementation of the regulations and to provide sufficient lead time for industry to prepare,
HAVING CONSIDERED, at its seventy -sixth session, draft 2021 Guidelines on operational carbon intensity indicators and the calculation methods (CII Guidelines, G1),
1 ADOPTS the 2021 Guidelines on operational carbon intensity indicators and the

calculation methods (CII Guidelines, G1), as set out in the annex to the present resolution;
2 INVITES Administrations to take the annexed Guidelines into account when developing and enacting national laws which give force to and implement requirements set forth in regulation 28.1 of MARPOL Annex VI;
3 REQUESTS the Parties to MARPOL Annex VI and other Member Governments to

---CHUNK---

SOURCE: MEPC.336(76).pdf
developing and enacting national laws which give force to and implement requirements set forth in regulation 28.1 of MARPOL Annex VI;
3 REQUESTS the Parties to MARPOL Annex VI and other Member Governments to
bring the annexed Guidelines to the attention of masters, seafarers, shipowners, ship operators and any other interested parties;
4 AGREES to consider substantiated proposals for CII correction factors for certain ship types, operational profiles and/or voyages with a view to enhanc ing, as appropriate, the annexed Guidelines before entry into force of the aforementioned amendments to MARPOL Annex VI;
5 AGREES to keep the Guidelines under review in light of experience gained with their implementation and in light of the review of CII regulations to be completed by the Organization by 1 January 2026 as identified in regulation 28.11 of MARPOL Annex VI.
RESOLUTION MEPC.336(76) (adopted on 17 June 2021)
2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)MEPC 76/15/Add.2
Annex 10, page 2

I:\MEPC\76\MEPC 76-15-Add.2.docx
ANNEX

2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE

---CHUNK---

SOURCE: MEPC.336(76).pdf
Annex 10, page 2

I:\MEPC\76\MEPC 76-15-Add.2.docx
ANNEX

2021 GUIDELINES ON OPERATIONAL CARBON INTENSITY INDICATORS AND THE CALCULATION METHODS (CII GUIDELINES, G1)

1 Introduction

1.1 In the Initial IMO Strategy on Reduction of GHG Emissions from Ships (Resolution MEPC.304(72)), the level of ambition on carbon intensity of international shipping is quantified by the CO2 emissions per transport work, as an average across international shipping.

1.2 These Guidelines address the calculation methods and the applicability of the operational carbon intensity indicator (CII) for individual ships to which chapter 4 of MARPOL Annex VI, as amended, applies.

2 Definitions

2.1 MARPOL means the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocols of 1978 and 1997 relating thereto, as amended.

2.2 IMO DCS means the data collection system for fuel oil consumption of ships referred to in regulation 27 and related provisions of MARPOL Annex VI.

2.3 For the purpose of these Guidelines, the definitions in MARPOL Annex VI, as amended, apply.

---CHUNK---

SOURCE: MEPC.336(76).pdf
to in regulation 27 and related provisions of MARPOL Annex VI.

2.3 For the purpose of these Guidelines, the definitions in MARPOL Annex VI, as amended, apply.

2.4 The metrics indicating the average CO 2 emissions per transport work of a ship are generally referred to as operational carbon intensity indicator (CII) in these Guidelines.

.1 A specific CII calculated based on the actual or estimated mass or volume of the shipment carried on board a ship is generally referred to as demand-based CII; and

.2 A specific CII, in which calculation the capacity of a ship is taken as proxy of the actual mass or volume of the shipment carried on board, is generally referred to as supply-based CII.

2.5 The supply-based CII which uses DWT as the capacity is referred to as AER, and the