The Ballast Water Record Book entries should be completed, taking into account any guidelines to be developed by the Organization.

The volume of ballast water on board should be estimated in cubic metres. It is recognized that the accuracy of estimating volumes of ballast is left to interpretation.

ENTRIES IN THE BALLAST WATER RECORD BOOK

Entries in the Ballast Water Record Book shall be made on each of the following occasions:

---CHUNK---

SOURCE: MEPC.369(80).pdf
that the accuracy of estimating volumes of ballast is left to interpretation.

ENTRIES IN THE BALLAST WATER RECORD BOOK

Entries in the Ballast Water Record Book shall be made on each of the following occasions:

(A) When ballast water is taken on board from the aquatic environment (ballasting operation)

.1 Start time and location (port of uptake or latitude/longitude)

.2 Completion time and location (port of uptake or latitude/longitude and minimum depth of water during uptake)

.3 The identity of the tanks affected

.4 Estimated volume of uptake and final total quantity retained in cubic metres

.5 Whether conducted in accordance with the approved Ballast Water Management Plan

.6 Ballast water treatment method

(B) When ballast water is discharged into the aquatic environment (deballasting operation)

.1 Start time and location (port of discharge or latitude/longitude)

.2 Completion time and location (port of discharge or latitude/longitude and minimum depth of water during discharge)

.3 The identity of the tanks affected

.4 Estimated volume of discharge and final total quantity retained in cubic metres

---CHUNK---

SOURCE: MEPC.369(80).pdf
.2 Completion time and location (port of discharge or latitude/longitude and minimum depth of water during discharge)

.3 The identity of the tanks affected

.4 Estimated volume of discharge and final total quantity retained in cubic metres

.5 Whether conducted in accordance with the approved Ballast Water Management Plan

.6 Ballast water treatment method

RESOLUTION MEPC.369(80) (adopted on 7 July 2023)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE CONTROL AND MANAGEMENT OF SHIPS BALLAST WATER AND SEDIMENTS, 2004- 4 -

(C) Whenever ballast water is exchanged, treated through internal circulation or treated in tank

1 Ballast water exchange

.1 Start time and location (latitude/longitude)

.2 Completion time and location (latitude/longitude)

.3 Minimum distance from the nearest land and minimum depth of water during the exchange or, if applicable, identify the designated exchange area in accordance with regulation B-4.2

.4 Whether conducted in accordance with the Ballast Water Management Plan and state the ballast water exchange method (Sequential or Flow -through or Dilution) used

.5 The identity of the tanks affected

---CHUNK---

SOURCE: MEPC.369(80).pdf
accordance with regulation B-4.2

.4 Whether conducted in accordance with the Ballast Water Management Plan and state the ballast water exchange method (Sequential or Flow -through or Dilution) used

.5 The identity of the tanks affected

.6 Total quantity exchanged and final total quantity on board in cubic metres

.7 Treatment method for the incoming ballast water

2 Ballast water internal circulation for treatment or in-tank treatment

.1 Start time

.2 Completion time

.3 The identity of the tanks affected (identifying source and destination tanks, if applicable)

.4 Total quantity treated (through circulation or in tank) in cubic metres

.5 Ballast water treatment method

(D) Uptake or discharge of ballast water from/to a port-based or reception facility

.1 Start time and location of uptake/discharge (state facility name)

.2 Completion time

.3 Operation carried out (whether uptake or discharge)

.4 The identity of the tanks affected

.5 Total quantity in cubic metres and final quantity retained on board

.6 Whether conducted in accordance with the approved Ballast Water Management Plan

---CHUNK---

SOURCE: MEPC.369(80).pdf
.4 The identity of the tanks affected

.5 Total quantity in cubic metres and final quantity retained on board

.6 Whether conducted in accordance with the approved Ballast Water Management Plan

.7 Onboard ballast water treatment method

RESOLUTION MEPC.369(80) (adopted on 7 July 2023)
AMENDMENTS TO THE INTERNATIONAL CONVENTION FOR THE CONTROL AND MANAGEMENT OF SHIPS BALLAST WATER AND SEDIMENTS, 2004- 5 -

(E) Accidental discharge/ingress or other exceptional uptake or discharge of ballast water

.1 Start time and location of ingress/uptake /discharge (port name or latitude/longitude)

.2 Completion time

.3 Operation carried out (whether ingress, uptake or discharge)

.4 The identity of the tanks affected

.5 Total quantity of ballast water in cubic metres

.6 State the circumstances of ingress, uptake, discharge or loss, the reason thereof, any treatment method used and general remarks

(F) Failures and inoperabilities* of the ballast water management system

.1 Time and location (port name or latitude/longitude) of failure of the ballast water management system

.2 Operation carried out (state whether uptake or discharge)

---CHUNK---

SOURCE: MEPC.369(80).pdf
(F) Failures and inoperabilities* of the ballast water management system

.1 Time and location (port name or latitude/longitude) of failure of the ballast water management system

.2 Operation carried out (state whether uptake or discharge)

.3 Description of the issue (e.g. kind of alarm or other description of circumstances)