---CHUNK---

SOURCE: MEPC.376(80).pdf
.2 allow for operators to demonstrate lower core life cycle emissions compared to the default core life cycle, thought a certification process.

2 Operators (e.g. fuel producers) can ask for being certified, in order to prove better performances than the default emission factor (that cannot therefore be the representation of the best available technology), obtain a certified "actual value". Actual values may also be used when the fuel producer has defined a new pathway that does not have a default core life cycle emission factor.

3 This template allows presenting the minimum set of data required for the calculation of default core LCA emission factors, ensuring quality in terms of data relevance, adequacy, quality, transparency and accessibility.

PATHWAY DESCRIPTION

4 This section should clearly present the pathway modelled, with the aim for providing at least information on: the type of feedstock used, a description of the technology used for converting such feedstock in the final fuel, and any other relevant information, consistently with the system boundary of the LCA guidelines.

---CHUNK---

SOURCE: MEPC.376(80).pdf
least information on: the type of feedstock used, a description of the technology used for converting such feedstock in the final fuel, and any other relevant information, consistently with the system boundary of the LCA guidelines.

5 Explanatory remarks on the pathway description: The default emission factors are based on the WtT methodology, aiming at evaluating the amount of GHG emissions for the fuel production and distribution. The production steps to be included in the WtT are:

Figure 2 Generic well-to-tank supply chain

The system boundaries defined for describing a specific feedstock-to-fuel pathway shall be in line with the definitions contained in the guidelines.

Additional details and relevant information may be added in appendices, such as location, production capacity, age of production facility or facilities.

INPUT DESCRIPTION

6 This section should clearly present the input used for the modelling exercise.

---CHUNK---

INPUT DESCRIPTION

6 This section should clearly present the input used for the modelling exercise.

7 Source of the data and of the used model should be reported.

8 Explanatory remarks on the input description: In order to provide guidance to fill the template, please see below some tables aiming at presenting the data that should be reported, per pathway (example based on a lipid feedstock production and conversion). As, in practical terms, the tables are "pathway specific", please adapt when needed.

Table 1: efecu inputs and outputs for XXX feedstock

| | XXXX, per dry kg | Data source/Model used |
|---|---|---|
| XXX feedstock Agricultural Inputs | Total N (g) | zzz et al. 2010 |
| efecu | P2O5 (g) | ecoinvent |
| | K2O (g) | GREET |
| Diesel (MJ) | | |
| per kg XXXX oil Oil Extraction Inputs | | |
| | Values | Data source/ Model used |
| Feedstock (g, dry) | | zzz et al. 2010 |
| NG (MJ) | | ecoinvent |
| N-Hexane (MJ) | | GREET |
| Electricity (MJ) | | |
| Electricity (MJ) | | |
| Co- | | |

product,
zzz(g)

Co-
product,
zzz (g)

---CHUNK---

SOURCE: MEPC.376(80).pdf
Feedstock
(g, dry)
zzz et al. 2010
NG (MJ) ecoinvent
N-Hexane
(MJ)
GREET
Electricity
(MJ)

Electricity
(MJ)

Co-
product,
zzz(g)

Co-
product,
zzz (g)

Oil Extraction
Outputs
Co-
product,
zzz (g)


Table 2: ep Inputs and outputs for XXXX conversion process Explanatory remark:
including all the needed steps to pre-treat the feedstock in order to be able
to convert it into the fuel, via the selected conversion process.

per MJ fuel

Values Data source/model used
Inputs
Feedstock (g oil) zzz et al. 2010
NG (MJ) ecoinvent
H2 (MJ) * GREET
Electricity (MJ)
Explanatory remark:
placeholder for key
material inputs (e.g.
chemicals, etc.)

Outputs
Co-product, propane
mix (MJ) **
Co-product, naphtha
(MJ) **
Co-product, xxxx (MJ)

---CHUNK---

SOURCE: MEPC.376(80).pdf
Electricity (MJ)