for ballast water emergency situations (BWM.2/Circ.17, as may be amended) also relevant to biofouling management.

14.3 States should consider these Guidelines when developing other measures and/or restrictions for managing ships' biofouling.

14.4 Where other measures are being applied, States should notify the Organization of the specific requirements, with supporting documentation, for dissemination to other States and non-governmental agencies where appropriate.

14.5 The application of other measures by States should not place the safety of the ship and crew at risk.

LIST OF APPENDICES

ABBREVIATIONS

APPENDIX 1 ASSESSMENT OF BIOFOULING RISK

APPENDIX 2 INSPECTION AND CLEANING REPORTS

---CHUNK---

SOURCE: MEPC.378(80).pdf

LIST OF APPENDICES

ABBREVIATIONS

APPENDIX 1 ASSESSMENT OF BIOFOULING RISK

APPENDIX 2 INSPECTION AND CLEANING REPORTS

APPENDIX 3 EXAMPLE FORM OF BIOFOULING MANAGEMENT PLAN

APPENDIX 4 EXAMPLE FORM OF BIOFOULING RECORD BOOK

ABBREVIATIONS

AFS Anti-fouling system
AFC Anti-fouling coating
BFMP Biofouling Management Plan
BFRB Biofouling Record Book
IMO International Maritime Organization
MGPS Marine growth prevention system

I:\MEPC\80\MEPC 80-17-Add.1.docx
APPENDIX 1

ASSESSMENT OF BIOFOULING RISK

1 Introduction

The Guidelines recommend taking a proactive approach to biofouling through assessment of

---CHUNK---

SOURCE: MEPC.378(80).pdf
Annex 17, page 25

I:\MEPC\80\MEPC 80-17-Add.1.docx
APPENDIX 1

ASSESSMENT OF BIOFOULING RISK

1 Introduction

The Guidelines recommend taking a proactive approach to biofouling through assessment of biofouling risk profiles for hull and niche areas and by monitoring various risk parameters during operation. An assigned risk profile is dependent on AFS type and protection and should be ship-specific. Definition of risk monitoring parameters and trigger points for actions should also be ship-specific.

Monitoring various risk parameters during operation will lead to a holistic approach to biofouling management in line with a risk-based approach.

2 Identification of risk areas

Typical niche areas and other areas susceptible to biofouling on the hull are indicated in figure 2, but other niche areas may be relevant.

Figure 2: Hull with typical niche areas susceptible to biofouling (source: Eugene,
Conduct of land-based biofouling surveys for domestic vessels)

3 Relevant parameters to be considered in the risk assessment

A ship -specific assessment should be established based on the possibility for biofouling

---CHUNK---

SOURCE: MEPC.378(80).pdf
Conduct of land-based biofouling surveys for domestic vessels)

3 Relevant parameters to be considered in the risk assessment

A ship -specific assessment should be established based on the possibility for biofouling accumulation. If any ship areas have no AFS installed, there is typically a higher risk of biofouling accumulation. If all ship areas have an AFS installed which is compatible with the ships operating profile, the ship has an overall lower risk profile.

Based on the risk profile, an inspection regime should be determined and described in the BFMP. If the assessment determines that an area has a high risk for biofouling accumulation, an inspection regime with short intervals between inspections is recommen ded. Further, the areas with a low risk profile may follow the inspection regime with longer fixed intervals as specified in chapter 8 of the Guidelines.

---CHUNK---

SOURCE: MEPC.378(80).pdf
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 26

I:\MEPC\80\MEPC 80-17-Add.1.docx
The risk profile indicates the possibility of accumulating biofouling and increases as a function of biofouling pressure versus biofouling protection over time. The biofouling risk parameters given in table 2 should be monitored as the risk of biofouling accumulation may increase over time. When higher risk is identified, recommended actions in the form of inspection, reactive cleaning and/or maintenance of AFS should be performed as described in the BFMP. Inspection as a contingency action, if completed by an inspection organization in line with chapter 8, can be treated as a starting point to define the interval for the next inspection.

A hull performance monitoring system can be used to assess the changes in the propulsion power and fuel consumption of the ship. Such changes may indicate a degradation of hull or

propeller condition due to biofouling.

---CHUNK---

SOURCE: MEPC.378(80).pdf
A hull performance monitoring system can be used to assess the changes in the propulsion power and fuel consumption of the ship. Such changes may indicate a degradation of hull or propeller condition due to biofouling.

The results from the hull performance monitoring may indicate biofouling growth on the hull and propeller; however, growth in niche areas will not necessarily be detected with this monitoring method.

Digital tools may be applied for monitoring of biofouling risk parameters. Monitoring of parameters should be as thorough as practicable.

In table 2 below, various biofouling risk parameters are presented with a description of possible risk impact.

RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO