Inspection conditions: ..

Inspection equipment used: ...

Divers/ROV operators participating: .

Quantitative assessment of biofouling cover is summarized in table 3 (in line with the ratings in table 1)

Table 3: Quantitative assessment of biofouling cover
For each transect and niche area surveyed, the mode of the fouling rating (most frequent rating) and the range (lowest and highest rating) should be recorded. An average should not be used. If more than one of the same type of area is assessed, these should be recorded separately and each be given their own fouling rating.

Areas
Fouling rating
(0-4)
Macrofouling

---CHUNK---

SOURCE: MEPC.378(80).pdf
be used. If more than one of the same type of area is assessed, these should be recorded separately and each be given their own fouling rating.

Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most
frequent
rating
Hull below the waterline
Port vertical side
1 m wide belt
    1 m wide belt of subsection X
    1 m wide belt of subsection X
Starboard vertical side
1 m wide belt
    1 m wide belt of subsection X
    1 m wide belt of subsection X
Flat bottom front
1 m wide belt
    1 m wide belt of subsection X
Flat bottom mid
1 m wide belt
    1 m wide belt of subsection X
Flat bottom aft

I:\MEPC\80\MEPC 80-17-Add.1.docx
Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most
frequent
rating
Hull below the waterline
1 m wide belt
    1 m wide belt of subsection X

---CHUNK---

SOURCE: MEPC.378(80).pdf
I:\MEPC\80\MEPC 80-17-Add.1.docx
Areas
Fouling rating
(0-4)
Macrofouling
cover

(%)
Lowest rating Highest rating Most
frequent
rating
Hull below the waterline
1 m wide belt
    1 m wide belt of subsection X
Niche areas
Bow
subsection X

Bow
subsection X

Bow thruster
Bilge keels
Sea chest gratings
    Location 1
    Location 2
Stern
Propeller and its shaft
Rudder and rudder shaft
Discharge pipes

Rope guards
Sounders/instruments
Sacrificial anodes
Internal seawater systems
..
..

An area should be assigned a fouling rating equal to the highest rated 1 m2 identified along the subdivided areas.

The inspection should be as comprehensive as practicable. The more subdivided areas that are inspected, the greater the certainty that the biofouling for the area is realistic. It is recommended that the identified niche areas should be in line with the BFMP.

RESOLUTION MEPC.378(80) (adopted on 7 July 2023)

---CHUNK---

SOURCE: MEPC.378(80).pdf
are inspected, the greater the certainty that the biofouling for the area is realistic. It is recommended that the identified niche areas should be in line with the BFMP.

The condition of the AFC and MGPS should be observed during the inspection and reported. The condition is recommended to be categorized in
line with tables 4 and 5, respectively. If the condition of the AFC could only be thoroughly assessed after reactive cleaning, table 4 should be part
of the cleaning report.

Table 4: The condition of the AFC

AFC condition
Areas Intact
and
effective
in
preventing
biofouling
Failure of adhesion
between a coating
and a metallic
surface

Blistering in
coating
Cracks in

the
coatings
Cold flow resulting
in irregular coating
thickness
Delamination /
peeling / detachment
between coatings

Polishing off
coating during the
ship's operation
(beyond
specifications)
Grounding / general
damage to coating

---CHUNK---

SOURCE: MEPC.378(80).pdf
the
coatings
Cold flow resulting
in irregular coating
thickness