changes are made that have an impact on the anticipated biofouling.
Date:
Most recent scheduled dry-docking
The next scheduled dry-docking

The following revisions have been made:
Date/timeline Developed by Implemented by/
responsible person
Updated parts

INDEX

<A table of contents should be included.>

PURPOSE

The purpose of the BFMP is to outline measures for the control and management of the ship's biofouling to minimize the spread of invasive aquatic species.

---CHUNK---

SOURCE: MEPC.378(80).pdf
INDEX

<A table of contents should be included.>

PURPOSE

The purpose of the BFMP is to outline measures for the control and management of the ship's biofouling to minimize the spread of invasive aquatic species.

DESCRIPTION OF OPERATING PROFILE

The ship's operating profile is described below and is the basis for the selection of the ship's anti-fouling systems (AFS) and operational practices.
Typical operating speed
Typical trading areas
<EXAMPLE>
<Domestic, great coasting, North Sea and Baltic trade, European trade, short international voyage, international voyage, overseas voyage or unrestricted voyages>
Typical operating areas, including climate zones in which the ship will operate
<EXAMPLE>

<Temperate, semi-temperate, tropical and/or
arctic>
Typical salinities of operating areas in
which the ship will operate
<EXAMPLE>
<Fresh water, brackish water and/or marine
water>
AFS installed are suitable for typical
operating profile (Y/N)

DESCRIPTION OF HULL AND NICHE AREAS WHERE BIOFOULING MAY
ACCUMULATE

The hull and niche areas where biofouling may accumulate are described below.
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)

---CHUNK---

SOURCE: MEPC.378(80).pdf
operating profile (Y/N)

DESCRIPTION OF HULL AND NICHE AREAS WHERE BIOFOULING MAY
ACCUMULATE

The hull and niche areas where biofouling may accumulate are described below.
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO
MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 40

I:\MEPC\80\MEPC 80-17-Add.1.docx
Areas on hull <EXAMPLE>
<flat-bottom- front
flat-bottom- mid
flat-bottom- aft
bow dome
boot top
vertical sides port side
vertical sides starboard side
vertical side aft
transom
or others>
Niche areas
(including quantity
where relevant)
<EXAMPLE>
<Sea chests
bow dome
bow thruster
tunnel
tunnel grates
cathodic protection anodes
bilge keels

anchor chain
chain locker
stabilizer fins
rudder
dock block positions
A-brackets/stern tube
cathodic protection anodes and systems
draft
internal pipework
ballast uptake system
inlet gratings
sea inlet pipes
stern thruster
thruster body
velocity probes
propeller
propeller shaft
stern tube seal
echo sounders
rope guards
box coolers
moon pools

---CHUNK---

SOURCE: MEPC.378(80).pdf
draft
internal pipework
ballast uptake system
inlet gratings
sea inlet pipes
stern thruster
thruster body
velocity probes
propeller
propeller shaft
stern tube seal
echo sounders
rope guards
box coolers
moon pools
free-flood spaces/voids
engine cooling system
fire-fighting system
auxiliary service system
or others>

I:\MEPC\80\MEPC 80-17-Add.1.docx
LOCATION OF AREAS WHERE BIOFOULING MAY ACCUMULATE ON THE SHIP

<A diagram of both side and bottom of the ship identifying the location of each area that may accumulate biofouling should be included.>

DESCRIPTION OF APPLIED ANTI-FOULING SYSTEM

The selected AFS that are applied, reapplied, installed or renewed on the ship are described below. When more than one type of anti -fouling coating (AFC) or marine growth prevention system (MGPS) are applied, reapplied, installed or renewed , each AFS should be described

---CHUNK---

SOURCE: MEPC.378(80).pdf
below. When more than one type of anti -fouling coating (AFC) or marine growth prevention system (MGPS) are applied, reapplied, installed or renewed , each AFS should be described individually and in accordance with each manufacturer's instructions.
Prior to a scheduled dry-docking, an evaluation of qualitative observations regarding the ship's biofouling should be made with the purpose of a potential improvement of the AFS selection. Previous reports on the performance of the ship's AFS should be part of the evaluation.