Manufacturer(s) and type(s) of AFC <EXAMPLE>
<Hard coating, self-polishing or fouling
release, etc.>
Biocides in AFC <EXAMPLE>
<Copper oxide, zineb, etc.>
Dry film thickness
Expected lifetime and, if any, expected
reduction of efficiency of AFC

Operating profiles which are suitable for
the AFC including temperature, salinity,
speed, periods of inactivity

Recommended regime for repairs,
maintenance and/or renewal to receive
the AFC optimal performance
<EXAMPLE>
<Regime for repairs>
<Regime for maintenance>
<Regime for renewal>
<N/A>
Cleaning methods recommended for AFC
Cleaning methods not appropriate for
AFC, if any

---CHUNK---

SOURCE: MEPC.378(80).pdf
maintenance and/or renewal to receive
the AFC optimal performance
<EXAMPLE>
<Regime for repairs>
<Regime for maintenance>
<Regime for renewal>
<N/A>
Cleaning methods recommended for AFC
Cleaning methods not appropriate for
AFC, if any
IAFS Certificate

Manufacturer(s), models and type(s) of
MGPS
<EXAMPLE>
<Anode, ultrasound, electrode, electrolysis,
ultraviolet radiation or other>

Type(s) of harmful discharge from MGPS
<EXAMPLE>

<Chlorine, noise or other>
Operating conditions/frequency of use
<EXAMPLE>
<dosing frequency temperature, salinity,
speed>
Required maintenance and frequency
Service life of MGPS

Manufacturer(s), models and type(s) of
other AFS

Type(s) of harmful discharge from other
AFS

Operating conditions/frequency
Required maintenance and frequency
Service life and expiry date of AFS

INSTALLATION OF ANTI-FOULING SYSTEM

---CHUNK---

SOURCE: MEPC.378(80).pdf
other AFS

Type(s) of harmful discharge from other
AFS

Operating conditions/frequency
Required maintenance and frequency
Service life and expiry date of AFS

INSTALLATION OF ANTI-FOULING SYSTEM

The areas on the ship which are protected with the selected AFS are described below.
If necessary, the individual AFS could be identified as A and B, respectively. Areas with no protection are also described.

AFS applied

Areas on ship where
AFS is applied
Date of
application
Recommended cleaning
technique
<EXAMPLE>
<AFC (A)>
<EXAMPLE>
<flat-bottom- front,
flat-bottom- mid,
flat-bottom- aft, bow
dome, boot top,
vertical sides port

side, vertical sides
starboard side, vertical
side aft, transom, or
others>
 <EXAMPLE>
<soft brush, blades, metal
brushes or water jet>
<EXAMPLE>
<MGPS (A)>
<EXAMPLE>
<Sea chests, internal
pipework, ballast
uptake system, inlet
gratings>
 <EXAMPLE>
<Steaming>
<EXAMPLE>
<Other AFS>

---CHUNK---

SOURCE: MEPC.378(80).pdf
<EXAMPLE>
<Other AFS>

RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO
MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 43

I:\MEPC\80\MEPC 80-17-Add.1.docx
<EXAMPLE>
<No AFS>

INSPECTION SCHEDULE OF HULL AND NICHE AREAS

An inspection will be carried out by organizations or personnel competent to undertake inspections in line with the fixed intervals described below:

Inspection areas Initial inspection Subsequent inspections
<EXAMPLE>
<Areas installed with
AFS and operating
within the profile>
<EXAMPLE>
<Inspection within 12
months>

<When utilizing a performance monitoring system that indicates adequate performance of the AFS, an inspection will be conducted within 18 months.
If the monitoring indicates that the AFS is not performing effectively, an inspection should be carried out as soon as possible.>

<EXAMPLE>
<If rating 0-1 in previous inspection, then inspection every 12-18 months
If rating 2, 3 or 4 in previous inspection, then more frequent inspections>
<EXAMPLE>
<Areas with no AFS and no other measures>