---CHUNK---

SOURCE: MEPC.378(80).pdf
possible.>

<EXAMPLE>
<If rating 0-1 in previous inspection,
then inspection every 12-18 months
If rating 2, 3 or 4 in previous inspection,
then more frequent inspections>
<EXAMPLE>
<Areas with no AFS
and no other
measures>
<EXAMPLE>
<Inspection within 12
months>
<EXAMPLE>
<Inspection more frequent>

CLEANING

Reactive cleaning should be performed as a result of any inspection with a fouling rating 2. It should be performed in line with procedures of the ship cleaning operator or the dry -dock facilities used, and the cleaning practices should be conducted in accordance with the jurisdiction's policies or regulations of the relevant au thority. Preferred cleaning methods and procedures that can be used are described below. The methods and cleaning operator used in each cleaning occasion should be recorded in the BFRB.

Reactive
cleaning
method(s)
Areas where
cleaning method
will be applied
Operating

---CHUNK---

SOURCE: MEPC.378(80).pdf
MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 44

I:\MEPC\80\MEPC 80-17-Add.1.docx

Reactive cleaning method(s)

Areas where cleaning method will be applied

Operating condition when cleaning method will be applied

Cleaning schedule

<EXAMPLE>
<Water jet and suction with capture in line with <name of the standard>>
<EXAMPLE>
<flat-bottom-front, flat-bottom-mid, flat-bottom-aft, bow dome, boot top, vertical sides port side, vertical sides starboard side, vertical side aft, transom, or others>
<EXAMPLE>
<moored in harbour, drifting in open sea, on anchorage in coastal waters, on voyage>
<EXAMPLE>
<When recommended based on monitoring of biofouling parameters and/or in case unforeseen biofouling levels are detected on hull or in niche areas>
<EXAMPLE>
<Steaming with capture performed in line with <name of the standard>>
<EXAMPLE>
<Sea chests, internal pipework, ballast uptake

system, inlet
gratings>
<EXAMPLE>
<in dry dock>
<EXAMPLE>
<When recommended based on
monitoring of biofouling parameters
and/or
in case unforeseen biofouling
levels are detected in niche areas>

---CHUNK---

SOURCE: MEPC.378(80).pdf
internal pipework,
ballast uptake
system, inlet
gratings>
<EXAMPLE>
<in dry dock>
<EXAMPLE>
<When recommended based on
monitoring of biofouling parameters
and/or
in case unforeseen biofouling
levels are detected in niche areas>
Possible
harmful
discharge
from cleaning
with reactive
cleaning
method

Manufacturer
and model of
ship-specific
reactive
cleaning
device, if
applicable

Reactive
cleaning
method
suitable for
AFC

Reactive cleaning method(s)

Areas where cleaning method will be applied

Operating condition when cleaning method will be applied

Cleaning schedule

Required maintenance and frequency, as applicable

Reactive cleaning suitable for typical operating