profile, i.e. is
the ship
expected to
stay enough
time in
locations
where
reactive
cleaning can
be carried out

Reactive
cleaning
device tested
in line with
<name of the
standard>
(Y/N), if

---CHUNK---

SOURCE: MEPC.378(80).pdf
suitable for
typical
operating
profile, i.e. is
the ship
expected to
stay enough
time in
locations
where
reactive
cleaning can
be carried out

Reactive
cleaning
device tested
in line with
<name of the
standard>
(Y/N), if
applicable

Proactive cleaning should take into account recommendations from the AFS manufacturer listed in this BFMP. Description of proactive cleaning activities which are planned on a regular basis, if any, are listed below.

Proactive
cleaning
method(s)
Areas where

cleaning method
will be applied
Operating
condition when
cleaning method
will be applied
Cleaning schedule
<EXAMPLE>
<ROV with
water jet, ROV
with soft brush,
<EXAMPLE>
<flat-bottom-
front, flat-bottom-
mid, flat-bottom-
<EXAMPLE>
<moored in
harbour,
drifting in open
<EXAMPLE>
<every <XX> days when operating
in temperate waters;

Proactive
cleaning
method(s)
Areas where
cleaning method

---CHUNK---

SOURCE: MEPC.378(80).pdf
MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 46

I:\MEPC\80\MEPC 80-17-Add.1.docx
Proactive
cleaning
method(s)
Areas where
cleaning method
will be applied
Operating
condition when
cleaning method
will be applied
Cleaning schedule

manual device
with soft brush
or other>
aft, bow dome,
boot top, vertical
sides port side,
vertical sides
starboard side,
vertical side aft,
transom, or
others>
sea, on anchorage
in coastal waters,
on voyage>
every <XX> days when operating
in tropical/semi-tropical waters;
when recommended based on
monitoring of biofouling
parameters; and
in case of unforeseen biofouling
levels defined as rating 1 are
detected on hull or in niche areas>
Possible harmful discharge
from cleaning with proactive
cleaning method
<EXAMPLE>
<AFC biocides, biofouling, particles or other>
Manufacturer and model of
ship-specific proactive cleaning
device, if applicable

Proactive cleaning method
suitable for AFC

Required maintenance and
frequency, as applicable

Proactive cleaning suitable for
typical operating profile, i.e. is
the ship expected to stay

---CHUNK---

SOURCE: MEPC.378(80).pdf
device, if applicable

Proactive cleaning method
suitable for AFC

Required maintenance and
frequency, as applicable

Proactive cleaning suitable for
typical operating profile, i.e. is

the ship expected to stay enough time in locations where proactive cleaning can be carried out

Description of how to avoid biofouling cleaning and discharge of macrofouling, if possible

Proactive cleaning device tested in line with <name of the standard> (Y/N), if applicable

MONITORING OF BIOFOULING RISK PARAMETERS AND CONTINGENCY ACTIONS

Relevant digital tools applied for monitoring of biofouling risk parameters and/or digitalized real-data input are <describe the tools and data used for this ship>.

The biofouling risk parameters given below should be monitored when the ship is in operation. When a parameter goes beyond the deviation limit, the risk of biofouling is increased, and the recommended contingency actions should be used as described.