---CHUNK---

SOURCE: MEPC.378(80).pdf
RESOLUTION MEPC.378(80) (adopted on 7 July 2023)
2023 GUIDELINES FOR THE CONTROL AND MANAGEMENT OF SHIPS' BIOFOULING TO MINIMIZE THE TRANSFER OF INVASIVE AQUATIC SPECIESMEPC 80/17/Add.1
Annex 17, page 47

I:\MEPC\80\MEPC 80-17-Add.1.docx
Biofouling risk parameters to monitor
Evaluation of a deviation including deviation limit of the risk parameter
Contingency actions
Long-term actions
<EXAMPLE>
<Deviation from speed specifications acceptable for the AFS>
<EXAMPLE>
<Incidental deviations should be evaluated for potential biofouling impact.
Continuous or regular deviations, or deviations not rectified, should lead to contingency actions>.
<EXAMPLE>
<Shorter inspection interval with inspection every 4 months.
When recommended by the AFS manufacturer, more frequent proactive cleaning activities could be implemented between inspections.>
<EXAMPLE>

<Evaluate the need
for a potential
improvement of the
AFS selection prior
to the next
dry-docking.>
<EXAMPLE>
<Deviation from salinity
specifications
acceptable for the
AFS>
<EXAMPLE>
<Incidental deviations
should be evaluated
for potential biofouling
impact.

---CHUNK---

SOURCE: MEPC.378(80).pdf
improvement of the
AFS selection prior
to the next
dry-docking.>
<EXAMPLE>
<Deviation from salinity
specifications
acceptable for the
AFS>
<EXAMPLE>
<Incidental deviations
should be evaluated
for potential biofouling
impact.
Continuous or regular
deviations, or
deviations not
rectified, should lead
to contingency
actions.>
<EXAMPLE>
<Shorter inspection
interval with
inspection every 4
months.
When recommended
by the AFS
manufacturer, more
frequent proactive
cleaning activities
could be
implemented
between
inspections.>

<EXAMPLE>
<Evaluate the need
for a potential
improvement of the
AFS selection prior
to the next
dry-docking.>
<EXAMPLE>
<Deviation from
temperature range
specifications
acceptable for the
AFS>
<EXAMPLE>
<Incidental deviations
should be evaluated
for potential biofouling
impact.
Continuous or regular
deviations, or
deviations not
rectified, should lead
to contingency
actions.>
<EXAMPLE>
<Shorter inspection
interval with
inspection every 4
months.
When recommended
by the AFS
manufacturer, more
frequent proactive
cleaning activities
could be
implemented
between
inspections.>
<EXAMPLE>

---CHUNK---

SOURCE: MEPC.378(80).pdf
actions.>
<EXAMPLE>
<Shorter inspection
interval with
inspection every 4
months.
When recommended
by the AFS
manufacturer, more
frequent proactive
cleaning activities

could be
implemented
between
inspections.>
<EXAMPLE>
<Evaluate the need
for a potential
improvement of the
AFS selection prior
to the next
dry-docking.>

Biofouling risk
parameters to
monitor
Evaluation of a