28(b) of the Convention on the International Maritime
Organization concerning the functions of the Committee,
RECALLING ALSO that the Assembly, at its thirteenth session, when
adopting resolution A.535(13) concerning Recommendation on emergency towing
requirements for tankers, requested the Committee to keep the Recommendation
under review, in particular in respect to new towing concepts which may be
introduced and to report as necessary to the Assembly,
NOTING that tankers, including oil tankers, gas carriers and chemical
tankers, in emergencies such as complete mechanical breakdowns, may need to be
---CHUNK---
SOURCE: MSC.35%2863%29.pdf
NOTING that tankers, including oil tankers, gas carriers and chemical
tankers, in emergencies such as complete mechanical breakdowns, may need to be
towed out of danger, and that technologically advanced towing arrangements
have been developed since the adoption of resolution A.535(13), whose
provisions need revision to incorporate new towing concepts,
NOTING ALSO that the new regulation V/15-1 of the International
Convention for the Safety of Life at Sea, 1974, as adopted by the Committee in
May 1994, requires that all tankers of not less than 20,000 tonnes deadweight
shall be fitted with an emergency towing arrangement, the design and
construction of which shall be approved by the Administration based on the
Guidelines developed by the Organization,
HAVING CONSIDERED the recommendation made by the Sub-Committee on Ship
Design and Equipment at its thirty-seventh session,
1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the
---CHUNK---
SOURCE: MSC.35%2863%29.pdf
Design and Equipment at its thirty-seventh session,
1. ADOPTS the Guidelines for Emergency Towing Arrangements on Tankers, the
text of which is set out in the Annex to the present resolution and which
supersedes resolution A.535(13);
2. RECOMMENDS that all Governments concerned take appropriate steps to
implement the Guidelines.
WII648n/EWP
RESOLUTION MSC.35(63)
(adopted on 20 May 1994)
ADOPTION OF GUIDELINES FOR EMERGENCY
TOWING ARRANGEMENTS ON TANKERS MSC 63/23/Add.l
ANNEX 7
Page 2
1 PURPOSE
ANNEX
GUIDELINES FOR EMERGENCY TOWING
ARRANGEMENTS ON TANKERS
1.1 Under regulation V/15-1 of the 1974 SOLAS Convention, as amended by
resolution MSC.31(63) in 1994, new and existing tankers of 20,000 tonnes
deadweight and above shall be fitted with an emergency towing arrangement,
the design and construction of which shall be approved by the Administration,
based on the Guidelines developed by the Organization.
---CHUNK---
SOURCE: MSC.35%2863%29.pdf
the design and construction of which shall be approved by the Administration,
based on the Guidelines developed by the Organization.
1.2 The present Guidelines are intended to provide standards for the design
and construction of emergency towing arrangements which Administrations are
recommended to implement.
1.3 For existing tankers fitted with the emergency towing arrangements in
accordance with resolution A.535(13), the existing towing arrangements forward
of the ship may be retained, but the towing arrangements aft of the ship
should be upgraded to comply with the requirements of the present Guidelines.
2 REQUIREMENTS FOR THE ARRANGEMENTS AND COMPONENTS
2.1 General
The emergency towing arrangements should be so designed as to facilitate
salvage and emergency towing operations on tankers primarily to reduce the
risk of pollution. The arrangements should at all times be capable of rapid
deployment in the absence of main power on the ship to be towed and easy
---CHUNK---
SOURCE: MSC.35%2863%29.pdf
risk of pollution. The arrangements should at all times be capable of rapid
deployment in the absence of main power on the ship to be towed and easy
connection to the towing vessel. Figure 1 shows arrangements which may be
used as reference.
2.2 Towing components
The major components of the towing arrangements sho