levant requirements of annex 7 for
all permitted cases of loading.
2.3.3 Subject to 2.3.4, all other craft should meet the following criteria
in all permitted conditions of loading:
.1 resolution A.562(14) (weather criterion);
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 28
.2 the area under the righting lever curve (GZ curve) should
not be less than 0.07 m.rad up to e = 15° when the maximum
righting lever (GZ) occurs at e = 15° and 0.055 m.rad up to
e = 30° when the maximum righting lever occurs at e = 30°
or above. Where the maximum righting lever occurs at angles
of between e = 15° and e = 30°, the corresponding area
under the righting lever curve should be:
A = 0.055 + 0.001 (30° - emax) (m.rad)
where:
emax is the angle of heel in degrees at which the righting
lever curve reaches its maximum;
.3 the area under the righting lever curve between e = 30° and
e = 40° or between e = 30° and the angle of flooding
---CHUNK---
SOURCE: MSC.36(63).pdf
where:
emax is the angle of heel in degrees at which the righting
lever curve reaches its maximum;
.3 the area under the righting lever curve between e = 30° and
e = 40° or between e = 30° and the angle of flooding
ef *, if this angle is less than 40°, should not be less
than 0.03 m.rad;
.4 the righting lever GZ should be at least 0.20 m at an angle of
heel equal to or greater than 30°;
.5 the maximum righting lever should occur at an angle of heel
not less than 15°; and
.6 the initial metacentric height GMo should not be less
than 0.15 m.
2.3.4 Where the characteristics of the craft are unsuitable for
application of 2.3.3, the Administration may accept alternative
criteria equivalent to those stipulated in 2.3.3, appropriate to
the type of craft and area of operation.
2.4 Intact stability in the non - displacement mode
2.4.1 The requirements of this section and section 2.12 should be applied
on the assumption that any stabilization systems fitted are fully
operational.
2.4.2 Suitable calculations should be carried out and/or tests conducted
to demonstrate that, when operating in the non-displacement and
---CHUNK---
SOURCE: MSC.36(63).pdf
on the assumption that any stabilization systems fitted are fully
operational.
2.4.2 Suitable calculations should be carried out and/or tests conducted
to demonstrate that, when operating in the non-displacement and
transient modes within approved operational limitations, the craft
will, after a disturbance causing roll, pitch, heave or heel due to
turning or any combination thereof, return to the original attitude.
2.4.3 The roll and pitch stability on the first and/or any other craft of
a series should be qualitatively assessed during operational safety
trials as required by chapter 18 and annex 8. The results of such
trials may indicate the need to impose operational limitations.
In applying this criterion, small openings through which progressive
flooding cannot take place need not be considered as open.
WII576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 29
2.4.4 Where craft are fitted with surface piercing structure or
appendages, precautions should be taken against dangerous attitudes
---CHUNK---
SOURCE: MSC.36(63).pdf
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

2.4.4 Where craft are fitted with surface piercing structure or appendages, precautions should be taken against dangerous attitudes or inclinations and loss of stability subsequent to a collision with a submerged or floating object.
2.4.5 In designs where periodic use of cushion deformation is employed as a means of assisting craft control, or periodic use of cushion air exhausting to atmosphere for purposes of craft manoeuvring, the