for determining the resistance
to flame of vertically supported textiles and films, adopted by the
Organization by resolution A.47l(XII), and amendments to the
recommendation adopted by resolution A.563(14).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
---CHUNK---
SOURCE: MSC.36(63).pdf
Organization by resolution A.47l(XII), and amendments to the
recommendation adopted by resolution A.563(14).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 7.4.3.4
7.4.3.5
7.4.3.6
7.4.3.7
7.4.3.8
MSC 63/23/Add.2
ANNEX 18
Page 61
.4 all upholstered furniture has qualities of resistance to the
ignition and propagation of flame in accordance with
standards* developed by the Organization;
.5 all bedding components comply with the standards** developed
by the Organization; and
.6 all deck finish materials comply with the standards***
developed by the O~ganization.
The following surfaces should, as a minimum standard be constructed
of materials having low flame-spread characteristics:
.1 exposed surfaces in corridors and stairway enclosures, and of
bulkheads, wall and ceiling linings in all accommodation and
service spaces and control stations;
.2 concealed or inaccessible spaces in accommodation, service
spaces and control stations.
Any thermal and acoustic insulation material, if not in compliance
with 7.2.1 or 7.2.2, should be of non-combustible material.
---CHUNK---
SOURCE: MSC.36(63).pdf
.2 concealed or inaccessible spaces in accommodation, service
spaces and control stations.
Any thermal and acoustic insulation material, if not in compliance
with 7.2.1 or 7.2.2, should be of non-combustible material.
Materials used in the craft, when exposed to fire, should not emit
smoke or toxic gases in quantities that could be dangerous to humans
as determined in tests of a standard developed by the Organization.
Void compartments, where low density combustible materials are used
to provide buoyancy, should be protected from adjacent fire hazard
areas by fire-resisting divisions, in accordance with tables 7.4-1
and 7.4-2. Also, the space and closures to it should be gastight
but it should be ventilated to atmosphere.
In compartments where smoking is allowed, suitable non-combustible
ash containers should be provided. In compartments where smoking is
not allowed, adequate notices should be displayed.
* Refer to the Recommendation on fire test procedures for upholstered
furniture, adopted by the Organization by resolution A.652(16).
** Refer to the Recommendation on fire test procedures for ignitability of
---CHUNK---
SOURCE: MSC.36(63).pdf
* Refer to the Recommendation on fire test procedures for upholstered
furniture, adopted by the Organization by resolution A.652(16).
** Refer to the Recommendation on fire test procedures for ignitability of
bedding components, adopted by the Organization by resolution A.688(17).
*** Refer to the Recommendation on improved fire test procedures for surface
flammability of bulkhead, ceiling and deck finish materials, adopted by
the Organization by resolution A.653(16) and the Recommendation on fire
test procedures for ignitability of primary deck coverings, adopted by
the Organization by resolution A.687(16).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18

7.4.3.9 The exhaust gas pipes should be arranged so that the risk of fire is kept to a minimum. To this effect, the exhaust system should be insulated and all the compartments and structures which are contiguous with the exhaust system, or those which may be affected by increased temperatures caused by waste gases in normal operation or in an emergency, should be constructed of non-combustible
---CHUNK---
SOURCE: MSC.36(63).pdf
contiguous