e distress and safety
system (GMDSS) and for electronic navigational aids .
. 3 Resolution A.698(17): Performance standards for ship earth stations capable of two-way communications and resolution A.570(14): Type approval of ship earth stations .
. 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio
---CHUNK---
SOURCE: MSC.36(63).pdf
. 3 Resolution A.698(17): Performance standards for ship earth stations capable of two-way communications and resolution A.570(14): Type approval of ship earth stations .
. 4 Resoluti~n A.609(15): Performance standards for shipborne VHF radio installations capable of voice communication and digital selective calling .
. 5 Resolution A.610(15): Performance standards for shipborne MF radio installations capable of voice communication and digital selective calling .
. 6 Resolution A.613(15): Performance standards for shipborne MF/HF radio installations capable of voice communication, narrow-band direct-printing and digital selective calling .
. 7 Resolution A.695(17): Performance standards for float-free satellite emergency position-indicating radio beacons (EPIRBs) operating on 406 MHz (see also Assembly resolution A.696(17): Type approval of satellite emergency position-indicating radio beacons (EPIRBs) operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143
---CHUNK---
SOURCE: MSC.36(63).pdf
operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143
.8 Resolution A.697(17): Performance standards for survival craft radar transponders for use in search and rescue operations •
. 9 Resolution A.612(15): Performance standards for float-free VHF emergency position-indicating radio beacons .
. 10 Resolution A.663(16): Performance standards for INMARSAT Standard-C ship earth stations capable of transmitting and rece~v~ng direct-printing communications and resolution A.570(14): Type approval of ship earth stations .
. 11 Resolution A.664(16): Performance standards for enhanced group call equipment .
. 12 Resolution A.661(16): Performance standards for float-free satellite emergency position-indicating radio beacons operating through the geostationary INMARSAT satellite system on 1.6 GHz •
. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the
---CHUNK---
SOURCE: MSC.36(63).pdf
. 13 Resolution A.662(16): Performance standards for float-free release and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the promulgation and co-ordination of maritime safety information using high-frequency narrow-band direct-printing .
. 15 Resolution A.700(17): Performance standards for narrow-band direct-printing telegraph equipment for the reception of navigational and meteorological warnings and urgent information to ships (MSI) by HF.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY

14.14
14.14.1
14.14.2
14.14.3
14.14.4
14.14.5
14 .14.6
14.14.1
14.14.8
Maint e nance requ irements
Equipment should be so designed that the main units can be replaced readily without elaborate recalibration or readjustment.
Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.
Adequate information should be provided to enable the equipment
---CHUNK---
SOURCE: MSC.36(63).pdf
Where applicable, equipme