and digital selective
calling .
. 5 Resolution A.610(15): Performance standards for shipborne MF radio
installations capable of voice communication and digital selective
calling .
. 6 Resolution A.613(15): Performance standards for shipborne MF/HF
radio installations capable of voice communication, narrow-band
direct-printing and digital selective calling .
. 7 Resolution A.695(17): Performance standards for float-free satellite
emergency position-indicating radio beacons (EPIRBs) operating on
406 MHz (see also Assembly resolution A.696(17): Type approval of
satellite emergency position-indicating radio beacons (EPIRBs)
operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143
---CHUNK---
SOURCE: MSC.36(63).pdf
operating in the COSPAS-SARSAT system).
W/1687n/pp/EWP
(
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT (Footnote continued)
MSC 62/23/Add.2
ANNEX 18
Page 143
.8 Resolution A.697(17): Performance standards for survival craft radar
transponders for use in search and rescue operations •
. 9 Resolution A.612(15): Performance standards for float-free VHF
emergency position-indicating radio beacons .
. 10 Resolution A.663(16): Performance standards for INMARSAT Standard-C
ship earth stations capable of transmitting and rece~v~ng
direct-printing communications and resolution A.570(14): Type
approval of ship earth stations .
. 11 Resolution A.664(16): Performance standards for enhanced group call
equipment .
. 12 Resolution A.661(16): Performance standards for float-free satellite
emergency position-indicating radio beacons operating through the
geostationary INMARSAT satellite system on 1.6 GHz •
. 13 Resolution A.662(16): Performance standards for float-free release
and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the
---CHUNK---
SOURCE: MSC.36(63).pdf
. 13 Resolution A.662(16): Performance standards for float-free release
and activation arrangements for emergency radio equipment .
. 14 Resolution A.699(17): System performance standard for the
promulgation and co-ordination of maritime safety information using
high-frequency narrow-band direct-printing .
. 15 Resolution A.700(17): Performance standards for narrow-band
direct-printing telegraph equipment for the reception of
navigational and meteorological warnings and urgent information to
ships (MSI) by HF.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 144
14.14
14.14.1
14.14.2
14.14.3
14.14.4
14.14.5
14 .14.6
14.14.1
14.14.8

Maint e nance requ irements
Equipment should be so designed that the main units can be replaced readily without elaborate recalibration or readjustment.
Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.
Adequate information should be provided to enable the equipment
---CHUNK---
SOURCE: MSC.36(63).pdf
Where applicable, equipment should be so constructed and installed that it is readily accessible for inspection and on-board maintenance purposes.
Adequate information should be provided to enable the equipment to be properly operated and maintained, taking into account the recommendations of the Organization*.
Adequate tools and spares should be provided to enable equipment to be maintained .
The Administration should ensure that radio equipment required by this chapter is maintained to provide the availability of the functional requirements specified in 14.4 and to meet the recommended performance standards of such equipment.
On crafts engaged on voyages i