iving general radiocommunications
to and from shore-based radio systems or networks subject to
14.14.8; and
.9 of transmitting and receiving bridge-to-bridge communications.
* Refer to resolution A.614(15) on carriage of radar operating in the
frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain
maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
---CHUNK---
SOURCE: MSC.36(63).pdf
frequency band 9,300-9,500 MHz adopted by the Organization.
** It should be noted that craft may have a need for reception of certain
maritime safety information while in port.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.5
14.5.1
14.5.2
14.5.3
14.6
14.6.1
Radio installations
MSC 62/23/Add.2
ANNEX 18
Page 133
Every craft should be provided with radio installations capable of
complying with the functional requirements prescribed by 14.4
throughout its intended voyage and, unless exempted under 14.3,
complying with the requirements of 14.6 and, as appropriate for the
sea area or areas through which it will pass during its intended
voyage, the requirements of either 14.7, 14.8, 14.9 or 14.10.
Every radio installation should:
.1 be so located that no harmful interference of mechanical,
electrical or other origin affects its proper use, and so
as to ensure electromagnetic compatibility and avoidance of
harmful interaction with other equipment and systems;
.2 be so located as to ensure the greatest possible degree of
safety and operational availability;
---CHUNK---
SOURCE: MSC.36(63).pdf
as to ensure electromagnetic compatibility and avoidance of
harmful interaction with other equipment and systems;
.2 be so located as to ensure the greatest possible degree of
safety and operational availability;
.3 be protected against harmful effects of water, extremes of
temperature and other adverse environmental conditions;
.4 be provided with reliable, permanently arranged electrical
lighting, independent of the main sources of electrical power,
for the adequate illumination of the radio controls for
operating the radio installation; and
.5 be clearly marked with the call sign, the ship station
identity and other codes as applicable for the use of the
radio installation.
Coritrol of the VHF radiotelephone channels, required for
navigational safety, should be immediately available on the
navigating bridge convenient to the conning position, and
where necessary, facilities should be available to permit
radiocommunications from the wings of the navigating bridge.
Portable VHF equipment may be used to meet the latter provision.
Radio eguipment: General
Every craft should be provided with:
.1 a VHF radio installation capable of transmitting and receiving:
---CHUNK---
SOURCE: MSC.36(63).pdf
Portable VHF equipment may be used to meet the latter provision.
Radio eguipment: General
Every craft should be provided with:
.1 a VHF radio installation capable of transmitting and receiving:
.1.1 DSC on the frequency 156.525 MHz (channel 70). It should
be possible to initiate the transmission of distress alerts
on channel 70 from the position from which the craft is
normally navigated*; and

.1.2 radiotelephony on the frequencies 156.300 MHz (channel 6), 156.650 MHz (channel 13) and 156.800 MHz (channel 16);
.2 a radio installation capable of maintaining a continuous DSC watch on VHF channel 70 which may be separate from, or combined with, that required by 14.6.1.1.1;~
Certain craft may be exempted from this requirement (see 14.8.4, 14.9.4, and 14.10.2.).

.3 a radar transponder capable of operating in the 9 GHz band, which:
.3.1
.3.2