the GMDSS, adopted by the
Organization.
** Refer to the Recommendation on promulgation of maritime safety
information, adopted by the Organization by resolution A.705(17).
*** Refer to resolution A.616(15) concerning search and rescue homing
capability, adopted by the Organization.
**** Subject to the availability of appropriate receiving and processing
---CHUNK---
SOURCE: MSC.36(63).pdf
*** Refer to resolution A.616(15) concerning search and rescue homing
capability, adopted by the Organization.
**** Subject to the availability of appropriate receiving and processing
ground facilities for each ocean region covered by INMARSAT satellites.
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.6.2
14.6.3
14.6.4
14.7
14.7.1
MSC 62/23/Add.2
ANNEX 18
Page 135
Until 1 February 1999, or until such other date as may be determined
by the Maritime Safety Committee, every craft should, in addition ,
be fitted with a radio installation consisting of a radiotelephone
distress frequency watch receiver capable of operating on 2,182 kHz.
Until 1 February 1999, every craft should, unless the craft is
engaged on voyages in sea area Al only, be fitted with a device for
generating the radiotelephone alarm signal on the frequency
2,182 kHz*.
The Administration may exempt craft constructed on or after
1 February 1997 from the requirements prescribed by 14.6.2 and
14.6.3.
Radi o equ ipment : Sea area A1
In addition to meeting the requirements of 14.6, every craft engaged
---CHUNK---
SOURCE: MSC.36(63).pdf
2,182 kHz*.
The Administration may exempt craft constructed on or after
1 February 1997 from the requirements prescribed by 14.6.2 and
14.6.3.
Radi o equ ipment : Sea area A1
In addition to meeting the requirements of 14.6, every craft engaged
on voyages exclusively in sea area Al should be provided with a
radio installation capable of initiating the transmission of
ship-to-shore distress alerts from the position from which the
craft is normally navigated, operating either:
.1 on VHF using DSC; this requirement may be fulfilled by the
EPIRB prescribed by 14.7.3, either by installing the EPIRB
close to, or by remote activation from, the position from
which the craft is normally navigated; or
. 2 through the polar orbiting satellite service on 406 MHz; this
requirement may be fulfilled by the satellite EPIRB, required
by 14.6.1.6, either by installing the satellite EPIRB close
to, or by remote activation from the position from which the
craft is normally navigated; or
. 3 if the craft on voyages within coverage of MF coast stations
equipped with DSC, on MF using DSC; or
.4 on HF using DSC; or
.5 through the INMARSAT geostationary satellite service; this
---CHUNK---
SOURCE: MSC.36(63).pdf
craft is normally navigated; or
. 3 if the craft on voyages within coverage of MF coast stations
equipped with DSC, on MF using DSC; or
.4 on HF using DSC; or
.5 through the INMARSAT geostationary satellite service; this
requirement may be fulfilled by:
.5.1 an INMARSAT ship earth station**; or
* Refer to resolution A.421(XI) concerning operational standards for
radiotelephone alarm signal generators, adopted by the Organization.
** This requirement can be met by INMARSAT ship earth stations capable of
two-way communications, such as Standard-A and B (resolution A.698(17»
or Standard-C (resolution A.663(16» ship earth stations. Unless

otherwise specified, this footnote applies to all requirements for an INMARSAT ship earth station prescribed by this chapter.
W/16B7n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the cra