tion
A.754(18).
**** Refer to the Recommendation on improved fire test procedures for surface flammability of bulkhead, ceiling and deck finish materials adopted by the Organization by resolution A.653(16).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT Machinery spaces
Open vehicle spaces
Spaces containing dangerous goods
Special category spaces
Store-rooms containing flammable liquids
MSC 63/23/Add.2
ANNEX 18
Page 55
.2 "Areas of moderate fire hazard" referred to in tables 7.4-1 and 7.4-2 by B, include the following spaces:
Auxiliary machinery spaces, as defined in 1.4.3
Bond stores containing packaged beverages with alcohol content not exceeding 24% by volume
Crew accommodations
---CHUNK---
SOURCE: MSC.36(63).pdf
and 7.4-2 by B, include the following spaces:
Auxiliary machinery spaces, as defined in 1.4.3
Bond stores containing packaged beverages with alcohol content not exceeding 24% by volume
Crew accommodations
Service spaces
.3 "Areas of minor fire hazard" referred to in tables 7.4-1 and 7.4-2 by C, include the following spaces:
Auxiliary machinery spaces, as defined in 1.4.4
Cargo spaces
Fuel tank compartments
Public spaces
Tanks, voids and areas of little or no fire risk
.4 "Control stations" referred to in tables 7.4-1 and 7.4-2 by D, as defined in 1.4.13 .
. 5 "Evacuation stations and external escape routes" referred to in tables 7.4-1 and 7.4-2 by E, include the following areas:
External stairs and open decks used for escape routes
Muster stations, internal and external
Open deck spaces and enclosed promenades forming lifeboat and liferaft embarkation and lowering stations
The craft's side to the waterline in the lightest seagoing condition, superstructure and deckhouse sides situated below and adjacent to the liferaft's and evacuation slide's embarkation areas
.6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 by F, include the following areas:
---CHUNK---
SOURCE: MSC.36(63).pdf
condition, superstructure and deckhouse sides situated below and adjacent to the liferaft's and evacuation slide's embarkation areas
.6 "Open spaces" referred to in tables 7.4-1 and 7.4-2 by F, include the following areas:
W/1576n/pp/EWP
Open spaces locations other than evacuation stations and external escape routes and control stations.
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 56
-
N-e~ of rraj a-
f 1r-e /'"e%lr'O
.o.r.e~ of /Tcc::):"I dte
f'ire t-czlr'O
..
.Are=~ of' min::r
f ire ~z:rd..
-

CO"1r:rc! ~tct!cn.
A
6
c
0
e:
e:~ticn stdticns
~e~ n:ut".
,
F
Open Spaces
WI1576n/pp/EWP
Table 7.4-1
STRUCTURAL FIRE PROTECTION TIMES FOR
SEPARATING BULKHEADS AND DECKS
OF PASSENGER CRAFT
/
A
I e I c /. . 0 -/ e: I F
IN. I~ I~~I~' ~ , 2 I ,8 I ' I I 7 I .)
-
IN ~ ~~~ ~
I~ ~~~
N~G;·
~-
- " ". :5
,
I~~
. .
~
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 8
N"ees of ~'"1!It~
of 1re t"azlrd
c
o
E
EVBCUSticn .tat1a1.
~ ~n:ute.
Open Spaces F
W/1576n/pp/EWP
Table 7.4-2
---CHUNK---
SOURCE: MSC.36(63).pdf
. .
~
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 8
N"ees of ~'"1!It~
of 1re t"azlrd
c
o
E
EVBCUSticn .tat1a1.
~ ~n:ute.
Open Spaces F
W/1576n/pp/EWP
Table 7.4-2
STRUCTURAL FIRE PROTECTION TIMES FOR
SEPARATING BULKHEADS AND DECKS
OF CARGO CRAFT
MSC 63/23/Add.2
ANNEX 18
Page 57
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 58
~:
The figures on either side of the diagonal line represent the required structural fire protection time for the protection system on the relevant side of the division.

1 The up