7.6.2, 7.7.1 and 7.7.4. The text of such
plans* should be in the official language of the flag State.
* Refer to Graphical symbols for fire control plans adopted by the Organization by resolution A.654(16).
W/1576n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 76
7.9.2
7.9.3
7.9.3.1
7.9.3.2
7.9.3.3
However, if the language is neither English nor French, a translation into one of those languages should be included.
A duplicate set of fire control plans or a booklet containing such plans should be permanently stored in a prominently marked weathertight enclosure outside the deckhouse for the assistance of
---CHUNK---
SOURCE: MSC.36(63).pdf
A duplicate set of fire control plans or a booklet containing such plans should be permanently stored in a prominently marked weathertight enclosure outside the deckhouse for the assistance of shore side fire-fighting personnel.
Openings in fire-resisting divisions
Except for the hatches between cargo, special category, store, and baggage spaces and between such spaces and the weather decks, all openings should be provided with permanently attached means of closing which should be at least as effective for resisting fires as the divisions in which they are fitted.
It should be possible for each door to be opened and closed from each side of the bulkhead by one person only.
Fire doors bounding major fire hazard areas and stairway enclosures should satisfy the following requirements:
.1 The doors should be self-closing and be capable of closing with an angle of inclination of up to 3.5 0 opposing closure, and should have an approximately uniform rate of closure of no more than 40 s and no less than 10 s with the craft in the upright position •
. 2 Remote-controlled sliding or power-operated doors should be
---CHUNK---
SOURCE: MSC.36(63).pdf
and should have an approximately uniform rate of closure of no more than 40 s and no less than 10 s with the craft in the upright position •
. 2 Remote-controlled sliding or power-operated doors should be equipped with an alarm that sounds at least 5 s but no more than 10 s before the door begins to move and continue sounding until the door is completely closed. Doors designed to reopen upon contacting an object in their paths should reopen sufficiently to allow a clear passage of at least 0.75 m, but no more than 1 m •
. 3 All doors should be capable of remote and automatic release from a continuously manned central control station, either simultaneously or in groups, and also individually from a position at both sides of the door. Indication should be provided at the fire control panel in the continuously manned control station whether each of the remote-controlled doors is closed. The release mechanism should be so designed that the door will automatically close in the event of disruption of the control system or central power supply. Release switches should have an on-off function to prevent automatic resetting
---CHUNK---
SOURCE: MSC.36(63).pdf
closed. The release mechanism should be so designed that the door will automatically close in the event of disruption of the control system or central power supply. Release switches should have an on-off function to prevent automatic resetting of the system. Hold-back hooks not subject to control station release should be prohibited .
. 4 Local power accumulators for power-operated doors should be provided in the immediate vicinity of the doors to enable the doors to be operated at least ten times (fully opened and closed) using the local controls.

.5 Double-leaf doors equipped with a latch necessary to their fire integrity should have a latch that is automatica