return inflation valve on each compartment: and
Refer to the Recommendation on the use and fitting of retro-reflective materials on life-saving appliances adopted by the Organization by resolution A.658(16).
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 217
.2 the buoyancy chambers should be so arranged that in the event of one
---CHUNK---
SOURCE: MSC.36(63).pdf
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 63/23/Add.2
ANNEX 18
Page 217
.2 the buoyancy chambers should be so arranged that in the event of one of the compartments being damaged or failing to inflate, the intact compartment should be able to support, with positive freeboard over the open reversible liferaft's entire periphery, the number of persons which the liferaft is permitted to accommodate, . each having a mass of 75 kg and seated in their normal positions.
2.6 The floor of the open reversible liferaft should be waterproof.
2.7 The open reversible liferaft should be inflated with a non-toxic gas by an inflation system complying with the requirements of regulati6n III/39 of the Convention. Inflation should be completed within the period of one minute at an ambient temperature of between 18°C and 20°C and within a period of three minutes at an ambient temperature of -18°C. After inflation the open reversible liferaft should maintain its form when loaded with its full complement o f persons and equipment.
---CHUNK---
SOURCE: MSC.36(63).pdf
three minutes at an ambient temperature of -18°C. After inflation the open reversible liferaft should maintain its form when loaded with its full complement o f persons and equipment.
2.8 Each inflatable compartment should be capable of withstanding a pressure equal to at least three times the working pressure and should be prevented from reaching a pressure exceeding twice the working pressure either by means of relief valves or by a limited gas supply. Means should be provided for fitting the topping-up pump or bellows.
2.9 The surface of the buoyancy tubes should be of non-slip material. At least 25% of these tubes should be of a highly visible colour.
2.10 The number of persons which an open reversible liferaft should be permitted to accommodate should be equal to the lesser of:
.1 the greatest whole number obtained by dividing by 0.096 the volume, measured in cubic metres of the main buoyancy tubes (which for this purpose should not include the thwarts if fitted) when inflated; or
. 2 the greatest whole number obtained by dividing by 0.372 the inner horizontal cross-sectional area of the open reversible liferaft
---CHUNK---
SOURCE: MSC.36(63).pdf
purpose should not include the thwarts if fitted) when inflated; or
. 2 the greatest whole number obtained by dividing by 0.372 the inner horizontal cross-sectional area of the open reversible liferaft
measured in square metres (which for this purpose may include the thwart or thwarts, if fitted) measured to the innermost edge of the buoyancy tubes; or
.3 the number of persons having an average mass of 75 kg, all wearing lifejackets, that can be seated inboard of the buoyancy tubes without interfering with the operation of any of the liferaft's equipment.
3 Open reversible liferaft fittings
3.1 Lifelines should be securely becketed around the inside and outside of the open reversible liferaft.
3.2 The open reversible liferaft should be fitted with an efficient painter of a length suitable for automatic inflation on reaching the water. For open reversible liferafts accommodating more than 30 persons an additional bowsing-in line should be fitted.
W/1689n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY