pted by the Organization.
** This requirement can be met by INMARSAT ship earth stations capable of two-way communications, such as Standard-A and B (resolution A.698(17» or Standard-C (resolution A.663(16» ship earth stations. Unless otherwise specified, this footnote applies to all requirements for an INMARSAT ship earth station prescribed by this chapter.
W/16B7n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated.
---CHUNK---
SOURCE: MSC.36(63).pdf
ANNEX lB
Page 136
14.7.2
14.7.3
14. B
l4.B.l
.5.2 ,the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated.
The VHF radio installation, required by 14.6.1.1, should also be capable of transmitting and receiving general radiocommunications using radiotelephony.
Craft engaged on voyages exclusively in sea area Al may carry, in lieu of the satellite EPIRB required by 14.6.1.6, an EPIRB which should be:
.1 capable of transmitting a distress alert using DSC on VHF channel 70 and providing for locating by means of a radar transponder operating in the 9 GHz band;
.2 installed in an easily accessible position;
.3 ready to be manually released and capable of being carried by one person into a survival craft;
.4 capable of floating free if the craft sinks and of being automatically activated when afloat; and
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged on voyages beyond sea area AI, but remaining within sea area A2,
---CHUNK---
SOURCE: MSC.36(63).pdf
.5 capable of being activated manually.
Radio egui!?ment - Sea areas Al and A2
In addition to meeting the requirements of 14.6, every craft engaged on voyages beyond sea area AI, but remaining within sea area A2,
should be provided with:
.1 an MF radio installation capable of transmitting and receiving, for distress and safety purposes, on the frequencies:
.1.1 2,187.5 kHz using DSC; and
.1.2 2,182 kHz using radiotelephony;
.2 a radio installation capable of maintaining a continuous DSC watch on the frequency 2,187.5 kHz which may be separate from, or combined with, that required by 14.8.1.1.1; and
.3 means of initiating the transmission of ship-to-shore distress alerts by a radio service other than MF operating either:
.3.1 through the polar orbiting satellite service on 406 MHz; this requirement may be fulfilled by the satellite EPIRB, required by 14.6.1.6, either by installing the satellite EPIRB close to, or by remote activation from, the position from which the craft is normally navigated;
or
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)

ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2
14.8.3
14.8.4
14.9
---CHUNK---
SOURCE: MSC.36(63).pdf
the position from which the craft is normally navigated;
or
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT 14.8.2
14.8.3
14.8.4
14.9
14.9.1
.3.2
.3.3
.3.3.1
.3.3.2
on HF using DSC; or
MSC 62123/Add.2
ANNEX 18
Page 137
through the INMARSAT geostationary satellite service;
this requirement may be fulfilled by:
the equipment specified in 14.8.3.2; or
the satellite EPIRB, required by 14.6.1.6, either
by installing the satellite EPIRB close to, or by remote
activation from, the position from which the craft is
normally navigated.
It should be possible to initiate transmission of distress alerts by
the radio installations specified in 14.8.1.1 and 14