to
override the automatic shutdown except in cases where there is a
risk of complete breakdown or explosion.
* Refer to the Code on alarms and indicators adopted by the Organization by
resolution A.686(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
---CHUNK---
SOURCE: MSC.36(63).pdf
risk of complete breakdown or explosion.
* Refer to the Code on alarms and indicators adopted by the Organization by
resolution A.686(17).
W/1687n/pp/EWP
RESOLUTION MSC.36(63)
(adopted on 20 May 1994)
ADOPTION OF THE INTERNATIONAL CODE OF SAFETY
FOR HIGH SPEED CRAFT MSC 62/23/Add.2
ANNEX 18
Page 110
12.1
12.1.1
12.1. 2
12.1. 3
12.1. 4
12.1. 5
12.2.
12.2.1
CHAPTER 12 - ELECTRICAL INSTALLATIONS
PART A - GENERAL
General
Electrical insta11ations* should be such that:
.1 all electrical auxiliary services necessary for maintaining
the craft in normal operation and habitable conditions will be
ensured without recourse to the emergency source of electrical
power;
.2 electrical services essential for safety will be ensured under
various emergency conditions; and
. 3 the safety of passengers, crew and craft from electrical
hazards will be ensured.
The FMEA should include the electrical system, taking into account
the effects of electrical failure on the systems being supplied. In
cases where faults can occur without being detected during routine
checks on the installations, the analysis should take into account
---CHUNK---
SOURCE: MSC.36(63).pdf
the effects of electrical failure on the systems being supplied. In
cases where faults can occur without being detected during routine
checks on the installations, the analysis should take into account
the possibility of faults occurring simultaneously or consecutively.
The electrical system should be designed and installed so that the
probability of the craft being at risk of failure of a service is
extremely remote.
Where loss of particular essential service would cause serious risk
to the craft, the service should be fed by at least two independent
circuits fed in such a way that no single failure in the electrical
supply or distribution systems would effect both supplies.
The securing arrangements for heavy items, i.e. accumulator
batteries, should, as far as practicable, prevent excessive movemen'
during the accelerations due to grounding or collision.
Precautions should be taken to minimize risk of supplies to
essential and emergency services being interrupted by the
inadvertent or accidental opening of switches or circuit breakers.
Main so u rce o f electrical p~
A main source of electrical power of sufficient capacity to supply
---CHUNK---
SOURCE: MSC.36(63).pdf
essential and emergency services being interrupted by the
inadvertent or accidental opening of switches or circuit breakers.
Main so u rce o f electrical p~
A main source of electrical power of sufficient capacity to supply
all those services mentioned in 12.1.1 should be provided. The main
source of electrical power should consist of at least two generating
sets.
Refer to the recommendations published by the International
Electrotechnical Commission and, in particu,lar, Publication 92 -
Electrical installations in ships.

The capacity of these generating sets should be such that in the event of anyone generating set being stopped or failing it will still be possible to supply those services necessary to provide the normal operational conditions of propulsion and safety. Minimum comfortable conditions of habitability should also be ensured which include at least adequate services for cooking, heating, domestic
---CHUNK---
SOURCE: MSC.36(63).pdf
normal operational conditions of propulsion and safety. Minimum comfortable co